

EYE CLINIC (233)**1 - RECEPTION AREA****1 - WRC01 - Waiting**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.

2 - RECP1 - Reception

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	2	VV	Telephone, desk, multiple line.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	2	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.

3 - TLTU1 - Toilet, Public

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.

A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

2 - PATIENT AREA

1 - EYOT2 - Exam / Treatment Room, Optometry

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5016	Desk, Refraction w/console, w/o Sink	1	VC	The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.
M5530	Lamp, Slit, w/Applanation Tonometer	1	VV	Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.
M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.
M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

2 - EYOT2 - Exam / Treatment Room, Ophthalmology

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5016	Desk, Refraction w/console, w/o Sink	1	VC	The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.
M5530	Lamp, Slit, w/Applanation Tonometer	1	VV	Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.
M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

3 - WRC01 - Waiting, Dilation

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.

4 - EYVF1 - Visual Fields Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1016	Telephone, Desk, With Speaker	1	VV	Telephone, desk, with speaker.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	1	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
F0300	Chair, Task, Swivel, With Arms	1	VV	Task chair, approximately 34" H X 26" W X 22" D with adjustable arms and a five caster adjustable swivel base. Seat and back are foam padded and upholstered in woven fabric or vinyl.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.
M5500	Autorefractor, Ophthalmic	1	VV	Ophthalmic autorefractor. Unit is a tabletop model consisting of a instant display TV monitor, forehead rest, measuring head, height adjustment ring, and joystick lever. It features an automatic fogging and a high speed printer. Designed for visual acuity screening.
M5510	Camera, Fundus, Digital	1	VV	The digital fundus camera system is designed for use in diagnosing and recording ocular disorders. It shall consist of a digital imager, computer, monitor, chin rest, joy stick and software to record, store, edit and print digital images. The system may also include a system table and an adjustable patient table.
M5520	Lensometer	1	VV	Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.
M5555	Perimeter, Automated	1	VV	Automated ophthalmic perimeter. Unit has on screen display for rapid and accurate alignment of patients automatic pupil size measurement, seven different fixation aids, ergonomic chin rest, several threshold strategies, and high target intensity.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.

5 - EYVF1 - Photography Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1016	Telephone, Desk, With Speaker	1	VV	Telephone, desk, with speaker.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	1	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
F0300	Chair, Task, Swivel, With Arms	1	VV	Task chair, approximately 34" H X 26" W X 22" D with adjustable arms and a five caster adjustable swivel base. Seat and back are foam padded and upholstered in woven fabric or vinyl.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.
M5500	Autorefractor, Ophthalmic	1	VV	Ophthalmic autorefractor. Unit is a tabletop model consisting of a instant display TV monitor, forehead rest, measuring head, height adjustment ring, and joystick lever. It features an automatic fogging and a high speed printer. Designed for visual acuity screening.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

M5510	Camera, Fundus, Digital	1	VV	The digital fundus camera system is designed for use in diagnosing and recording ocular disorders. It shall consist of a digital imager, computer, monitor, chin rest, joy stick and software to record, store, edit and print digital images. The system may also include a system table and an adjustable patient table.
M5520	Lensometer	1	VV	Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.
M5555	Perimeter, Automated	1	VV	Automated ophthalmic perimeter. Unit has on screen display for rapid and accurate alignment of patients automatic pupil size measurement, seven different fixation aids, ergonomic chin rest, several threshold strategies, and high target intensity.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.

6 - EYVS1 - Pre-testing Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.

E0945	Cart, Computer, Mobile	1	VV	<p>A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase.</p> <p>This Typical may include:</p> <ul style="list-style-type: none"> 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>
F0340	Stool, Self Adjusting	2	VV	<p>Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.</p>
F2010	Basket, Wastepaper, Step-On	1	VV	<p>"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	<p>Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.</p>
M5027	Table, Multiple Instrument, Ophthalmic	1	VV	<p>A multiple instrument ophthalmic table. This table is designed to hold up to three ophthalmologic instruments allowing the patient to turn only slightly between them for testing. The table top is adjustable from approximately 26" to 38" and facilitates complete wheelchair accessibility to all instruments.</p>
M5500	Autorefractor, Ophthalmic	1	VV	<p>Ophthalmic autorefractor. Unit is a tabletop model consisting of a instant display TV monitor, forehead rest, measuring head, height adjustment ring, and joystick lever. It features an automatic fogging and a high speed printer. Designed for visual acuity screening.</p>
M5570	Armed Forces Vision Tester	1	VV	<p>Armed Forces Vision Tester. Unit is spring balanced for easy height adjustment and has a tension lock. It contains rotating drums for slide alignment and 5 point tests. It is designed to provide accurate vision screening for near point and far point vision. This unit is a special order item normally procured through DSCP. This item is designed for the government and is not available on the open market.</p>

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.
M6045	Corneal Topography Unit	1	VV	Computerized corneal mapping system for pre- and post- surgical diagnosis of astigmatism, refractive error, irregularly shaped corneas and other eye conditions. The unit performs analysis of 5,000 - 6,000 different points on a ring pattern reflected from the patient's cornea to quantify the curvature and contours of the corneal surface.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

7 - EYFD1 - Eyeglass Fitting and Display, and Dispensing Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	<p>This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	<p>Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E1500	Rail, MOD, W/MNTD, HX144XD	2	VV	<p>Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.</p>
F0275	Chair, Swivel, High Back	1	VV	<p>Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.</p>

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5520	Lensometer	1	VV	Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M5735	Warmer, Spectacle, Plastic	1	VV	Plastic spectacle warmer. Bath type. Thermostatically controlled. For use with glass beads or salt.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

8 - XDUS1 - Ultrasound / Optical Coherence Tomography Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
C0036	Rail, Apron, 4x30x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.
C03F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	5	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
E0930	Locker, Supply, 6 Drawers, Mobile, 29"W x 20"D	1	VV	THIS TYPICAL INCLUDES: 1 Mobile Supply Locker 2 Tray/Shelf 4 Drawers, 3"H 2 Drawers, 6"H Drawer Organizer Bins

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

E0945	Cart, Computer, Mobile	1	VV	<p>A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase.</p> <p>This Typical may include:</p> <ul style="list-style-type: none"> 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>
F0355	Footstool, Straight	1	VV	<p>Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.</p>
F2010	Basket, Wastepaper, Step-On	1	VV	<p>"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	<p>Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.</p>
M4255	Stand, IV, Adjustable	1	VV	<p>Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.</p>
M4266	Pump, Volumetric, Infusion, Multiple Line	1	VV	<p>Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.</p>
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	<p>Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.</p>

M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.
M8940	Stool, Anesthesia, With Back	1	VV	Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.
X2100	Scanner, Ultrasound, General Purpose	1	VV	High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse and continuous wave imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.

9 - EYOT2 - Eye Procedure Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0945	Cart, Computer, Mobile	1	VV	<p>A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase.</p> <p>This Typical may include:</p> <ul style="list-style-type: none"> 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>
F0340	Stool, Self Adjusting	1	VV	<p>Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.</p>
F2010	Basket, Wastepaper, Step-On	1	VV	<p>"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>
M5016	Desk, Refraction w/console, w/o Sink	1	VC	<p>The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.</p>
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	<p>Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.</p>
M5530	Lamp, Slit, w/Aplplanation Tonometer	1	VV	<p>Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.</p>

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.
M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

10 - TREY2 - Laser Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0041	Rail, Apron, 4x60x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C03P0	Cabinet, Sink, U/C/B, 2 Door, 30" W	1	CC	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS090	Sink, SS, Single Compartment, 7.5x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.

E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	<p>THISTYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface</p>
E0903	Locker, Supply, w/Shelves, Wall Mtd, 23" W x 20" D	1	VV	<p>THISTYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an E0921 to transport the locker from place to place.</p>
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	<p>Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.</p>
F0205	Chair, Side With Arms	1	VV	<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>
F0280	Chair, Swivel, Low Back	1	VV	<p>Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1620	Holder, Chart, Patient, Wall or Door Mounted	1	VV	<p>Wall or door mounted patient chart holder. Constructed of durable plastic or metal. Used for holding patient records. Size as required.</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>
M5030	Stool, Surgeon, Revolving	1	VV	<p>Revolving stool. Consists of a padded upholstered seat with height adjustment. Unit rotates and is mounted on ball bearing swivel casters. Designed for use in examinations, treatment, and surgical procedures.</p>
M5515	Laser System w/Slit Lamp or Ophthalmoscope	1	VV	<p>Dual delivery ophthalmic laser system. Unit allows rapid switching between two laser delivery systems. The unit includes safety goggles and a slit lamp or an indirect ophthalmoscope, both with high visibility safety filters.</p>
M5545	Ophthalmometer/Keratometer	1	VV	<p>Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.</p>

M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.
M8900	Carriage, Pail, CRS, Without Pail	1	VV	Carriage, pail (kick bucket) CRS. Consists of a stainless steel ring type carriage mounted on ball bearing casters. Includes circular non-marring bumper. For use in the surgical operating room.
M8905	Pail, Utility, CRS, With Carriage	1	VV	Utility pail (kick bucket). Shall be a stainless steel 12 quart bucket for use in surgical operating rooms.
M8925	Stand, Basin, CRS, Mobile, Single	1	VV	Mobile single basin stand with shelf. The stand shall be constructed of tubular stainless steel and mounted on 2" swivel casters. Shall include a shelf and an 8 quart stainless steel basin. Intended for use in ORs and treatment areas.
S4800	Sterilizer, SURG INSTRU & Dressing, 10" DIA CHMBR	1	VV	A self-contained, countertop mounted, electrically heated, steam sterilizer. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides visual indication of cycle stages and deviations. A printer-recorder documents and records each cycle performance. For low volume, convenient, steam sterilization of liquids, media, instruments, glassware, and absorbent materials, in clinics and other areas of the health care facility.

11 - EYER1 - Electrodagnosis Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M4915	Chair, Exam/Treatment, ENT, w/Adjustable Light	1	VV	ENT exam/treatment chair with adjustable light. Chair can be rotated 330 degrees locking at desired position. Unit is electrically powered for precise positioning and has an adjustable headrest and armrest. It may include an adjustable gooseneck light. Unit is designed for use during examinations, treatments, and minor procedures.
M5555	Perimeter, Automated	1	VV	Automated ophthalmic perimeter. Unit has on screen display for rapid and accurate alignment of patients automatic pupil size measurement, seven different fixation aids, ergonomic chin rest, several threshold strategies, and high target intensity.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.
M5580	Tonometer, Applanation	1	VV	Applanation tonometer. Unit is designed to be used in conjunction with a slit lamp. It provides direct pressure reading in mm of mercury. No adjustment is required on guide plate of slit lamp. Used for mass screening, checking of tensions of glaucoma patients, diagnosis of glaucoma and diurnal pressure curves.
M5605	Retinoscope, Streak	1	VV	Streak retinoscope. Lightweight instrument with interchangeable heads, rechargeable battery handle, mirror, forehead rest and one halogen lamp. Continuous 360-degree streak rotation.
M6050	Retinal Imaging System, Fluorescein/Indocyanine	1	VV	Digital camera system for conducting fluorescing and indocyanine green studies of the choroid of the retina. The infrared sensitive camera has interchangeable barrier and exciter filters for the different dyes. The camera transmits images to a high resolution computer system and monitors for viewing, analysis, enhancement, manipulation, recording and color printing. Database reflects pricing and physical characteristics for the entire system with its required computer.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

12 - EYOT2 - Exam / Training Room, Low Vision				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5016	Desk, Refraction w/console, w/o Sink	1	VC	The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.
M5530	Lamp, Slit, w/Applanation Tonometer	1	VV	Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.
M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.

M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

13 - EYOT2 - Training Room, Low Vision / Polytrauma

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0945	Cart, Computer, Mobile	1	VV	<p>A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase.</p> <p>This Typical may include:</p> <ul style="list-style-type: none"> 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>
F0340	Stool, Self Adjusting	1	VV	<p>Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.</p>
F2010	Basket, Wastepaper, Step-On	1	VV	<p>"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>
M5016	Desk, Refraction w/console, w/o Sink	1	VC	<p>The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.</p>
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	<p>Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.</p>
M5530	Lamp, Slit, w/Aplplanation Tonometer	1	VV	<p>Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.</p>

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.
M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

14 - EYCL1 - Patient Education / Contact Lens Dispensing Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.

				Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Consider the need for an E0921 to transport the locker from place to place.
E1500	Rail, MOD, W/MNTD, HX144XD	2	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5525	Lensometer, Soft Contact	1	VV	Soft contact lensometer. Unit features lens holder, external scale, prism holder, prism axis from 0 to 180 degree, external power, printer and axis readings with an American style cross-line target. Used for measuring soft and hard contact lenses as well as conventional spectacle lenses.
M5565	Radiuscope	1	VV	Ophthalmic radiuscope. Unit consists of a fine compound microscope with concentric coarse and fine focusing adjustments. It includes a 6.5 V lamp, monochromatic filter, two lens mount and a built-in variable voltage selector. For contact lenses measuring and inspection.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

3 - SUPPORT AREA

1 - UCCL1 - Supply Room, Clean				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
E0903	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an E0921 to transport the locker from place to place.
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
P8710	Utility Center, Plumbing Connection	1	CC	Plumbing connection utility center, sometimes referred to as a 'GUY GRAY BOX'. This recessed utility center provides for hot and cold water connections and a drain connection at sink and other equipment locations. The utility center includes cutoff valves for the water connections, a plug seal for the drain and an outside cover to provide an aesthetic appearance when connections are no longer required. This center may be installed in locations where no plumbing fixtures are included in a design as a future flexibility device, saving many dollars for later facility modifications to incorporate sinks as functions change.

2 - USCL1 - Utility Room, Soiled				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS200	Sink, SS, Single Compartment, 12x28x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT050	Countertop, Stainless Steel	7	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.

M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

3 - MEDP1 - Medication Preparation Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.

CS250	Sink, SS, Single Compartment, 6x12x9 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	8	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3150	Distribution System, Medication, Automatic	2	VV	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.

4 - SRE01 - Storage, Equipment

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

5 - RCA01 - Storage Alcove, Medical Equipment				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.
M1110	Resuscitator, Bag-Mask, Hand Op, Infant	1	VV	Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M7905	Oximeter, Pulse	1	VV	Pulse oximeter for continuous surveillance of patient pulse and oxygen saturation rates. Instrument features LED display, audio and visual alarms, automatic calibration and battery operation in case of power failure. Other applications include sleep studies, exercise testing and monitoring certain patients in the home (e.g. infants or patients requiring respiratory therapy).
M8770	Aspirator/Pressure Unit, General Purpose	1	VV	General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes.
6 - SRLW1 - Storage Alcove, Wheelchair				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION

M4705	Wheelchair, Patient Transport, Folding	1	VV	Folding patient transport wheelchair. Constructed of chrome plated steel with detachable armrest and footrests. Unit has heavy duty front casters with sealed radial high-precision ball bearing assembly. Unit is used for patient transport.
M4710	Wheelchair, Patient, Bariatric, Transport, Folding	1	VV	Folding bariatric patient transport wheelchair with a capacity of at least 500 lbs. Constructed with a heavy duty steel frame and double cross brace, with detachable armrest and swing away footrests. Unit has heavy duty front casters and rear wheels with precision wheel bearings in front and rear assembly. Unit is used for patient movement.

7 - SRS01 - Storage, Eyeglass Frame

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

8 - JANC1 - Housekeeping Aides Closet (HAC)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.

P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

4 - STAFF AND ADMINISTRATIVE AREA

1 - OFA09 - Office, Ophthalmology / Optometry Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
				THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - OFA09 - Office, Ophthalmology Service Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

3 - OFA09 - Office, Optometry Service Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

4 - SEC01 - Secretary / Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	<p>This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0305	Chair, Waiting Room, Single	2	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

5 - OFA07 - Workstation, Clerical

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

6 - OFA07 - Workstation, Eyecare Provider

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

7 - OFD04 - Office, Social Work / Intake/ Adjustment Counseling

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	<p>This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0115	Bookcase, Open, 5 Shelf	1	VV	<p>Freestanding open shelf bookcase, approximately 82" high X 37" wide X 18" deep with 5 (five) adjustable shelves. Unit can be separate or part of a system with available add-on shelving.</p>
F0205	Chair, Side With Arms	1	VV	<p>Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.</p>
F0275	Chair, Swivel, High Back	1	VV	<p>Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.</p>
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	<p>Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>

8 - WRCH1 - Nurse Workroom

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	2	VV	Telephone, desk, 1 line.
E0042	Workcenter, Computer, Free Standing, 48" W	2	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0275	Chair, Swivel, High Back	4	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0750	Table, Office, (size as required)	1	VV	Office table, sized as required. May be used as either a four (4) to six (6) person conference table or as an extra work surface area.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

9 - SRE01 - Support Equipment Area

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

10 - RECP3 - Reception

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

11 - OFA09 - Office, Nurse Manager

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

12 - OFA07 - Workstation, Administration

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
13 - XVC01 - Consult Room / Viewing Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0117	Workstation, Straight, Free Standing, 48" W	1	VV	<p>This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces.</p> <p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	<p>Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>

X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.
-------	---	---	----	--

14 - CRA01 - Conference Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0220	Chair, Conference	8	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation, approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0755	Table, Conference, Wood	1	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.

M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	1	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.

15 - SL001 - Lounge, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.
M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.

16 - LR001 - Locker Room, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	4	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.

17 - TLTU1 - Toilet, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.

A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

5 - EDUCATION AREA

1 - OFA09 - Office, Ophthalmology Residency Director

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - OFA09 - Office, Optometry Residency Director

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

3 - CRA02 - Conference Room / Classroom

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

EYE CLINIC (233) - Contents - VA PG-18-5 (18 Jul 2016 04:55PM ET)

A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0220	Chair, Conference	10	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
F0295	Chair, Stacking	8	VV	Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending upon the model selected. These chairs are intended primarily as overflow capacity for conference rooms.
F0600	Credenza, Executive, Wood	1	VV	Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with adjustable shelf and floor glides.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0755	Table, Conference, Wood	2	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.
F2005	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.