

NUCLEAR MEDICINE SERVICE (252)

1 - RECEPTION AREA

1 - WRC01 - Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.

2 - RECP1 - Reception

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	2	VV	Telephone, desk, multiple line.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	2	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.

3 - CLSC1 - Patient Education Kiosk / Alcove

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M1890	Kiosk, Educational, Stand-Up	1	VV	A free standing Kiosk providing educational information for patients. The kiosk will, as a minimum, include a computer, an LCD display of approximately 19" with a touch screen, keyboard with track ball, speakers, printer, card reader, bar code scanner and housed in a durable steel enclosure. The unit will contain all necessary software packages to satisfy a wide spectrum of information distribution. Final configuration of kiosk will be determined at time of purchase.

4 - TLTU1 - Toilet, Public

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

2 - PATIENT AREA

1 - WRC01 - Sub-Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.

2 - PAIA1 - Patient Interview Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0205	Chair, Side With Arms	2	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

3 - NM GS1 - Scanning Room, NM

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.
E0963	Cart, General Storage, Mobile	1	VV	Mobile General Storage Cart, approximately 72"H x 23"W x 22"D. THIS TYPICAL INCLUDES: 1 Locker Storage Container on Wheels, w/Solid Door 3 Tray/Shelves 2 Drawers, 3"H 4 Drawers, 6"H 1 Tray/Shelf Divider Drawer Organizer Bins
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.
X9830	Scanner, Nuclear, SPECT, Dual Head	1	VC	The system shall be a single plane or variable angle dual detector emission system, designed for fast data acquisition and high patient throughput for Single Photo Emission Computed Tomography (SPECT), whole body and general purpose nuclear medicine procedures. It shall be designed to image at any energy range for any procedure. The unit detects and counts photons emanating from radiopharmaceuticals. Collimators available to suit full range applications. The system shall be DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations.

4 - NM CR1 - Computer Imaging Processing Area

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.

E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4112	Console, PACS, Remote View, w/Two 2MP Monitors	1	VV	Two monitor remote viewing station for picture archiving and retrieval (PACS) system. This station is for use by providers inside or outside of radiology to review images. Station includes local image storage, image manipulation, and simultaneous display of multiple images on two 1200 x 1600 image display monitors. Images are stored on a resident hard disk and roll off the disk as more recent images are sent to the station. Provider may request images from the PACS. Unit must be connected to the PACS by LAN for image and result receipt. This station is for use in areas like radiologist's offices and the E.R. where a more comprehensive system is required. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.
X4160	Information System, DIN-PACS	1	VC	The Digital Imaging Network – Picture Archiving and Communications System (DIN-PACS) is an open system network of digital devices designed for the acquisition, transmission, display and management of diagnostic imaging studies. Equipment for DIN-PACS will include workstations, storage devices, servers, interconnecting cables, and all software, hardware, firmware and ancillary devices required for full functionality. Systems will meet DICOM and HL7 standards. Turnkey installation and integration with existing networks and legacy systems is required. Size of system is based on volume of exams taken and file size. Equipment configuration and site preparation, if required, is unique and specific to each medical facility.

5 - CMP01 - Data Processing Equipment				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A0900	Relay Rack, Aluminum	2	VV	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).
A0901	Cable Management, Horizontal Base Unit	2	VV	Horizontal cable management unit for a 19" rack with a channel approximately 2"x2". Provides for professional finish to hide cables in a switch rack. Various models are quoted with fingered type exits or brackets and/or rear access holes.
A0902	Rear Wire Frame	2	VV	For use with horizontal base unit for double sided management. This item is intended to be used with JSNs A0901 and/or A0903 model HC219 series from Hubbell only.
A0903	Rear Hinged Cover, for LAN Rack	2	VV	This item is intended to be used with JSNs A0901 and/or A0902 model HC219 series from Hubbell only.
A0904	Fiber Optic Cabinet, 36 Port, Rack Mounted	2	VV	This cabinet is designed to accommodate up to 6 six-packs of adapters or blank panels. This cabinet is specifically designed to accommodate Hubbell adapter panels as reflected in JSNs A0905 and A0906.
A0905	Adapter Panel With Couplers, Blue, 6 Port, SM/MM	2	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style blue adapters, standard density.
A0906	Adapter Panel With Couplers, Yellow, 6 Port, SM/MM	2	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style Yellow adapters, standard density.
A0908	Patch Panel, 110 Block/RJ45, Cat 5E, 48 Port,568A	1	VV	This 48 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI).
A0910	Patch Panel, 110 Block/RJ45, Cat 5E, 96 Port,568A	2	VV	This 96 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI).
A0911	Power Supply, Uninterruptable, Rack Mounted	2	VV	Uninterruptable Power Supply, Approximately 2200VA/1600W, Rack Mount with extendable Run Time. Unit must incorporate hot user swappable batteries and must have an overload indicator, replace battery indicator, audible alarm, automatic voltage regulation and include Smart Slot card and software. It must use RS232 DB-9 interface for communication. NEMA L5-30P power connector, and (8) NEMA 5-15R outlets.
A0913	Switch, Local Area Network (LAN)	1	VV	Omni switch router, 9 slot chassis, 725W AC power supply and rack mount brackets. Supports high speed frame switching fabric. Software and Manual included. Requires management module JSN A0914 and works with Power Supply A0915.
A0914	Management Processor Module for LAN Switch	1	VV	Management processor module with 10BaseT with layer-3 switching (HRE-X); 32 MB DRAM & 8 MB flash memory. Operates over the 22G distributed switching fabric. Works with Switch LAN JSN A0913 and Power Supply A0915.
A0915	Power Supply, 725 W, for LAN Switch	1	VV	725 Watt powersupply. Redundant or spare power supply for the 9 slot Omni Switch Router. Works with Switch LAN JSN A0913 and Management Processor JSN A0914.
A0916	Switching Module, Desktop, Fast Ethernet	1	VV	High Density Fast Ethernet desktop switching module. Thirty-two 10/100Base TX switching ports, RJ-45 connectors. Supports Cat 5 twisted pair cable-100 ohm and CAM support for 1024 MAC addresses.
A0917	Switching Module, MM Fiber, Gigabit Ethernet Server	1	VV	Gigabit Ethernet server switching module. Four 1000 base SX switching ports, SC connectors. Supports multi-mode fiber optic cable and CAM support for 4096 MAC addresses. Must be used in the Omni Switch/Router product only.

A0918	Switching Module, SM, Gigabit Ethernet Server	1	VV	Gigabit Ethernet server switching module. Four 1000 Base LX switching ports, SC connectors. Supports single mode fiber optic cable and CAM support for 4096 MAC addresses. Must be used in the Omni Switch/Router product only.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A6200	Uninterruptible Power Supply, Three Phase	1	CC	Uninterruptible power supply (UPS) available in 208, 480 or 600 VAC configuration. Used in areas where power protection is required for large computer systems, communication equipment, radiographic equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

6 - XVC01 - Reading and Consultation Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray

E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.

7 - EXRG1 - Patient Examination Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismantling of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismantling equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins

E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

8 - NMIR1 - Patient Dose Administration Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C03J0	Cabinet, U/C/B, 8 Half Drawers, 36x30x22	1	CC	Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C03L0	Cabinet, U/C/B, 1 DR, 3 Half DR, 1 Door, 30" W	1	CC	Standing height under counter base cabinet, 34" H x 30" W x 22" D with a full width drawer above three half width drawers alongside a solid right or left door/cupboard (appropriate door/cupboard configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	2	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS140	Sink, SS, Single Compartment, 10x14x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1410	Chair, Laboratory, Blood Drawing, w/Storage	1	VV	Laboratory blood drawing chair with storage. Chair has built-in storage cabinet(s) and locking arm assembly that may be positioned on either side of the fiberglass chair.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M5030	Stool, Surgeon, Revolving	1	VV	Revolving stool. Consists of a padded upholstered seat with height adjustment. Unit rotates and is mounted on ball bearing swivel casters. Designed for use in examinations, treatment, and surgical procedures.
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.
M8830	Table, Instrument/Dressing, Mobile	1	VV	Mobile instrument/dressing table, approximately 34" H x 20" W x 16" D Corrosion resistant stainless steel mobile table with sound-deadening shelf and drawer. Unit is mounted on 2" casters. Designed for all purpose use in the hospital or clinic.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.

9 - NMUR1 - Thyroid Uptake Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.
C03F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C03H0	Cabinet, U/C/B, 2 Half Drawers, 3 DR, 36x30x22	1	CC	Standing height under counter base cabinet with two half width drawers side-by-side above three full width drawers. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C03J0	Cabinet, U/C/B, 8 Half Drawers, 36x30x22	1	CC	Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C03P0	Cabinet, Sink, U/C/B, 2 Door, 30" W	1	CC	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS090	Sink, SS, Single Compartment, 7.5x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	9	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L2191	Calibrator, Radioisotope	1	VV	Radioisotope dose calibrator. The characteristics/components include a self test feature that verifies the operation of the entire unit, continuous or on demand activity measurement, 0.1-199.9 micro Curie resolution range, response time less than 5 seconds, a hermetically sealed pressurized argon ionization chamber and an accuracy of plus or minus 0.5%. Used to ensure the dose rate of the radioisotope prescribed.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.
X9305	Cabinet, Storage, Lead Lined	1	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.
X9500	System, Uptake, Thyroid, Mobile	1	VV	Mobile thyroid uptake system. The characteristics and components include; amplifier tube assembly and base, uptake stand and collimated shield. This is a mobile unit with arm medical stand, 2 inch probe with I.A.E.A. flat field collimator and thyroid positioner, neck phantom, and analyzer/scaler/timer with automatic background subtract and automatic % readout.

10 - NMRP1 - NM "Hot Lab" / Radiopharmacy

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	2	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	4	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.
C0039	Rail, Apron, 4x48x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C0041	Rail, Apron, 4x60x1	4	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	2	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	2	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CT060	Countertop, Modified Epoxy Resin	44	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	2	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.
F0230	Chair, Drafting, Rotary	3	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	3	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	12	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.

X9315	Safe, Storage, Radium	1	VV	Radium storage safe. The unit assures optimum shielding against exposure to radioisotopes. It is made of steel (CRS) with a minimum of 2 inches of lead lining, has a door key-lock and is fire-proof.
-------	-----------------------	---	----	--

11 - OPPE2 - Cardiac Stress Testing Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	1	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
A6210	Uninterruptible Power Supply, Single Phase	1	VV	Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C03J0	Cabinet, U/C/B, 8 Half Drawers, 36x30x22	1	CC	Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.

CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M8185	System, Stress Exercise, w/Treadmill	1	VV	Stress exercise system with treadmill and respiratory/metabolic assessment. The system includes an ECG amplifier, chart recorder, display, console, treadmill and modules for respiratory/metabolic assessment. Used to determine patient's functional capacity, predict and diagnose cardiopulmonary and vascular diseases and for rehabilitation of patients recovering from leg injuries or other type of illness. Some vendors require a NEMA 5-20R non-locking receptacle for their treadmills.
X9810	System, Camera, Gamma, Mobile	1	VC	Mobile gamma camera system. This unit is a compact scintillation camera system. The characteristics and components include a detector, electronics and a console mounted on a mobile base. The console contains all operating controls and the image display. This unit is used for bedside evaluation of critically ill patients.
X9830	Scanner, Nuclear, SPECT, Dual Head	1	VC	The system shall be a single plane or variable angle dual detector emission system, designed for fast data acquisition and high patient throughput for Single Photo Emission Computed Tomography (SPECT), whole body and general purpose nuclear medicine procedures. It shall be designed to image at any energy range for any procedure. The unit detects and counts photons emanating from radiopharmaceuticals. Collimators available to suit full range applications. The system shall be DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations.

12 - TLTU1 - Toilet, NM Patient				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

13 - DR001 - Dressing Room / Cubicle

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	1	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
14 - ORPP1 - Holding Bay, Patient Stretcher				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1107	Rail System , Utility, Gas and Electric	2	CC	The headwall rail system shall consist of three horizontal rails mounted to the patient room headwall to provide utilities and patient services to support ancillary equipment to include gas and vacuum. The rail system must be capable of quickly adding or relocating medical gases services and be able to accept new equipment, provide physical support to equipment, brackets, shelves and other patient support items.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	34	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0210	Chair, Side, Without Arms	2	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0340	Stool, Self Adjusting	2	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	2	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	2	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	2	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	2	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	VV	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.

M3072	Frame, Infectious Waste Bag w/Lid	2	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4100	Sphygmomanometer, Aneroid, Wall Mounted	2	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.
M4255	Stand, IV, Adjustable	2	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	2	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.
M7040	Table, Overbed	1	VV	Overbed table. Adjustable height table constructed of heavy gauge steel. Mounted on 2" diameter twin swivel casters with bumper caps. Table top is constructed with a high pressure plastic laminated surface that resists chipping, scratching, and staining. It includes a vanity tray and a mirror. Table is designed for use over bed, wheelchair or large chair.
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.
M7845	Monitor, Physiological, Bedside, 4 Channel	2	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

15 - XDBD1 - Bone Densitometry Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X2120	Scanner, Bone Density, Full Body	1	VV	Full body scanner used to determine bone mineral density measurements and vertebral assessment associated with osteoporotic fracture risk.

16 - NM SS1 - PET: Scanning Room, PET / CT

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A6200	Uninterruptible Power Supply, Three Phase	1	CC	Uninterruptible power supply (UPS) available in 208, 480 or 600 VAC configuration. Used in areas where power protection is required for large computer systems, communication equipment, radiographic equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
A6210	Uninterruptible Power Supply, Single Phase	1	VV	Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
C03F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C03P0	Cabinet, Sink, U/C/B, 2 Door, 30" W	1	CC	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	2	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS090	Sink, SS, Single Compartment, 7.5x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	8	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.

E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	<p>THISTYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder</p>
E0912	Locker, Supply, Med Surg, Wall Mtd	1	VV	<p>Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THISTYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.</p>
E0915	Locker, Supply, Medication, Wall Mtd, 23"W x 20"D	1	VV	<p>THISTYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Locked Drawer w/Locked Lid, 6"H 5 Drawers, 3"H 3 Drawers, 6"H 2 Tray/Shelves Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.</p>
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	<p>Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.</p>
F0275	Chair, Swivel, High Back	1	VV	<p>Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.</p>
F0340	Stool, Self Adjusting	1	VV	<p>Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.</p>
F0355	Footstool, Straight	1	VV	<p>Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>

M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.

M4250	Pump, Syringe, Infusion	1	VV	The infusion syringe pump ensures highly accurate volume delivery and consistent flow for small volumes (<50 ml) of pharmacologic agents or thick feeding solutions. It shall be small, lightweight construction, making it transportable. Shall have menu-driven programming capable of flow rates (e.g. 0.1 or 1.0 mL/hr) that are intended for long-term bedside use and/or critical care patient transport, plunger positioning sensor, LCD display for easy viewing, volume limit programming to serve as a convenient cue of volume or dose delivery completion and multiple delivery modes for all applications requiring precisely controlled infusion rates. The infusion pump shall have automatic syringe size sensing which will give the flexibility to accept a wide range of syringe sizes (up to 60 mL) from different manufacturers. Shall be battery powered/AC adapter.
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	1	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
X9805	Stand, Injection, Nuclear Medicine	1	VC	An injection stand designed for arm positioning for radionuclide injections. The arm rest holds the patient's arm firmly in place. A utility tray sits adjacent to the armrest to hold supplies and includes a lead-lined multi syringe holder. The stand height is adjustable approximately from 29" to 44." Casters allow the stand to be rolled into position or out of the way for storage. It is structurally balanced so that it won't tip over.
X9825	Nuclear Imaging System	1	VC	A system that combines the functionality of PET and SPECT with the anatomical landmarks of CT to perform Functional Anatomic Mapping.
X9830	Scanner, Nuclear, SPECT, Dual Head	1	VC	The system shall be a single plane or variable angle dual detector emission system, designed for fast data acquisition and high patient through put for Single Photo Emission Computed Tomography (SPECT), whole body and general purpose nuclear medicine procedures. It shall be designed to image at any energy range for any procedure. The unit detects and counts photons emanating from radiopharmaceuticals. Collimators available to suit full range applications. The system shall be DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations.

17 - NM CR1 - PET: Control Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.

E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4112	Console, PACS, Remote View, w/Two 2MP Monitors	1	VV	Two monitor remote viewing station for picture archiving and retrieval (PACS) system. This station is for use by providers inside or outside of radiology to review images. Station includes local image storage, image manipulation, and simultaneous display of multiple images on two 1200 x 1600 image display monitors. Images are stored on a resident hard disk and roll off the disk as more recent images are sent to the station. Provider may request images from the PACS. Unit must be connected to the PACS by LAN for image and result receipt. This station is for use in areas like radiologist's offices and the E.R. where a more comprehensive system is required. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.
X4160	Information System, DIN-PACS	1	VC	The Digital Imaging Network – Picture Archiving and Communications System (DIN-PACS) is an open system network of digital devices designed for the acquisition, transmission, display and management of diagnostic imaging studies. Equipment for DIN-PACS will include workstations, storage devices, servers, interconnecting cables, and all software, hardware, firmware and ancillary devices required for full functionality. Systems will meet DICOM and HL7 standards. Turnkey installation and integration with existing networks and legacy systems is required. Size of system is based on volume of exams taken and file size. Equipment configuration and site preparation, if required, is unique and specific to each medical facility.

18 - XMRC2 - PET: System Component Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
19 - NMRP1 - PET: Radio Chemistry Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	2	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	4	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.
C0039	Rail, Apron, 4x48x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C0041	Rail, Apron, 4x60x1	4	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	2	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.

CS150	Sink, SS, Single Compartment, 10x19x16 ID	2	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CT060	Countertop, Modified Epoxy Resin	44	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	2	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.
F0230	Chair, Drafting, Rotary	3	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	3	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	12	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.
X9315	Safe, Storage, Radium	1	VV	Radium storage safe. The unit assures optimum shielding against exposure to radioisotopes. It is made of steel (CRS) with a minimum of 2 inches of lead lining, has a door key-lock and is fire-proof.

20 - XTLA1 - PET: Cyclotron

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5215	Bracket, Television, Ceiling Mounted	1	CC	Ceiling mounted television bracket for flat panel LCD and Plasma screens. The bracket shall be a universal style mount with a load capacity of 200 pounds with adjustments of 0-15 degree tilt and 360 degree swivel. Shall be capable of accommodating various size units.
C03F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C03H0	Cabinet, U/C/B, 2 Half Drawers, 3 DR, 36x30x22	1	CC	Standing height under counter base cabinet with two half width drawers side-by-side above three full width drawers. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C03J0	Cabinet, U/C/B, 8 Half Drawers, 36x30x22	1	CC	Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C03P0	Cabinet, Sink, U/C/B, 2 Door, 30" W	1	CC	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	3	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CR070	Cabinet, F/S, 5 Shelf, 1 DO, Sloping Top, 95x24x16	3	CC	Floor standing steel storage cabinet with five adjustable shelves, a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a tall case or a tall cabinet. For general purpose storage use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	10	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F2245	Camera, Video Surveillance, HD, IP Powered	1	VV	A high definition, full functional video surveillance camera. The camera is capable of full 1080p resolution at 30 frames per second while optimizing network usage with H.264, MPEG-4 and JPEG compression formats. Camera will have an open, standards-based design providing a platform for integration and operation as an independent device or as part of a surveillance network.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40" diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
X1415	Laser Positioning System, Patient-Wall	2	VV	Laser positioning system. This unit is designed for accurate patient alignment for radiation therapy. Three vertical laser beams and a horizontal beam intersect to define the iso-center to aid in patient positioning. The unit is generally supplied as a component of various radiation therapy systems.

X8700	Accelerator, Linear, 18 MeV	1	VC	This is a multi-energy linear accelerator. This unit is an isocentrally-mounted, Mega-voltage therapy machine which provides electron therapy in the range 4 to 18 MeV and x-ray therapy at 6 MV and 15 MV. The system consists of the following items: radio frequency (RF), power source (magnetron) and (RF) circuit (isolator, directional coupler, RF load and phase shifter). It also includes an accelerating structure and automatic frequency control system (AFC). The units applications are radiation therapy.
21 - XVC01 - PET: Reading / Staff Consultation Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.

22 - DR001 - PET: Dressing Room / Cubicle

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	1	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

23 - TLTU1 - PET: Toilet, Patient

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.

A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

24 - ORPP1 - PET: Holding Bay, Patient Stretcher

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1107	Rail System , Utility, Gas and Electric	2	CC	The headwall rail system shall consist of three horizontal rails mounted to the patient room headwall to provide utilities and patient services to support ancillary equipment to include gas and vacuum. The rail system must be capable of quickly adding or relocating medical gases services and be able to accept new equipment, provide physical support to equipment, brackets, shelves and other patient support items.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	34	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	2	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0210	Chair, Side, Without Arms	2	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0340	Stool, Self Adjusting	2	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	2	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	2	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	2	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.

M0765	Regulator, Vacuum	2	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	VV	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	2	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4100	Sphygmomanometer, Aneroid, Wall Mounted	2	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.
M4255	Stand, IV, Adjustable	2	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	2	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.
M7040	Table, Overbed	1	VV	Overbed table. Adjustable height table constructed of heavy gauge steel. Mounted on 2" diameter twin swivel casters with bumper caps. Table top is constructed with a high pressure plastic laminated surface that resists chipping, scratching, and staining. It includes a vanity tray and a mirror. Table is designed for use over bed, wheelchair or large chair.

M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.
M7845	Monitor, Physiological, Bedside, 4 Channel	2	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

25 - LBRI1 - BAU: Data Reduction and Reporting Receiving/ Preparation

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.

CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert material(s) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert material(s) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	1	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Equip Rail, Wall-Mt, 48"W; 1 Clinical Panel, Open 80"H x 24"W; 2 Clinical Panel, Open 80"H x 30"W; 3 Clinical Panel, Open 80"H x 48"W; 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 2 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 80"H x 48"W; 1 Light, 24"W; 5 Light 48"W; 2 Electric/Data Channel 48"W; 1 Electrical/Data Channel 72"W; 2 Electrical/Data Channel, Corner; 4 Cantilevered Work Surf, 30"D x 48"W; 1 Cantilevered Work Surf, 30"D x 72"W; 1 Height Adjustable Table, 30"D x 48"W; 3 Drw, 3"H; 3 Drw, 6"H; 1 Lockable Flipper Unit, 24"W; 4 Lockable Flipper Unit, 48"W; 3 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 4 Shelf, Storage/Display 48"W; 1 3-Shelf Unit with Door, 48"W; 1 Shelf, Storage/Display 24"W; 4 Extra Deep Shelf, 48"W; 1 Sink Base Cab, Dbl Doors, Backsplash, w/Corian Top 30"D x 48"W; 1 Swing-Away Eyewash; 1 SS Double Sink 19"D x 33"D; 1 Gooseneck Mixing Faucet ASSY . with Wristbands; 1 Strainer and Tailpiece; 1 Coat Hook; Drawer Organizer Bins.
E0584	Workstation Blood Bank/Serology Lab, Small	1	VV	* Connecting hardware required to complete installation.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L1180	Dilutor, 1:25,000 Dilution	1	VV	Pipetter/Diluter. It has a sample volume of 20 micro liters and a diluent volume of 5 ml and is compatible with most caustic lab solutions such as HCL, H2SO4 glacial acetic acid, cholesterol reagent, total lipid reagent and a vast number of other corrosives. Each instrument is precisely calibrated to assure dilution accuracy and reproducibility with in 1%. The system also has a factory preset volume ration. The cycle light indicates when units are ready to sample or the dispense hand has a reagent draw-back feature that prevents sample reagent mixing inside the pipette after the dispensing cycle. This is a precise automatic instrument for sampling and dispensing. Used for hemoglobin determinations, and other required dilutions.
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
L9835	Counter, Radioimmunoassay, Multichannel	1	VV	Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9836	Counter, Radioimmunoassay, Single Channel	1	VV	Single-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (serum, urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9840	Counter, Gamma, RIA, Manual	1	VV	Gamma counter. Unit can be either a single well or a multi-well system that requires manual sample changing. It includes a NAI crystal detector. Uses RIA techniques to measure trace quantities of gamma radiation in substances such as hormones, drugs, enzymes, viruses, antibodies, tumor markers and receptors that are found in serum, urine and other body fluids.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	2	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.

26 - LBRI 1 - BAU: Assay Preparation

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.

C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	1	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Equip Rail, Wall-Mt, 48"W; 1 Clinical Panel, Open 80"H x 24"W; 2 Clinical Panel, Open 80"H x 30"W; 3 Clinical Panel, Open 80"H x 48"W; 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 2 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 80"H x 48"W; 1 Light, 24"W; 5 Light 48"W; 2 Electric/Data Channel 48"W; 1 Electrical/Data Channel 72"W; 2 Electrical/Data Channel, Corner; 4 Cantilevered Work Surf, 30"D x 48"W; 1 Cantilevered Work Surf, 30"D x 72"W; 1 Height Adjustable Table, 30"D x 48"W; 3 Drw, 3"H; 3 Drw, 6"H; 1 Lockable Flipper Unit, 24"W; 4 Lockable Flipper Unit, 48"W; 3 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 4 Shelf, Storage/Display 48"W; 1 3-Shelf Unit with Door, 48"W; 1 Shelf, Storage/Display 24"W; 4 Extra Deep Shelf, 48"W; 1 Sink Base Cab, Dbl Doors, Backsplash, w/Corian Top 30"D x 48"W; 1 Swing-Away Eyewash; 1 SS Double Sink 19"D x 33"D; 1 Gooseneck Mixing Faucet ASSY . with Wristbands; 1 Strainer and Tailpiece; 1 Coat Hook; Drawer Organizer Bins.
E0584	Workstation Blood Bank/Serology Lab, Small	1	VV	* Connecting hardware required to complete installation.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L1180	Dilutor, 1:25,000 Dilution	1	VV	Pipetter/Diluter. It has a sample volume of 20 micro liters and a diluent volume of 5 ml and is compatible with most caustic lab solutions such as HCL, H2SO4 glacial acetic acid, cholesterol reagent, total lipid reagent and a vast number of other corrosives. Each instrument is precisely calibrated to assure dilution accuracy and reproducibility with in 1%. The system also has a factory preset volume ration. The cycle light indicates when units are ready to sample or the dispense hand has a reagent draw-back feature that prevents sample reagent mixing inside the pipette after the dispensing cycle. This is a precise automatic instrument for sampling and dispensing. Used for hemoglobin determinations, and other required dilutions.
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
L9835	Counter, Radioimmunoassay, Multichannel	1	VV	Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9836	Counter, Radioimmunoassay, Single Channel	1	VV	Single-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (serum, urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9840	Counter, Gamma, RIA, Manual	1	VV	Gamma counter. Unit can be either a single well or a multi-well system that requires manual sample changing. It includes a NAI crystal detector. Uses RIA techniques to measure trace quantities of gamma radiation in substances such as hormones, drugs, enzymes, viruses, antibodies, tumor markers and receptors that are found in serum, urine and other body fluids.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	2	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.

27 - LBRI 1 - BAU: Biohazard Preparation

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.

C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	1	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Equip Rail, Wall-Mt, 48"W; 1 Clinical Panel, Open 80"H x 24"W; 2 Clinical Panel, Open 80"H x 30"W; 3 Clinical Panel, Open 80"H x 48"W; 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 2 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 80"H x 48"W; 1 Light, 24"W; 5 Light 48"W; 2 Electric/Data Channel 48"W; 1 Electrical/Data Channel 72"W; 2 Electrical/Data Channel, Corner; 4 Cantilevered Work Surf, 30"D x 48"W; 1 Cantilevered Work Surf, 30"D x 72"W; 1 Height Adjustable Table, 30"D x 48"W; 3 Drw, 3"H; 3 Drw, 6"H; 1 Lockable Flipper Unit, 24"W; 4 Lockable Flipper Unit, 48"W; 3 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 4 Shelf, Storage/Display 48"W; 1 3-Shelf Unit with Door, 48"W; 1 Shelf, Storage/Display 24"W; 4 Extra Deep Shelf, 48"W; 1 Sink Base Cab, Dbl Doors, Backsplash, w/Corian Top 30"D x 48"W; 1 Swing-Away Eyewash; 1 SS Double Sink 19"D x 33"D; 1 Gooseneck Mixing Faucet ASSY . with Wristbands; 1 Strainer and Tailpiece; 1 Coat Hook; Drawer Organizer Bins.
E0584	Workstation Blood Bank/Serology Lab, Small	1	VV	* Connecting hardware required to complete installation.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L1180	Dilutor, 1:25,000 Dilution	1	VV	Pipetter/Diluter. It has a sample volume of 20 micro liters and a diluent volume of 5 ml and is compatible with most caustic lab solutions such as HCL, H2SO4 glacial acetic acid, cholesterol reagent, total lipid reagent and a vast number of other corrosives. Each instrument is precisely calibrated to assure dilution accuracy and reproducibility with in 1%. The system also has a factory preset volume ration. The cycle light indicates when units are ready to sample or the dispense hand has a reagent draw-back feature that prevents sample reagent mixing inside the pipette after the dispensing cycle. This is a precise automatic instrument for sampling and dispensing. Used for hemoglobin determinations, and other required dilutions.
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
L9835	Counter, Radioimmunoassay, Multichannel	1	VV	Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9836	Counter, Radioimmunoassay, Single Channel	1	VV	Single-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (serum, urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9840	Counter, Gamma, RIA, Manual	1	VV	Gamma counter. Unit can be either a single well or a multi-well system that requires manual sample changing. It includes a NAI crystal detector. Uses RIA techniques to measure trace quantities of gamma radiation in substances such as hormones, drugs, enzymes, viruses, antibodies, tumor markers and receptors that are found in serum, urine and other body fluids.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	2	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.

28 - LBRI 1 - BAU: Sample Counting / Measurement

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.

C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95"x36"	1	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Equip Rail, Wall-Mt, 48"W; 1 Clinical Panel, Open 80"H x 24"W; 2 Clinical Panel, Open 80"H x 30"W; 3 Clinical Panel, Open 80"H x 48"W; 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 2 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 80"H x 48"W; 1 Light, 24"W; 5 Light 48"W; 2 Electric/Data Channel 48"W; 1 Electrical/Data Channel 72"W; 2 Electrical/Data Channel, Corner; 4 Cantilevered Work Surf, 30"D x 48"W; 1 Cantilevered Work Surf, 30"D x 72"W; 1 Height Adjustable Table, 30"D x 48"W; 3 Drw, 3"H; 3 Drw, 6"H; 1 Lockable Flipper Unit, 24"W; 4 Lockable Flipper Unit, 48"W; 3 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 4 Shelf, Storage/Display 48"W; 1 3-Shelf Unit with Door, 48"W; 1 Shelf, Storage/Display 24"W; 4 Extra Deep Shelf, 48"W; 1 Sink Base Cab, Dbl Doors, Backsplash, w/Corian Top 30"D x 48"W; 1 Swing-Away Eyewash; 1 SS Double Sink 19"D x 33"D; 1 Gooseneck Mixing Faucet ASSY . with Wristbands; 1 Strainer and Tailpiece; 1 Coat Hook; Drawer Organizer Bins.
E0584	Workstation Blood Bank/Serology Lab, Small	1	VV	* Connecting hardware required to complete installation.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L1180	Dilutor, 1:25,000 Dilution	1	VV	Pipetter/Diluter. It has a sample volume of 20 micro liters and a diluent volume of 5 ml and is compatible with most caustic lab solutions such as HCL, H2SO4 glacial acetic acid, cholesterol reagent, total lipid reagent and a vast number of other corrosives. Each instrument is precisely calibrated to assure dilution accuracy and reproducibility with in 1%. The system also has a factory preset volume ration. The cycle light indicates when units are ready to sample or the dispense hand has a reagent draw-back feature that prevents sample reagent mixing inside the pipette after the dispensing cycle. This is a precise automatic instrument for sampling and dispensing. Used for hemoglobin determinations, and other required dilutions.
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
L9835	Counter, Radioimmunoassay, Multichannel	1	VV	Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9836	Counter, Radioimmunoassay, Single Channel	1	VV	Single-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (serum, urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9840	Counter, Gamma, RIA, Manual	1	VV	Gamma counter. Unit can be either a single well or a multi-well system that requires manual sample changing. It includes a NAI crystal detector. Uses RIA techniques to measure trace quantities of gamma radiation in substances such as hormones, drugs, enzymes, viruses, antibodies, tumor markers and receptors that are found in serum, urine and other body fluids.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	2	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.

3 - SUPPORT AREA

1 - WRCH1 - Work Area, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	2	VV	Telephone, desk, 1 line.
E0042	Workcenter, Computer, Free Standing, 48" W	2	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0275	Chair, Swivel, High Back	4	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0750	Table, Office, (size as required)	1	VV	Office table, sized as required. May be used as either a four (4) to six (6) person conference table or as an extra work surface area.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - XRM 01 - Storage, Mobile Equipment

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
X4780	Radiographic Unit, Mobile, Battery, 100 mA, 100kVp	1	VV	Mobile radiographic, rechargeable battery powered x-ray unit. The unit is 100 mA, 110 kVp. For use in surgery or patient treatment areas.

3 - SRR02 - Storage, Refrigerated

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
R6060	Refrigerator, Biological, SS, 2 Door, 40 Cu Ft	2	VV	Biological refrigerator. This unit shall have a minimum volume of 40 cubic feet, double doors, stainless steel cooler storage with stainless steel drawers, three adjustable shelves and one stationary stainless steel shelf. This refrigerator is used in research laboratories and hospital pharmacies for storage and dispensing of drugs.

4 - XVC01 - PACS: Digital Quality Control

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray

E0117	Workstation, Straight, Free Standing, 48" W	1	VV	<p>This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces.</p> <p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	<p>Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>
X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	<p>Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.</p>

5 - XFDS1 - PACS: Digital Archival Storage

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A0900	Relay Rack, Aluminum	1	VV	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).
A0905	Adapter Panel With Couplers, Blue, 6 Port, SM/MM	1	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style blue adapters, standard density.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A6210	Uninterruptible Power Supply, Single Phase	1	VV	Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

X4160	Information System, DIN-PACS	1	VC	The Digital Imaging Network – Picture Archiving and Communications System (DIN-PACS) is an open system network of digital devices designed for the acquisition, transmission, display and management of diagnostic imaging studies. Equipment for DIN-PACS will include workstations, storage devices, servers, interconnecting cables, and all software, hardware, firmware and ancillary devices required for full functionality. Systems will meet DICOM and HL7 standards. Turnkey installation and integration with existing networks and legacy systems is required. Size of system is based on volume of exams taken and file size. Equipment configuration and site preparation, if required, is unique and specific to each medical facility.
-------	------------------------------	---	----	--

6 - XFSA1 - Patient Film Records

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
C0045	Frame, Apron, 1 Drawer, 4x36x22	2	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall. Constructed of steel.
CT030	Countertop, High Pressure Laminate	6	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
X1170	Cabinet, Filing, Film, 5 Shelves, 88x36x18	1	VV	Film filing cabinet. Open shelf system with 5 shelves. Each 36 inch shelf has three interlocking dividers for use with X-ray film jackets. The system is used to store and file X-ray film folders.
X3930	Illuminator, Film, Double, Wall Mounted	1	VV	X-ray film illuminator approximately 20' H x 29' W x 6" D. This is a double, wall mounted type unit with a continuous viewing surface. The tension film grips are adjustable top and bottom with standard grip strip. The unit's balanced-light viewing is assured by the 32W circular fluorescent lamp. It provides 500 feet candles of cool operation across the entire 14" X 17" viewing surface. It is available with or without film-activated switch. The unit can be used in hospitals, examining rooms, satellite office or lab.

7 - XFDS1 - Patient Treatment Files				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A0900	Relay Rack, Aluminum	1	VV	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).
A0905	Adapter Panel With Couplers, Blue, 6 Port, SM/MM	1	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style blue adapters, standard density.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A6210	Uninterruptible Power Supply, Single Phase	1	VV	Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

X4160	Information System, DIN-PACS	1	VC	The Digital Imaging Network – Picture Archiving and Communications System (DIN-PACS) is an open system network of digital devices designed for the acquisition, transmission, display and management of diagnostic imaging studies. Equipment for DIN-PACS will include workstations, storage devices, servers, interconnecting cables, and all software, hardware, firmware and ancillary devices required for full functionality. Systems will meet DICOM and HL7 standards. Turnkey installation and integration with existing networks and legacy systems is required. Size of system is based on volume of exams taken and file size. Equipment configuration and site preparation, if required, is unique and specific to each medical facility.
-------	------------------------------	---	----	--

8 - XTLB1 - Biosafety / Health Physics Lab

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1016	Telephone, Desk, With Speaker	2	VV	Telephone, desk, with speaker.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
C0045	Frame, Apron, 1 Drawer, 4x36x22	2	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall. Constructed of steel.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C04J0	Cabinet, U/C/B, 8 Half Drawer, 36x36x22	1	CC	Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CE040	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x36x13	4	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS140	Sink, SS, Single Compartment, 10x14x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

CT030	Countertop, High Pressure Laminate	15	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
CW150	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 98"x48"	2	CC	Floor standing storage cabinet approximately 98" H x 48" W x 22" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.
D0860	Light, Bench, Dental	2	CC	Bench light. Used on dental prosthetic laboratory benches. The database physical dimensions refer to the reach of the lamp arm.
F0230	Chair, Drafting, Rotary	2	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0535	Cart, Utility	2	VV	Utility cart, 32-39" high X 36" wide X 24" deep, with 4 (four) heavy duty caster wheels.
F2000	Basket, Wastepaper, Round, Metal	3	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
T0010	Beam Analyzer, Radiation Therapy	1	VV	Radiation Beam Analyzer This is a quality assurance system that measures therapy radiation sources, including dose and dose rates, enabling user calculation of beam constancy, flatness and symmetry.
T0025	Meter, Radiation Survey	2	VV	Radiation survey meter. Characteristics/components include hand held and battery operated with a built-in detector; and ability to detect alpha, beta, gamma and x-ray radiation. This unit is used for spot-checking laboratories and other work areas for contamination of equipment, counter tops and floors. The unit is also well suited for detecting accidental exposures to personnel clothes, checking x-ray equipment for possible leakage or locating small spills.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

T0030	Radiation-Light Field Analyzer	1	VV	Light and radiation field analyzer for quality assurance testing of radiation therapy devices. Unit is self contained and checks the coincidence of light and radiation fields, symmetry of radiation field, flatness of radiation field, and penumbra size of the radiation field. Unit has a built in graphics printer for hard copy output of scanned information.
T0180	Cabinet, Storage, Tool, F/Mounted	1	CC	The cabinet shall be designed to store and secure tools and will be non mobile.
T0801	Workbench, Electric, Pedestal Base	2	VV	Electrical workbench approximately 34" H x 72" W x 36" D. Characteristics/components include butcher block maple top; with two drawer or door pedestals and an electronic riser wiring kit. This workbench is used in wood and metal workshops. Workbench is a mix and match construction and can be configured to end users needs.
T1000	Cabinet, Tool, Mobile, With Mechanics Tool Chest	2	VV	Tool cabinet and chest. Characteristics/components include: a mobile tool cabinet with 5 inch casters; shall have a minimum of 7 tamper-proof drawers; and have an internal drawer locking system that prevents unintentional drawer openings. The mechanics tool chest shall be capable of sitting on top of the mobile tool cabinet. It shall have a minimum of 10 tamper-proof drawers and have an internal drawer locking system that prevents unintentional drawer opening. All drawers shall lock automatically when the lid is closed. Shall have a partitioned top till that holds the lift-out trays equipped with socket dividers.
T8005	Signal - Differential Amp. Analyzer	1	VV	Signal analyzer. This unit is capable of analyzing the electrical signals for distortion, networking, noise levels, and burst signals. The system can be used to determine Electro magnetic interface and many other applications. The unit is programmable to measure and analyze all aspects of signal transmission. Used in research and maintenance in a healthcare facility.
T8020	Generator, Pulse	1	VV	Pulse generator. Characteristics/components include four output modes; and complement dual outputs that greatly increase unit applicability in logic design areas, especially interfacing within a system or to peripherals. The unique output flexibility within the normal and complement modes is particularly useful in logic design or control applications requiring simultaneous signals.
T8025	Generator, Function	1	VV	Function generator. Characteristics/components include generated size, triangle and square waveforms; covers 0.2 Hz to 2.0 MHz in 7 ranges; voltage controlled amplitude output; 20 dB step attenuator; four digit frequency counter display and ability to generate low-distortion sine waves which make the unit uniquely appropriate for applications requiring audio signals.
T8045	Oscilloscope, With Accessories	1	VV	Oscilloscope. Characteristics/components include 100 MHz unit; digitizing scope with a fully-functional analog scope that can control data acquisition and a switch-selectable Pre/Post/Mid-triggering with reference to a triggering event. This unit is used to evaluate electronic equipment faults.
T9420	Vise, Bench/Pipe, Swivel Base, 5 Inch Jaw	1	VV	Bench and pipe vise. Characteristics/components include 6 inch opening jaw; 5 inch width jaw; holds 1/8 to 1-1/2 inch pipe. Swivel base allows full 360 degrees rotation, geared lock bolt insures positive locking against slippage.

9 - NMDS1 - Storage, Radioactive Waste

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.

X9305	Cabinet, Storage, Lead Lined	4	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.
-------	------------------------------	---	----	--

10 - NMDC1 - Equipment Calibration

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
X9305	Cabinet, Storage, Lead Lined	1	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.
X9310	Cart, Transport, Radium	1	VV	Radium transport cart. The cart is a rugged, enameled-steel and equipped with two wheels, a caster and a long handle. It is designed for safety and convenience when transporting radioactive material between a permanent storage safe and the patient's bedside.

11 - RCA01 - Alcove, Crash Cart

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.
M1110	Resuscitator, Bag-Mask, Hand Op, Infant	1	VV	Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M7905	Oximeter, Pulse	1	VV	Pulse oximeter for continuous surveillance of patient pulse and oxygen saturation rates. Instrument features LED display, audio and visual alarms, automatic calibration and battery operation in case of power failure. Other applications include sleep studies, exercise testing and monitoring certain patients in the home (e.g. infants or patients requiring respiratory therapy).
M8770	Aspirator/Pressure Unit, General Purpose	1	VV	General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes.

12 - UCCL1 - Utility Room, Clean

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.

E0903	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	<p>Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	<p>Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
P8710	Utility Center, Plumbing Connection	1	CC	<p>Plumbing connection utility center, sometimes referred to as a 'GUY GRAY BOX'. This recessed utility center provides for hot and cold water connections and a drain connection at sink and other equipment locations. The utility center includes cutoff valves for the water connections, a plug seal for the drain and an outside cover to provide an aesthetic appearance when connections are no longer required. This center may be installed in locations where no plumbing fixtures are included in a design as a future flexibility device, saving many dollars for later facility modifications to incorporate sinks as functions change.</p>

13 - USCL1 - Utility Room, Soiled

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS200	Sink, SS, Single Compartment, 12x28x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT050	Countertop, Stainless Steel	7	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.

P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

14 - JANC1 - Housekeeping Aides Closet (HAC)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.

P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

15 - LCCL1 - Alcove, Linen

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
F0515	Cart, Supply, Linen	1	VV	Closed linen supply cart. Equipped with four (4) non-marking rubber tire roller bearing casters and heavy duty cover. May be used for the delivery and user storage of clean linen as well as the return of soiled linen.
M7300	Dispenser, Garment, Scrubs	1	VV	A garment dispenser and receiver cabinet for dispensing scrub sets to customers. Dispenser holds approximately 64 sets of scrubs and accommodates 85 users per day with 2 refills per day. Garments are dispensed in sets by size to authorized personnel by use of hospital ID, bar code, magnetic strip or with keypad backup. Maintains control of scrub sets through usage reports and digital recording of returns.

16 - SRLW2 - Storage, Stretcher / Wheelchair

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M4655	Stretcher, Mobile, CRS, 9 Position	2	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.

4 - STAFF AND ADMINISTRATIVE AREA

1 - OFA09 - Office, Nuclear Medicine Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - OFA07 - Workstation, Secretary

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
3 - RECP3 - Reception				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

4 - OFA07 - Workstation, Administrative Assistant

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

5 - OFA07 - Workstation, Staff Physician

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
6 - OFA07 - Workstation, Non-Physician Professional				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
-------	---	---	----	---

7 - OFA07 - Workstation, Physicist

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

8 - OFA07 - Workstation, Chief Technologist				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
9 - OFA07 - Workstation, Cyclotron Operator				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

10 - OFA07 - Workstation, PACS Administrator

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
11 - OFA07 - Workstation, Quality Assurance				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

12 - WRTM2 - Office, Tele-Nuclear Medicine

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.

F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3025	Board, Bulletin, Wood Framed	1	VV	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.

13 - OFA07 - Workstation, Clerical

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

14 - OFA07 - Workstation, Data Processing

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

15 - OFA07 - Workstation, Scheduler

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

16 - OFA07 - Workstation, Transcriptionist

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

17 - SL001 - Lounge, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.

F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.
M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.

18 - LR001 - Locker Room, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	4	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.

19 - TLTU1 - Toilet, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

NUCLEAR MEDICINE SERVICE (252) - Contents - VA PG-18-5 (18 Jul 2016 04:57PM ET)

A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

5 - EDUCATION AREA

1 - OFA07 - Workstation, Resident Intern / Student

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	<p>Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.</p>
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	<p>Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	<p>Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.</p>