#### **LOGISTICS SERVICE (284)** 2 - LOADING DOCK AREA 1 - DOCK1 - Receiving Dock, Clean JSN NAME QTY ACQ/INS DESCRIPTION Unit attaches to the face of the dock for easy installation. It consists of a counterbalance lip that can be extended to rest on the bed of the trailer for loading and unloading of merchandise. When the trailer departs, the lip will automatically retract behind the bumper face. Size will vary depending on A6125 Leveler, Dock 1 CC the application. Air curtain. The unit is generally fabricated to size for operation. This unit is used at entrances and docks to prevent cold and humid or dry and hot air from entering through openings which are exposed to weather conditions. The database pricing reflects an unheated air door 6-1/2' wide with a 3" or 6" deep discharge nozzle to cover a standard two-door width entry. Some units run on 120V power; refer to the manufacturer's specifications for the model chosen. Larger width and industrial CC K0450 Curtain, Air 1 duty air doors are available. Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in K9300 Washer, Pressure w/Sanitizer VC 1 commercial areas and institutions such as hospitals. Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates M2105 Pallet Lift, Hydraulic, Manual, 48" Pallet VV 48" pallets and is designed to handle all types of lifting tasks. 2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound M2115 Truck, Hand, 2 Wheel 1 VV weight capacity with two 8 or 10 inch wheels. For use in the warehouse. A 4 wheel platform truck (push cart). Truck has heavy duty platform and is mounted on four 8" diameter casters. The load capacity is 2000-2500 pounds. It is designed for use in the receiving and M2120 Truck, Platform, 4 Wheel WW other material handling areas. 1 Freestanding roll on scale with a 2000 pound capacity. Unit consists of a heavy duty anodized ٧٧ aluminum or steel platform with powered digital readout. For use in food service or the laundry. M4025 Scale, Roll On, Freestanding, 2000 Pound Capacity 2 - DOCK1 - Receiving Dock, Soiled JSN NAME QTY ACQ/INS DESCRIPTION Unit attaches to the face of the dock for easy installation. It consists of a counterbalance lip that can be extended to rest on the bed of the trailer for loading and unloading of merchandise. When the

the application.

1

CC

A6125 Leveler, Dock

trailer departs, the lip will automatically retract behind the bumper face. Size will vary depending on

	Truck, Platform, 4 Wheel  Scale, Roll On, Freestanding, 2000 Pound Capacity	1	VV	diameter casters. The load capacity is 2000-2500 pounds. It is designed for use in the receiving and other material handling areas.  Freestanding roll on scale with a 2000 pound capacity. Unit consists of a heavy duty anodized aluminum or steel platform with powered digital readout. For use in food service or the laundry.
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.  A 4 wheel platform truck (push cart). Truck has heavy duty platform and is mounted on four 8"
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.
K9300	Washer, Pressure w/Sanitizer	1	VC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K0450	Curtain, Air	1	CC	Air curtain. The unit is generally fabricated to size for operation. This unit is used at entrances and docks to prevent cold and humid or dry and hot air from entering through openings which are exposed to weather conditions. The database pricing reflects an unheated air door 6-1/2' wide with a 3" or 6" deep discharge nozzle to cover a standard two-door width entry. Some units run on 120V power; refer to the manufacturer's specifications for the model chosen. Larger width and industrial duty air doors are available.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
				Unit attaches to the face of the dock for easy installation. It consists of a counterbalance lip that can
				be extended to rest on the bed of the trailer for loading and unloading of merchandise. When the
				trailer departs, the lip will automatically retract behind the bumper face. Size will vary depending on
A6125	Leveler, Dock	1	CC	the application.
K0450	Curtain, Air	1	СС	Air curtain. The unit is generally fabricated to size for operation. This unit is used at entrances and docks to prevent cold and humid or dry and hot air from entering through openings which are exposed to weather conditions. The database pricing reflects an unheated air door 6-1/2' wide with a 3" or 6" deep discharge nozzle to cover a standard two-door width entry. Some units run on 120V power; refer to the manufacturer's specifications for the model chosen. Larger width and industrial duty air doors are available.
K9300	Washer, Pressure w/Sanitizer	1	VC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.

M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
M2120	Truck, Platform, 4 Wheel	1	VV	A 4 wheel platform truck (push cart). Truck has heavy duty platform and is mounted on four 8" diameter casters. The load capacity is 2000-2500 pounds. It is designed for use in the receiving and other material handling areas.
M4025	Scale, Roll On, Freestanding, 2000 Pound Capacity	1	VV	Freestanding roll on scale with a 2000 pound capacity. Unit consists of a heavy duty anodized aluminum or steel platform with powered digital readout. For use in food service or the laundry.
4 - M M	BK1 - Breakout Room			
JSN	NAME	QTY	ACQ/INS	
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2016	Waste Receptacle, 40 GAL	1	VV	Rectangular steel waste receptacle with step-on lid and a 40 gallon capacity. The receptacle is used to collect and temporarily store small quantities of paper refuse. Can be used in restrooms, patient areas laboratories, pharmacies, etc.
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1832	Printer, Color, Small	1	VV	Desktop color printer. Printer shall be capable of printing a minimum of 10 pages per minute (ppm) of black print and 7 ppm color print. Resolution shall be no less than 600 X 600 dpi. It shall be capable of printing on multiple media types (plain, inkjet and photo paper) and be capable of accepting media sizes of 3 X 5 to 8.5 X 14 inches. The printer is used in small offices.

5 - M M	5 - MMST1 - Staging Room, Logical Unit of Measure Delivery (LUM)							
JSN	NAME	QTY	ACQ/INS	DESCRIPTION				
				Hand held laser bar code reader with computer interface. Used for automated inventory, using bar				
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	code stickers / labels. Convenience outlet required at point of use.				

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
6 - SR 0	GC1 - Storage, Full Gas Cylinder			
M1803	Workstation, Computer, Wall Mounted, Adjustable	1		and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information. A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard

6 - SRG	C1 - Storage, Full Gas Cylinder			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
				Medical gas cylinder storage rack. Unit is a modular cage frame for holding various sizes of gas cylinders. Nylon or fabric securing straps can be attached to the frame bars to stabilize gas cylinders.
M2025	Rack, Storage, Cylinder, Gas	1	VV	Add additional units or specify size as required when ordering. This item is often locally fabricated.
M2117	Truck, Hand, 2 Wheel, Gas Cylinder	1	VV	A gas cylinder hand truck for a single 12" cylinder with a minimum capacity of 300 lbs.

7 - SRG	GC1 - Storage, Empty Gas Cylinder			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
				Medical gas cylinder storage rack. Unit is a modular cage frame for holding various sizes of gas cylinders. Nylon or fabric securing straps can be attached to the frame bars to stabilize gas cylinders.
M2025	Rack, Storage, Cylinder, Gas	1	VV	Add additional units or specify size as required when ordering. This item is often locally fabricated.
M2117	Truck, Hand, 2 Wheel, Gas Cylinder	1	VV	A gas cylinder hand truck for a single 12" cylinder with a minimum capacity of 300 lbs.

8 - SRH	3 - SRHM1 - Storage, Flammable					
JSN	NAME	QTY	ACQ/INS	DESCRIPTION		
				Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use		
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	with nitric and sulfuric acids.		

Cabinet, Storage, Flammable, Freestanding	1	VV	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.
			Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available.
Shelving, Storage, 77hx36wx18d	1	VV	For use in the storage room.
Shower Safaty Franctanding With Eve/Eace Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.
	<u> </u>	Shelving, Storage, 77hx36wx18d 1	Shelving, Storage, 77hx36wx18d 1 VV

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	СС	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.

	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

# 3 - WAREHOUSE AREA

1 - M M	RP1 - Receiving and Issue			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:  4 standard solid panels;  2 panel connectors, 2-way corner;  1 panel-to-panel connector;  2 finished end hardware;  1 cantilevered work surface;  1 peninsula work surface;  2 lockable flipper units;  2 shelf, storage/display;  2 lights;  1 tack board, 48"W;  1 tool rail, 30"W;  1 paper tray;  1 diagonal tray;  1 adjustable keyboard tray;
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	1 mobile pedestal, box/file.
				Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
F0205	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base.

				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
F0775	Table, Work, 2 Drawer	1	VV	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.
<b>50700</b>			,,,,	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	code stickers / labels. Convenience outlet required at point of use.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
F0000	OL 1 D (1 40   D)			unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat
				panel monitor, keyboard, mouse and speakers. The system shall have the following minimum
				characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-
				ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
WITOOT	Computer, interoproceeding, with fact and interinter		• • •	Thornton. The compared to deed throughout the reality to imput, memperate and remove information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
				Safety storage cabinet. This unit is of double steel wall construction, with vented grounding
				attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-
				point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements.
				Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework
				configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet
				requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	conditioning) system.
				Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For
				use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
2000	and any second s	<u> </u>	, ,	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	48" pallets and is designed to handle all types of lifting tasks.
				2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound
M2115	Truck, Hand, 2 Wheel	1	VV	weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
				0. 18 4 1 70 8 1 11 11 11 11 11 11 11 11 11 11 11 11
				Straddle stacker. Battery powered with 2000 pound lifting capacity. Unit lifts to heights up to 127".
MOAOE	Stocker Streetile 1971 Lift 2000 lb Constitu	4	\/\/	Equipped with a extra heavy duty hydraulic system. Unit has a built-in automatic battery charger.
1012125	Stacker, Straddle, 127" Lift, 2000 lb Capacity	1	VV	Electrical requirements are for the charger. Designed for pallet lifting.

JSN	NAME	OTY	ACQ/INS	DESCRIPTION
5 - SRS	E1 - Storage, Emergency Preparedness			
M2070	Shelving, Storage, 77hx36wx18d	2	VV	For use in the storage room.
				Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Pric provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
- SRS	E1 - Storage, Pandemic			
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Prior provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
	Telecommunication Outlet	1	VV	Telecommunication outlet location.
JSN	01 - Storage, Flex NAME	QTY	ACQ/INS	DESCRIPTION
	Shelving, Storage, Warehouse	3	VV	Warehouse storage shelving approximately 75 inches high by 36 inches wide by 24 inches deep.
		3	VV	
A6155	Cage, Security, Heavy Duty	1	CC	Modular woven wire security partition with doors creating a secure area or separate zones without blocking light or air. Easy surveillance of protective area. Durable 10 gauge, 1½" diamond wire woven into a sturdy 1" x 1/2" x 1/8" channel frame. Size and shape of the security room will vary depending on the application. Price is per panel. Separate pricing required for doors, windows, and installation components.
JSN	NAME	QTY	ACQ/INS	
- SSC	01 - Storage, Equipment Prep and Staging			
M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.
/12130	Truck, Hydraulic Lift, Electric	1	VV	distances or over uneven surfaces.
				Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long

M2055 Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2070 Shelving, Storage, 77hx36wx18d	2	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
				Hand held laser bar code reader with computer interface. Used for automated inventory, using bar
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	code stickers / labels. Convenience outlet required at point of use.
				Pallet storage shelving starter section. This unit is of heavy duty construction and has channel type bracing in between columns, heavy duty foot plate with 3-point security. The size will be determined
M2085	Shelving, Storage, Pallet	2	VV	by weight load. It is designed for easy forklift access in storage areas and warehouses.
M2090	Shelving, Storage, Warehouse	1	VV	Warehouse storage shelving approximately 75 inches high by 36 inches wide by 24 inches deep.
				Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	48" pallets and is designed to handle all types of lifting tasks.
NACAAE	Twist, Head OWheel		\/\/	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound
M2115	Truck, Hand, 2 Wheel	1	VV	weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
				Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within
				enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger.
				Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long
M2130	Truck, Hydraulic Lift, Electric	1	VV	distances or over uneven surfaces.

7 - SRS	7 - SRSE1 - Storage, Unit I tems						
JSN	NAME	QTY	ACQ/INS	DESCRIPTION			
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.			
M2070	Shelving, Storage, 77hx36wx18d	2		Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.			

8 - M M	RP1 - Receiving Breakout and Inspection Room			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

				This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:  4 standard solid panels;  2 panel connectors, 2-way corner;  1 panel-to-panel connector;  2 finished end hardware;  1 cantilevered work surface;  1 peninsula work surface;  2 lockable flipper units;  2 shelf, storage/display;
				2 lights; 1 tack board, 48"W;
				1 tool rail, 30"W;
				1 paper tray;
				1 diagonal tray; 1 adjustable keyboard tray;
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	1 mobile pedestal, box/file.
	, , , , , , , , , , , , , , , , , , , ,			Uphol stered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
F0205	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base.
F007F	Chair Ovival High Book	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F02/5	Chair, Swivel, High Back	- '	VV	and upholstered with either woven textile fabric or vinyl.  Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
F0775	Table, Work, 2 Drawer	1	VV	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.
1 21 00	, See Soud, Held Hold, Will Hitelian	1	<b>V V</b>	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
1VI 10-10	1 THRO/ COPIO/ I ax Combination	'	V V	maintanonona pintos, tux, sociino and copio (11 0) an in onomionino.

M2020	Cabinet, Storage, Safety, Built-In, Vented	1	cc	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.
1012103	ranet Litt, Hydraunc, Mandal, 40 Fanet	1	V V	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound
M2115	Truck, Hand, 2 Wheel	1	VV	weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
M2125	Stacker, Straddle, 127" Lift, 2000 lb Capacity	1	VV	Straddle stacker. Battery powered with 2000 pound lifting capacity. Unit lifts to heights up to 127". Equipped with a extra heavy duty hydraulic system. Unit has a built-in automatic battery charger. Electrical requirements are for the charger. Designed for pallet lifting.
				Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long
M2130	Truck, Hydraulic Lift, Electric	1	VV	distances or over uneven surfaces.
M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.

9 - SRS	04 - Storage, Sterile Consumables (Soft Goods)			
JSN	NAME	QTY A	ACQ/INS	DESCRIPTION

				THIS TYPICAL INCLUDES
				THIS TYPICAL INCLUDES:
				1 Cart body, style-A narrow, w/raised edge top
				1 Accessory rail, side
				1 Accessory rail, back
				1 Defibrillator tray
				1 IV pole
				1 Breakaway bar
				1 Flip-up shelf
				1 Wastebasket
				1 Oxygen tank holder
				1 Electrical box-4 outlet
				1 Cord wrap
				4 Drawer, 3"H
				·
				3 Drawer, 6"H
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	2	VV	Drawer organizer bins.
				THIS TYPICAL INCLUDES:
				1 Wire Cart, w/Casters
				5 Wire Shelves w/Dividers
				5 Vertical Back/Side Panels
				2 Storage Frame
				4 Drawers, 6"H
				1 Cart Cover
				Label Clips
E0984	Cart, Wire, Mobile, 72"H x 60"W x 24"D	1	VV	Drawer Dividers
				Hand held laser bar code reader with computer interface. Used for automated inventory, using bar
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	code stickers / labels. Convenience outlet required at point of use.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
E3200	Clock, Battery, 12" Diameter	1	VV	not included).
F3200	Clock, Dattery, 12 Diameter	1	V V	not moradea).
				Deals to a minute of the control of
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat
				panel monitor, keyboard, mouse and speakers. The system shall have the following minimum
				characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-
				ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
				A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard
				and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor
				enable frequent position changes. Unit contains an integrated cable management system to hide
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	VV	wires. A separate wall-mounted CPU holder is included.
				Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For
				use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	10	VV	provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

			Surgical case cart. Unit consists of two hinged cabinet sections, each section equipped with two pull- out shelves with stops. The entire unit is mounted on four heavy duty conductive swivel casters.
M8910 Cart, Surgical Case	2	VV	Used to transport surgical packs and supplies to surgery and soiled items back to central supply.

10 - NT001 - Pneumatic Tube Station				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A6165	Station, Pneumatic Tube System	1		The basic pneumatic tube system consists of a tube linking two or more different locations, a carrier to carry the payload and a power source to move the carrier from one location to another. The systems becomes more complex when the system is expanded to a network containing hundreds of locations and dozens of zones that need to transport the payload simultaneously.

# 4-POSTAL/MAIL SERVICE AREA

1 - OF <i>F</i>	A09 - Office, Postal / Mail Service Chief			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.
				THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel-to-Panel Connectors
				1 Panel Connector, 2-Way Corner
				2 Finished End Hardware
				2 Lockable Flipper Units
				2 Shelves, Storage/Display
				3 Lights
				3 Tackboards
				2 Cantillevered Work Surfaces
				1 Adjustable Keyboard Tray
				1 Mobile Pedestal, Box/File
				1 Pencil Drawer
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	2 Support Panels
				Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
F0205	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base.

				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
<b>F</b> 0000	OL 1 D 11 4011 D: 1			unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
F0422	Wasketetian Otsaiakt Fran Otsasking 70" W	4		This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:  4 Standard Solid Panels  2 Panel Connectors, 2-Way Corner  1 Panel-to-Panel Connector  2 Finished End Hardware  1 Cantilevered, Work Surface  2 Lockable Flipper Units  2 Shelf, Storage/Displays  2 Lights  1 Tack board  1 Tool Rail  1 Paper Tray  1 Diagonal Tray  1 Adjustable Keyboard Tray
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	1 Mobile Pedestal, Box/File
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1		and upholstered with either woven textile fabric or vinyl.

F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

3 - MR	RS1 - Mailroom			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A1055	Mailbox, Horizontal, Rear Loading	2	СС	Horizontal, rear loading mail box. Consists of aluminum compartment doors with single dial resettable combination lock, and zinc plated steel compartments. Used for mail distribution. Unit consists of 60 doors (door sizes either 12" high and 5" wide or 12" wide and 5" high). Size as required.
A 1066	Mirror, Float Glass, With SS Frame	1	cc	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A 1000	Willion, Float Grass, With SS Frame	1		Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable
A5075	Dispenser, Soap, Disposable	1	VV	soap cartridge and valve.
				A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	СС	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
F0100	Bin, Mail Sorting, Table Mounted	2	VV	Table mounted mail sorting bin with sufficient adjustable dividers to accommodate all standard size papers, and computer reports. Typical number of compartments for bin is forty eight (48).
F0275	Chair, Swivel, High Back	3	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0640	Desk, Single Pedestal	2	VV	Single pedestal flat top desk, 30" high X 66" wide X 30" deep with right or left hand pedestal, one (1) box drawer, one (1) file drawer, modesty panel and floor glides.

F0775	Table, Work, 2 Drawer	2	VV	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2017	Waste Receptacle, 24 GAL	2	VV	Rectangular steel waste receptacle with step-on lid and 24 gallon capacity. The receptacle is used to collect and temporarily store small quantities of paper refuse. Can be used in restrooms, patient areas laboratories, pharmacies, etc.
F2025	Container, Recycling, Small	1	VV	Recycling container shall be approximately 10-gallons in capacity. The container may be Recycle Blue in color with the recycle symbol identified on the container.
F3100	Safe, Collection Agent	1	VV	Collection agent safe. Unit consists of thick door equipped with combination lock. All steel welded construction. For special document and record storage.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays.  Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
	Shelving, Storage, 77hx36wx18d	2	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.
	Lavatory, Vitreous China, Slab Type		CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

4 - RPR	102 - Reproduction Room, High Volume			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F0100	Bin, Mail Sorting, Table Mounted	1		Table mounted mail sorting bin with sufficient adjustable dividers to accommodate all standard size papers, and computer reports. Typical number of compartments for bin is forty eight (48).
		2		Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.

				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
F2026	Container, Recycling, Large	1	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.
F2530	Drill, Paper	1	VV	Paper drill, 17" high X 20" wide X 20" deep with spring-loaded paper hold down bar, and 1 (one) 1/4" drill. Unit used to drill holes in stacks of paper up to one inch thick. This is a table top unit. Requires convenience outlet at point of use.
	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
	Shelving, Storage, 77hx36wx18d	2	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

NAM E elecommunication Outlet elephone, Desk, 1 Line in, Mail Sorting, Table Mounted	1 1	VV VV	Telecommunication outlet location. Telephone, desk, 1 line.  Table mounted mail sorting bin with sufficient adjustable dividers to accommodate all standard size
	1		Table mounted mail sorting bin with sufficient adjustable dividers to accommodate all standard size
in, Mail Sorting, Table Mounted	1	VV	
			papers, and computer reports. Typical number of compartments for bin is forty eight (48).
			Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
asket, Wastepaper, Round, Metal	1	VV	nursing stations.
eader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.
lock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
l	ock, Battery, 12" Diameter  mputer, Microprocessing, w/Flat Panel Monitor		

6 - SRSE1 - Storage	Room			
JSN	NAME	QTY ACQ/INS	DESCRIPTION	

M2055 Shelving.	, Storage, Wire, CRS, w/Adjustable Shelves	2		Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2070 Shelving	, Storage, 77hx36wx18d	2	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

# 5 - STAFF AND ADMINISTRATIVE AREA

1 - OF	A09 - Office, Logistics Chief			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.
				THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel-to-Panel Connectors
				1 Panel Connector, 2-Way Corner
				2 Finished End Hardware
				2 Lockable Flipper Units
				2 Shelves, Storage/Display
				3 Lights
				3 Tackboards
				2 Cantillevered Work Surfaces
				1 Adjustable Keyboard Tray
				1 Mobile Pedestal, Box/File
				1 Pencil Drawer
E0090	Workstation, L-Shaped, Free Standing, 72x72	1		2 Support Panels
				Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
F0205	Chair, Side With Arms	1		Seat height is a minimum of 17". Available with or without sled base.
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1		and upholstered with either woven textile fabric or vinyl.
				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.

				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - OF	A09 - Office, Assistant Logistics Chief			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.
				THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel-to-Panel Connectors
				1 Panel Connector, 2-Way Corner
				2 Finished End Hardware
				2 Lockable Flipper Units
				2 Shelves, Storage/Display
				3 Lights
				3 Tackboards
				2 Cantilevered Work Surfaces
				1 Adjustable Keyboard Tray
				1 Mobile Pedestal, Box/File
				1 Pencil Drawer
E0090	Workstation, L-Shaped, Free Standing, 72x72	1		2 Support Panels
				Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
F0205	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base.
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.

				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

3 - SEC	3 - SEC01 - Secretary / Waiting					
JSN	NAME	QTY	ACQ/INS	DESCRIPTION		
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.		
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.		
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.		
				This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TY PICAL INCLUDES:  4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray;		
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	1 mobile pedestal, box/file.		
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.		
	Chair, Waiting Room, Single	2	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.		

				Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	locking device. Each drawer has label holder, handle and roller cradle.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays.  Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or
				administrative spaces. There will be a price decrease if typical work stations are used with vertical
				hanging strips instead of panels. THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel Connectors, 2-Way Corner
				1 Panel-to-Panel Connector
				2 Finished End Hardware
				1 Cantilevered, Work Surface
				2 Lockable Flipper Units
				2 Shelf, Storage/Displays
				2 Lights
				1 Tack board
				1 Tool Rail
				1 Paper Tray
				1 Diagonal Tray
				1 Adjustable Keyboard Tray
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	1 Mobile Pedestal, Box/File
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.

				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

5 - CR/	A01 - Conference Room / Training Room			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	facility to hang various items of apparel.
				A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	compliant unit with a load capacity of up to 130 lbs.
				Wall mounted television bracket backing which provides additional support and strength for the
				installation of the television bracket. Option available for interior or exterior plate and sized for 12"
A5220	Bracket, Television, Wall Backing	1	CC	16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
				Conference chair designed to complement the executive furniture package selected. Foam rubber
				cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel
F0220	Chair, Conference	8	VV	casters.
				Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
. 0000	Tronacaron, Comparor, Endocesa, Francesa	·		Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying
F0755	Table, Conference, Wood	1	VV	from 74" to 96". These tables add traditional elegance to any conference room.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).

M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	1	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copyboard with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.

6 - RPF	R01 - Copier / Office Supply Room			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F0465	Cabinet, Storage, 2 Door, 5 Shelf	1	VV	Storage cabinet, 78" high X 48" wide X 24" deep with two (2) doors and five (5) adjustable shelves.
		_		Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
F0550	Chradder Denor House Duty			Shredder shall be able to process a minimum of 25 sheets of paper per pass at a minimum rate of 20 feet per minute. The unit shall have a 16 inch throat to accept paper. Paper shall be shredded into 1/4 inch string.
F2550	Shredder, Paper Heavy Duty	1	VV	inch strips.

M1810 Copier, Floor Standing, Digital	1	VV	Floor standing copier. Unit features automatic paper size selection, automatic document feeder and sorter. The system also has zoom capabilities and automatic two-sided copying. For use where medium volume reproduction is required in the range of 30 to 40 copies per minute.
M1835 Printer, Color Laser, Large	1	VV	Color laser printer designed for high volume use and network capable. The printer shall be capable of printing a minimum of 25 pages per minute (ppm) of black print and 20 ppm color print. Resolution shall be no less than 600 X 600 dpi. It shall be capable of printing on multiple media types (plain, inkjet, photo paper and transparencies) and be capable of accepting media sizes of 3 X 5 to 8.5 X 14 inches. The printer is used in multi-user network offices.
M1855 Facsimile Machine	1	VV	Plain paper facsimile unit used to transmit printed matter or images over standard telephone lines. The unit operates at a modem speed of 33.6 Kbps and automatically recognizes and communicates with a variety of standard facsimile machines. Commonly referred to as "fax" unit.

7 - SL0	01 - Lounge, Staff			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	cc	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
				Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. Fo
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	general purpose use throughout the facility.
			İ	Standing height under counter base cabinet with four full width drawers of equal height. Also
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	referred to as a drawer cabinet. For general purpose use throughout the facility.

C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	СС	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
OT-000		_		A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring
	Countertop, Solid Surface	7	CC	optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
				Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed
K4665	Oven, Microwave, Consumer	1	VV	selectors for commonly cooked items. This oven is commonly found in staff lounges.

				42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC
M0515	Television, Plasma	1	VV	tuner, built-in stereo speakers and surround sound.
				Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It
				also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	commercial or residential design and use.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
				Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal
A1030	Locker, 2 Person, Over/Under	10	VV	belongings. Other width and depths are available.
				Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with
A1080	Mirror, Posture, Wall Mounted	1	CC	water proof back. For educational and therapy programs.
A5020	Bench, Locker Room, Floor Mounted	1		Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).

9 - LR0	9 - LR002 - Locker / Changing Room, Female					
JSN	NAME	QTY	ACQ/INS	DESCRIPTION		
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.		
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.		
				Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door		
				equipped with safety guard handles. Designed for storage of coats, hats, and other personal		
A1030	Locker, 2 Person, Over/Under	10	VV	belongings. Other width and depths are available.		
				Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with		
A1080	Mirror, Posture, Wall Mounted	1	CC	water proof back. For educational and therapy programs.		
				Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of		
				moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel		
A5020	Bench, Locker Room, Floor Mounted	1	CC	pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.		

				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).

10 - TL	0 - TLTU1 - Toilet, Staff						
JSN	NAME	QTY	ACQ/INS	DESCRIPTION			
	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.  Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable			
A5075	Dispenser, Soap, Disposable	1	VV	soap cartridge and valve.			
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.			
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.			
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.			
	Hook, Garment, Double, SS, Surface Mounted	1	СС	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.			
A 5000	Discourse Tailed Times CO o Dall Conference 1		00	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For			
	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	general purpose use in restrooms.  "Step on" wastenesses baset with inner lines and feet notal activated file top.			
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.			

P3000 Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050 Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.