EDUCATIONAL FACILITIES (402)

1 - STAFF AND ADMINISTRATIVE AREA

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray
F0123	Workstation, Straight, Free Standing, 72" W	1	VV	1 Mobile Pedestal, Box/File
	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
	Telecommunication Outlet	2	VV	Telecommunication outlet location.
1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
\ 51 15	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
13143	Trook, Garrierit, Double, 33, Surrace Mounted	'		THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel-to-Panel Connectors
				1 Panel Connector, 2-Way Corner
				2 Finished End Hardware
				2 Lockable Flipper Units
				2 Shelves, Storage/Display
				3 Lights
				3 Tackboards 2 Cantilevered Work Surfaces
				1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
				· ·
-0000	Workstation I Channel From Standing 70:70	1	VV	1 Pencil Drawer
=0090	Workstation, L-Shaped, Free Standing, 72x72	<u> </u>	VV	2 Support Panels Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
=020E	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base.
-0203	Chair, Side With Arms	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
E0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
0275	Chair, Swiver, High Back	'	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
=0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
0420	Cabinet, Filling, Lateral, Harringgill	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
=2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
2000	Daska, Wasiquapa, Nouriu, Madi	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batterie
=3300	Clock, Battery, 12" Diameter	1	VV	not included).
J200	orom, ballay, 12 brailiad	1	V V	not moracaj.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
//1 2 ∩1	Computer Microprocessing w/Flat Panel Manifer	1	\/\/	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
И1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	ROMDVD combo; 1.44MB network inte

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
	Telecommunication Outlet	2	VV	Telecommunication outlet location.
	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.
				THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel-to-Panel Connectors
				1 Panel Connector, 2-Way Corner
				2 Finished End Hardware
				2 Lockable Flipper Units
				2 Shelves, Storage/Display
				3 Lights
				3 Tackboards
				2 Cantilevered Work Surfaces
				1 Adjustable Keyboard Tray
				1 Mobile Pedestal, Box/File
-	W 1			1 Pencil Drawer
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	2 Support Panels
E000E	Chair Cida Mith Arras		VV	Uphol stered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
FU2U5	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base. Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
E0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
1 0273	Grian, Swiver, High Dack	!	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
				recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
	James Comments of the Comments			Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat
				panel monitor, keyboard, mouse and speakers. The system shall have the following minimum
				characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-
				ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

4 - OF	A07 - Workstation, Education Administrative Assista	nt		
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	Adjustable Keyboard Tray Mobile Pedestal, Box/File
	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
5 - SEC	C01 - Secretary / Waiting			
JSN	NAME	OTV	ACQ/INS	DESCRIPTION
JON	INAIVI C	WIT	ACM/IN2	DESCRIPTION

Telecommunication outlet location.

Telephone, desk, multiple line.

VV

VV

A1010 Telecommunication Outlet

A1015 Telephone, Desk, Multiple Line

				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
710110	Trook, Carrion, Double, Co, Carrioto Mounted		- 00	This section will provide a whole work station typical to quickly plan work areas in clinical or
				administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:
				4 standard solid panels;
				2 panel connectors, 2-way corner;
				1 panel-to-panel connector;
				2 finished end hardware;
				1 cantilevered work surface;
				1 peninsula work surface;
				2 lockable flipper units;
				2 shelf, storage/display;
				2 lights; 1 tack board, 48"W;
				1 tool rail, 30"W;
				1 paper tray;
				1 diagonal tray;
				1 adjustable keyboard tray;
F0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	1 mobile pedestal, box/file.
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
				Single seat waiting room chair with foam padded seat and back. Upholstered with either woven
F0305	Chair, Waiting Room, Single	2	VV	fabric textile or vinyl. Arms and floor glides included.
				Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	locking device. Each drawer has label holder, handle and roller cradle.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desirtes missessessing assessment. The unit shall assess to a sected assessing and it.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat
				panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-
				ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
IVI TOUT	Computer, who oprocessing, w/riat rane world	l I	V V	monitor. The computer is used throughout the facility to input, mailipulate and retrieve information.

			High resolution computer printer with a variety of type styles and sheet/envelope feeder trays.
			Database information reflects network ready, medium duty office style laser printers. Other types of
M1825 Printer, Computer	1	VV	printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner
				1 Panel-to-Panel Connector
				2 Finished End Hardware
				1 Cantilevered, Work Surface
				2 Lockable Flipper Units
				2 Shelf, Storage/Displays
				2 Lights
				1 Tack board
				1 Tool Rail
				1 Paper Tray
				1 Diagonal Tray
				1 Adjustable Keyboard Tray
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	1 Mobile Pedestal, Box/File
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
-0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
- 0420	Cobingt Filing Lateral Half Haight	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
-0420	Cabinet, Filing, Lateral, Half Height	l I	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
=2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
2000	Dane, Wasiepapa, Nouliu, Madi	1	v v	nuising stations.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
/11801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information

7 - OFA07 - Workstation, Workforce Development Coordinator

A1010 Telecommunication Outlet

A1015 Telephone, Desk, Multiple Line

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	Adjustable Keyboard Tray Mobile Pedestal, Box/File
	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
	<u> </u>			
8 - OF <i>F</i>	A07 - Workstation, High Performance Development C		<u> </u>	
JSN	NAME	QTY	ACQ/INS	DESCRIPTION

٧V

٧٧

Telecommunication outlet location.

Telephone, desk, multiple line.

9 - OF <i>A</i>	9 - OFA07 - Workstation, Education Technician								
JSN	NAME	QTY	ACQ/INS	DESCRIPTION					
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.					
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.					

				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair Quival High Dook	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl. Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

10 - CR	A02 - Conference Room			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	facility to hang various items of apparel.
				A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	compliant unit with a load capacity of up to 130 lbs.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.

				Conference chair designed to complement the executive furniture package selected. Foam rubber
F0220	Chair, Conference	10	VV	cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
1 0220	Oldi, collicate	10	V V	Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending
				upon the model selected. These chairs are intended primarily as overflow capacity for conference
F0295	Chair, Stacking	8	VV	rooms.
F0600	Credenza, Executive, Wood	1	VV	Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with adjustable shelf and floor glides.
				Comparison an evistary word station, comparison tally FOII bight V OCII wide V OCII door A fully an elected
EOGOO	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0090	Workstation, Computer, Enclosed, With Lock	1	V V	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying
F0755	Table, Conference, Wood	2	VV	from 74" to 96". These tables add traditional elegance to any conference room.
	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.
1 2000	Dana, Wasapapa, Excalivo, Wood		• •	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression
				components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing
M0507	Video Teleconferencing System	1	VV	capabilities to dispersed geographic sites.
				A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will
				have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may
M0512	Television, HDTV, Large Screen, 60"	2	VV	be LED, Plasma or LCD. TV will include a stand.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat
				panel monitor, keyboard, mouse and speakers. The system shall have the following minimum
				characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-
				ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
				Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of
				sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make
				multiple copies of a single scanning. Single sided version, single copy version, and office size boards
				are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-
				board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level
M1875	Board, Copy, Electronic Facsimile	1	VV	of the supporting frame.

11 - SR	11 - SRS01 - Storage Room						
JSN	NAME	QTY	ACQ/INS	DESCRIPTION			
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.			
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.			

				Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For
				use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price
M205	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

12 - SL	001 - Lounge, Staff			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
				Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with
A1080	Mirror, Posture, Wall Mounted	1	CC	water proof back. For educational and therapy programs.
				Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable
A5075	Dispenser, Soap, Disposable	1	VV	soap cartridge and valve.
				A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features:
				tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	paper towels. For general purpose use throughout the facility.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.
				Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
				Wall mounted television bracket backing which provides additional support and strength for the
				installation of the television bracket. Option available for interior or exterior plate and sized for 12"
A5220	Bracket, Television, Wall Backing	1	CC	16" or 24" stud spacing.
				Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a
				solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment
				elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	general purpose use throughout the facility.
				Standing height under counter base cabinet with four full width drawers of equal height. Also
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	referred to as a drawer cabinet. For general purpose use throughout the facility.
				Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double
				door sink cabinet. For general purpose use throughout the facility where a sink is to be used.
				Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	to ensure that they are compatible.
				Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge
0000			00	configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	a solid hinged single door case. For general purpose use throughout the facility.

CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT000	Countaries Calid Curfees	7	00	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" but backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring
	Countertop, Solid Surface Chair, Dining Room	7	CC	optimum physical and chemical resisting properties. Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
	Table, Dining	1	VV	Dining room chair with grides. Chair has straight regs with cushioned croth of whyr seat. Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility. Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
F3200	Clock, Battery, 12" Diameter	1	VV	unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
V AGGE	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.
				42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC
M0515	Television, Plasma	1	VV	tuner, built-in stereo speakers and surround sound. Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	commercial or residential design and use.

13 - LR001 - Locker Room, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
				Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door
				equipped with safety guard handles. Designed for storage of coats, hats, and other personal
A1030	Locker, 2 Person, Over/Under	4	VV	belongings. Other width and depths are available.
				Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with
A1080	Mirror, Posture, Wall Mounted	1	CC	water proof back. For educational and therapy programs.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
	Mirror, Float Glass, ADA Accessible Dispenser, Soap, Disposable	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available. Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	СС	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	СС	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.

P3000 La	avatory, Vitreous China, Straight Back	1		Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050 To	oilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

2 - NURSING EDUCATION AND TRAINING AREA

1 - OF	A09 - Office, Associate Chief for Nursing Education			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	facility to hang various items of apparel.
				THIS TYPICAL INCLUDES:
				4 Standard Solid Panels
				2 Panel-to-Panel Connectors
				1 Panel Connector, 2-Way Corner
				2 Finished End Hardware
				2 Lockable Flipper Units
				2 Shelves, Storage/Display
				3 Lights
				3 Tackboards
				2 Cantilevered Work Surfaces
				1 Adjustable Keyboard Tray
				1 Mobile Pedestal, Box/File
F0000	W () O F O 70 70			1 Pencil Drawer
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	2 Support Panels
БОООБ	Chair Cida Wish Arma		1/1/	Uphol stered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs.
F0205	Chair, Side With Arms	1	VV	Seat height is a minimum of 17". Available with or without sled base.
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
E007E	Chair Cuival High Dools		1/1/	base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded
FU2/5	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.
				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with
E0400	Cohinet Filing Leteral Holf Height	4	\/\/	recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
FU4ZU	Cabinet, Filing, Lateral, Half Height	T	VV	legal size materials.

				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - SEC	01 - Secretary / Waiting			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
				This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray:
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	1 mobile pedestal, box/file.
E0275	Chair Suivel High Dode	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
r02/5	Chair, Swivel, High Back	I	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven
F0305	Chair, Waiting Room, Single	2	VV	fabric textile or vinyl. Arms and floor glides included.

				Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	locking device. Each drawer has label holder, handle and roller cradle.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

3 - OF	- OFA07 - Workstation, Nursing Instructor					
JSN	NAME	QTY	ACQ/INS	DESCRIPTION		
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.		
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.		
				This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray		
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	1 Mobile Pedestal, Box/File		
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel		
				base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded		
F0275	Chair, Swivel, High Back	1	VV	and upholstered with either woven textile fabric or vinyl.		

				Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	legal size materials.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
				A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	compliant unit with a load capacity of up to 130 lbs.
				Wall mounted television bracket backing which provides additional support and strength for the
				installation of the television bracket. Option available for interior or exterior plate and sized for 12"
A5220	Bracket, Television, Wall Backing	2	CC	16" or 24" stud spacing.
E0000	Observe Aurea Maritim re	00	1/1/	Standard leg chair with 24" x 18" writing tablet. Book basket connected to underside of chair.
F0200	Chair, Arm Writing	30	VV	Minimum distance of seat-to-floor is 17".
				Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel
E0275	Chair, Swivel, High Back	1	VV	base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
10275	Char, Swiver, High Back	1	VV	and upriorsia ed with a the wover textile rabile of virigi.
				Computer operator workstation, approximately 58" high X 36" wide X 25" deep. A fully enclosed
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
. 0000	Tromacatori, Computor, Endrocess, Trian Econ			Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.
				Portable floor lectern with reading light and self-contained audio. May use 110V or batteries (not
F2100	Lectern, Mobile, With Reading Light	1	VV	included). Convenience outlet required if not using batteries.
				Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to
F3010	Board, Bulletin, 48 x 48	1	VV	choose from. Used for posting notes and messages.
				Whiteboard and projection screen combination approximately 48" H x 72" W. Magnetic surface with
				matte finish for projection. Hard board stabilizer with aluminum foil back. For use with water color
F3060	Whiteboard, Projection Screen Combination	1	VV	pens.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
-3200	Clock, Battery, 12" Diameter	1	VV	not included).

JSN	Telecommunication Outlet	1	VV	Telecommunication outlet location.
101	NAME	-	ACQ/INS	
5 - SRS	01 - Storage Room			
M1875	Board, Copy, Electronic Facsimile	1	VV	sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boar are options. May have a PC interface option. Database pricing reflects a mobile two-panel copyboard with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types o printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV mabe LED, Plasma or LCD. TV will include a stand.
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencin capabilities to dispersed geographic sites.
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.

provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

VV

M2055 Shelving, Storage, Wire, CRS, w/Adjustable Shelves

3 - EDUCATION AUDITORIUM AREA

JSN	NAME	ΩTY	ACQ/INS	DESCRIPTION
	Telecommunication Outlet	4	VV	Telecommunication outlet location.
	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
	Public Address System	1	CC	Public address system. System features built-in speaker-microphone for hands-free operation, volume controls, battery backup for power failures, master clock programmer, group all call, and alert tone for emergency situations. Communications distribution system designed for facilities.
F0190	Chair, Auditorium, With Tablet Arm	200	СС	Tablet arm auditorium chair. Chair consists of wood or upholstered arm rest with plastic rear panel and self-rise molded foam over upholstered spring seat. It includes a folding writing surface that stores at the side of the chair. Unit is constructed with 3/16" steel. To be used in auditoriums during conferences or lectures.
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F2105	Lectern, Mobile, With Self Contained Audio	1	VV	Portable floor lectern with built-in public address system. May use 110V or batteries (not included). Convenience outlet required at point of use if not using batteries.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.
M0400	Screen, Projection, 144x144, Remote Control	1	cc	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information

Z - AUL	701 - Stage / Instruction Area		
JSN	NAME	QTY ACQ/INS	DESCRIPTION

A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A4005	Public Address System	1	CC	Public address system. System features built-in speaker-microphone for hands-free operation, volume controls, battery backup for power failures, master clock programmer, group all call, and alert tone for emergency situations. Communications distribution system designed for facilities.
F0190	Chair, Auditorium, With Tablet Arm	200	CC	Tablet arm auditorium chair. Chair consists of wood or upholstered arm rest with plastic rear panel and self-rise molded foam over upholstered spring seat. It includes a folding writing surface that stores at the side of the chair. Unit is constructed with 3/16" steel. To be used in auditoriums during conferences or lectures.
F2015	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F2105	Lectern, Mobile, With Self Contained Audio	1	VV	Portable floor lectern with built-in public address system. May use 110V or batteries (not included). Convenience outlet required at point of use if not using batteries.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

4 - SRS	4 - SRSE1 - Storage, Equipment						
JSN	NAME	QTY	ACQ/INS	DESCRIPTION			
				Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price			
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.			

				Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel,
				galvanized or stainless steel open unit with adjustable shelves. The closed version is also available.
M2070	Shelving, Storage, 77hx36wx18d	2	VV	For use in the storage room.

5 - SRS	5 - SRS02 - Storage, Moveable Furniture						
JSN	NAME	QTY	ACQ/INS	DESCRIPTION			
M2070	Shelving, Storage, 77hx36wx18d	8		Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.			

6 - CR	A02 - Multipurpose Room			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	facility to hang various items of apparel.
				A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA
	Bracket, Television, Wall-Mounted, Tilt/Angle	2		compliant unit with a load capacity of up to 130 lbs.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.
				Conference chair designed to complement the executive furniture package selected. Foam rubber
				cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel
F0220	Chair, Conference	10		casters.
				Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending
				upon the model selected. These chairs are intended primarily as overflow capacity for conference
F0295	Chair, Stacking	8	VV	rooms.
				Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with
F0600	Credenza, Executive, Wood	1	VV	adjustable shelf and floor glides.
				0
F0000	Washinterian Committee Frederical With Look			Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
E0755	Table Conference Was d		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying
	Table, Conference, Wood	2		from 74" to 96". These tables add traditional elegance to any conference room.
F2005	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.
				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
F0000	Olaska Battama 401 Bismastan		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1		not included).
				Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression
140507	Video Telesconferencia a Ocatava	,		components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing
M0507	Video Teleconferencing System	1	VV	capabilities to dispersed geographic sites.

M0512 Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801 Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1875 Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copyboard with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.

7 - TLT	M 2 - Toilet, M ale Public			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	2	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
	Table, Diaper Changing, Wall Mounted	1	CC	Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15 " high, 32" wide and 19" deep.
	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	2	СС	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	cc	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.

A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	2	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
C0041	Rail, Apron, 4x60x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
CT020	Countertop, Solid Surface	5	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F2015	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
P3070	Lavatory, Vitreous China, Under or Counter Top Mtd	2	CC	An undercounter or countertop mounted vitreous china lavatory (approximate bowl size 6"x17"x14") with gooseneck spout, wrist blade handles, and grid drain. Counter top mounted lavatory to be self rimming with mounting kit provided. Undercounter lavatory to have unglazed rim with a mounting kit also provided. For general purpose use in vanity tops in public, patient and staff toilet rooms.
	Urinal, Wall Hung	2	CC	A low consumption (1.0 gallon per flush) vitreous china, wall hung, washout flush action urinal with extended sides, flushing rim, 3/4" inlet spud, 2" I.P.S. female outlet connection and stainless steel strainer. For general purpose use in male toilet rooms.
P9050	Toilet, Wall Hung, Siphon Jet	2	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

8 - TLT	TLTF2 - Toilet, Female Public						
JSN	NAME	QTY	ACQ/INS	DESCRIPTION			
A1067	Mirror, Float Glass, ADA Accessible	2		A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.			
A4995	Table, Diaper Changing, Wall Mounted	1		Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15 " high, 32" wide and 19" deep.			
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.			

A5082	Dispenser, Paper Towel, Sensor, Hands Free	2	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	3	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	cc	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	1	cc	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met.
	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	3	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
C0041	Rail, Apron, 4x60x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
	Countertop, Solid Surface	5	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
D0070	Laurten Witnesse Okina Hadanan Osuntan T. Mill		00	An undercounter or countertop mounted vitreous china lavatory (approximate bowl size 6"x17"x14") with gooseneck spout, wrist blade handles, and grid drain. Counter top mounted lavatory to be self rimming with mounting kit provided. Undercounter lavatory to have unglazed rim with a mounting
P3070	Lavatory, Vitreous China, Under or Counter Top Mtd	2	CC	kit also provided. For general purpose use in vanity tops in public, patient and staff toilet rooms.

P9050 Tollet, Wall Hung, Sipnon Jet 3 CC Tacility.	P9050 Toilet, Wall Hung, Siphon Jet	3	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.
--	-------------------------------------	---	----	---

NAME	QTY	ACQ/INS	DESCRIPTION
Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1		A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop an mop bucket; not included).
Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes
Valve. Mixing. Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
			Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose
	Dispenser, Soap, Disposable Dispenser, Paper Towel, SS, Surface Mounted Dispenser, Glove, Surgical/Examination, Wall Mntd Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd Cart, Janitor's Bucket, Mop, With Wringer, 26 Quart	Dispenser, Soap, Disposable 1 Dispenser, Paper Towel, SS, Surface Mounted 1 Dispenser, Glove, Surgical/Examination, Wall Mntd 1 Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd 1 Cart, Janitor's 1 Bucket, Mop, With Wringer, 26 Quart 1 Eyewash, Wall Mounted, Hands-Free 1	Dispenser, Soap, Disposable 1 VV Dispenser, Paper Towel, SS, Surface Mounted 1 CC Dispenser, Glove, Surgical/Examination, Wall Mntd 1 VV Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd 1 CC Cart, Janitor's 1 VV Bucket, Mop, With Wringer, 26 Quart 1 CC

4 - EDUCATION LABORATORY AREA

10.1	P01 - Computer Lab	6=11	100 "110	DE00D: ==: 0::
JSN	NAME	QTY	ACQ/INS	
A0900	Relay Rack, Aluminum	2	VV	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).
A0901	Cable Management, Horizontal Base Unit	2	VV	Horizontal cable management unit for a 19" rack with a channel approximately 2"x2". Provides for professional finish to hide cables in a switch rack. Various models are quoted with fingered type exits or brackets and/or rear access holes.
A0902	Rear Wire Frame	2	VV	For use with horizontal base unit for double sided management. This item is intended to be used with JSNs A0901 and/or A0903 model HC219 series from Hubbell only.
A0903	Rear Hinged Cover, for LAN Rack	2	VV	This item is intended to be used with JSNs A0901 and/or A0902 model HC219 series from Hubbell only. This cabinet is designed to accommodate up to 6 six-packs of adapters or blank panels. This cabinet
A0904	Fiber Optic Cabinet, 36 Port, Rack Mounted	2	VV	is specifically designed to accommodate Hubbell adapter panels as reflected in JSNs A0905 and A0906.
A0905	Adapter Panel With Couplers, Blue, 6 Port, SM/MM	2	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style blue adapters, standard density.
A0906	Adapter Panel With Couplers, Yellow, 6 Port, SM/MM	2	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style Yellow adapters, standard density.
A0908	Patch Panel, 110 Block/RJ-45, Cat 5E, 48 Port,568A	1	VV	This 48 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI).
A0910	Patch Panel, 110 Block/RJ-45, Cat 5E, 96 Port,568A	2	VV	This 96 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI).
A0911	Power Supply, Uninterruptable, Rack Mounted	2	VV	Uninterruptable Power Supply, Approximately 2200V A/1600W, Rack Mount with extendable Run Time. Unit must incorporate hot user swappable batteries and must have an overload indicator, replace battery indicator, audible alarm, automatic voltage regulation and include Smart Slot card and software. It must use RS232 DB-9 interface for communication. NEMA L5-30P power connector, and (8) NEMA 5-15R outlets.
A0913	Switch, Local Area Network (LAN)	1	VV	Omni switch router, 9 slot chassis, 725W AC power supply and rack mount brackets. Supports high speed frame switching fabric. Software and Manual included. Requires management module JSN A0914 and works with Power Supply A0915.
	Management Processor Module for LAN Switch	1	VV	Management processor module with 10BaseT with layer-3 switching (HRE-X); 32 MB DRAM & 8 MB flash memory. Operates over the 22G distributed switching fabric. Works with Switch LAN JSN A0913 and Power Supply A0915.
	Power Supply, 725 W, for LAN Switch	1	VV	725 Watt powersupply. Redundant or spare power supply for the 9 slot Omni Switch Router. Works with Switch LAN JSN A0913 and Management Processor JSN A0914.
AUSIS	rowa Suppry, 725 W, Tor LAIN SWITCH	1	VV	High Density Fast Ethernet desktop switching module. Thirty-two 10/100Base TX switching ports, RJ-45 connectors. Supports Cat 5 twisted pair cable-100 ohm and CAM support for 1024 MAC
A0916	Switching Module, Desktop, Fast Ethernet	1	VV	addresses.

				Gigabit Ethernet server switching module. Four 1000 base SX switching ports, SC connectors.
				Supports multi-mode fiber optic cable and CAM support for 4096 MAC addresses. Must be used in
A0917	Switching Module, MM Fiber, Gigabit Ethernet Server	1	VV	the Omni Switch/Router product only.
				Gigabit Ethernet server switching module. Four 1000 Base LX switching ports, SC connectors.
				Supports single mode fiber optic cable and CAM support for 4096 MAC addresses. Must be used in
A0918	Switching Module, SM, Gigabit Ethernet Server	1	VV	the Omni Switch/Router product only.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
				Uninterruptible power supply (UPS) available in 208, 480 or 600 VAC configuration. Used in areas
				where power protection is required for large computer systems, communication equipment,
				radiographic equipment, etc. The UPS is used to keep the equipment on line or safely turn the
A6200	Uninterruptible Power Supply, Three Phase	1	CC	equipment off in the event of a power loss.
				Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star
F0230	Chair, Drafting, Rotary	1	VV	base with casters. Padded seat and back. Foot ring adjusts with chair.
				Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect
				and temporarily store small quantities of paper refuse in patient rooms, administrative areas and
F2000	Basket, Wastepaper, Round, Metal	1	VV	nursing stations.

2 - CR/	A02 - Video Conference Room			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
				A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed
				mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	facility to hang various items of apparel.
				A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	compliant unit with a load capacity of up to 130 lbs.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.
				Conference chair designed to complement the executive furniture package selected. Foam rubber
				cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel
F0220	Chair, Conference	10	VV	casters.
				Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending
				upon the model selected. These chairs are intended primarily as overflow capacity for conference
F0295	Chair, Stacking	8	VV	rooms.
				Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with
F0600	Credenza, Executive, Wood	1	VV	adjustable shelf and floor glides.
				Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
				Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying
F0755	Table, Conference, Wood	2	VV	from 74" to 96". These tables add traditional elegance to any conference room.
F2005	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.

				Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted
				unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries
F3200	Clock, Battery, 12" Diameter	1	VV	not included).
				Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression
				components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing
M0507	Video Teleconferencing System	1	VV	capabilities to dispersed geographic sites.
				A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will
				have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may
M0512	Television, HDTV, Large Screen, 60"	2	VV	be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
				Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copyboard with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level
M1875	Board, Copy, Electronic Facsimile	1	VV	of the supporting frame.

3 - CLR	R07 - Simulation Lab			
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1122	Column, Equipment Arm, Ceiling Mounted, Surgery	1	CC	A ceiling mounted retractable equipment arm for use in the OR. Designed to provide equipment placement support, power receptacles including low-voltage panels, gas outlets and flat screen mounting for a surgical suite. Unit will provide a range of motion of up to 330 degrees with arm providing additional vertical movement. Units are custom configured with multiple options available. Price is based on a unit with two (double) retractable arms. Also available are units for use in anesthesia, ICU and ER.
A1130	Cabinet, Control, Nitrogen	1	СС	Nitrogen control cabinet. Unit consists of supply cut-off valve, supply pressure gauge, pressure regulator (adjustable 0 to 200 PSI), outlet pressure gauge, nitrogen outlet and connection to surgical gas column. Specify recessed or surface mounting. Designed for powering surgical pneumatic tools.
A4015	Clock, Elapsed Time, Electric	1	СС	Elapsed time digital electric clock. Single display time that can be used either as a clock or elapsed time indicator. Clock consists of buttons to set minutes, and hours for the time. For use in operating and delivery room, and medical service columns. Analog or digital displays may be provided as specified by the user.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	2	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.

				A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for
A5108	Waste Disposal Unit, Sharps	1	VV	handling sharps.
E0130	Workstation, Documentation, OR, L-Shaped	1	VV	A 60" L-shaped documentation workstation for use in the OR. The workstation may be either a right or left hand configuration. It will consist of a back panel with dry-erase whiteboard, marker storage tray, optional mounting for monitors, an articulating task light and a keyboard tray. The workstation will also include electrical, data, telecommunication and video cable channels and wire ways to support various applications. An integrated power source will be desk-top mounted and provide two electrical outlets, a telephone jack and a computer network jack. Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically
F0355	Footstool, Straight	1	VV	conductive rubber tips.
	Camera, Video Surveillance, HD, IP Powered	1	VV	A high definition, full functional video surveillance camera. The camera is capable of full 1080p resolution at 30 frames per second while optimizing network usage with H.264, MPEG-4 and JPEG compression formats. Camera will have an open, standards-based design providing a platform for integration and operation as an independent device or as part of a surveillance network.
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M0630	Anesthesia Apparatus, 3 Gas	1	VV	Three gas anesthesia apparatus. Basic unit consists of steel cabinet with casters with one shallow, one medium, and one deep drawer, seven long scale eleven-inch flowmeters, five cylinder yokes, and telescoping absorber post. It includes two-canister model carbon dioxide absorber with inhalation and exhalation check valves, switch valve, switch valve elbow, sidearm Vernitrol, flow calculator, mounting kit, ventilator calculator, ventilator and an oxygen piping inlet. Also features nitrous oxide fail safe valve kit, aspirator kit, gas evacuator with vacuum and a flow meter safety cover. Used to dispense a mixture of gases during surgical procedures.
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.

M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
				Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	monitor. The computer is used throughout the facility to input, manipulate and retrieve information. A biohazard waste container with a step-on lid. The container will have a capacity of approximately
M3073	Container, Biohazard Waste, Step-on, Fire Safe	1	VV	12 gallons and be made of a fire safe material.
				Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball
M4255	Stand, IV, Adjustable	1	VV	bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	1	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M4815	Hypo/Hyperthermia Unit, Automatic/Manual, Mobile	1	VV	Automatic/manual hypo/hyperthermia unit. Sealed refrigeration system. Microprocessor controlled with multiple alarm system constantly monitoring temperature and water levels. Cabinet type unit. Designed to regulate body temperature by application of water-filled hypothermia blankets.
M4816	Warming Unit, Patient, Automatic/Manual, Air	1	VV	Automatic/manual patient warming unit. Unit delivers a flow of warmed air through a perforated plastic blanket. Used primarily for postoperative patients to speed recovery of normal body temperature.
M5030	Stool, Surgeon, Revolving	1	VV	Revolving stool. Consists of a padded upholstered seat with height adjustment. Unit rotates and is mounted on ball bearing swivel casters. Designed for use in examinations, treatment, and surgical procedures.
	Light, Surgical, Ceiling Mounted, Single, Medium	1	VC	Single ceiling mounted surgical light with a light head diameter generally between 21" and 30" depending on the manufacturer. The light is mounted from a pole extending down from the ceiling and then from a pivotal arm assembly that rotates 360 degrees. It includes a variable intensity control and sterile focus handle. The minimum ceiling height for most models is 8'-9"; check the manufacturers' specific recommendations. The database height dimension below refers to the lamp head housing itself. Width and depth are the length of the swing arm plus the diameter of the light head. This light can be used for both minor and major surgical procedures.

M7845	Monitor, Physiological, Bedside, 4 Channel	1	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.
	Laryngoscope, Video Glidescope	1	VV	A video-assist laryngoscope system with a digital color monitor and digital camera providing real-time view of the airway enabling quick intubation. Unit is designed for first pass success. The unit includes a reusable video baton with digital camera and sterile single use GVL Stats in various sizes.
M8551	Light Source, Fiberoptic Headlamp	1	VV	Fiberoptic light source for surgical headlamps. This unit provides color corrected light for surgical procedures where photography is not required.
M8555	Insufflator, Automatic Controls	1	VV	Automatic controlled insufflator is used to infuse CO2 during endoscopic and laser surgery. Unit provides controlled pressure of CO2 within the cavity of interest and eliminates air from the site. This item is also a component of the JSN M8605-M8607 and M8610-M8611 endoscopy carts.
M8606	Endoscopy Cart, Fiberoptic, w/Video Accessories	1	VV	Endoscopy cart with video and print capabilities for use with fiberoptic (direct vision) endoscopes. This cart does not work with videoscopes. System takes optical images from a single endoscope and directly records them or converts them to digital signals for recording. A typical system cart includes the cart, a light source, an insufflator, a suction unit, a heat probe unit, an electrosurgical apparatus, a digital camera converter or color video camera, a camera controller, a monitor, a video/DVD recorder and a color printer. This JSN does not include the endoscope; refer to the endoscopes at JSNs M8500-M8550. Each cart can support one or more types of endoscope and should be specifically tailored to its intended use(s). This cart can be configured to interface with a network endoscopy information management system; refer to JSN M8600. Database physical information and pricing is for a higher cost system containing one of each of the above components.
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.
M8910	Cart, Surgical Case	1	VV	Surgical case cart. Unit consists of two hinged cabinet sections, each section equipped with two pull- out shelves with stops. The entire unit is mounted on four heavy duty conductive swivel casters. Used to transport surgical packs and supplies to surgery and soiled items back to central supply.
	Table, Operating, 5 or 6 Section, Trauma	1	VV	Pedestal type, 5 or 6 section, operating table. Pedestal table, mounted on a solid base with casters and locks. Table top surface is fabricated from radio-translucent and conductive panels and is equipped with cassette tunnels in each of the table top sections. Table includes: Electro-hydraulic controls, side rail locking system, grounding receptacle and dual arm support section. It is designed for use in the operating room in a variety of surgical procedures. Table is configured to address the needs of trauma surgery.

X3150 Rack, Apron/Gloves, Wall Mounted	1	CC	Apron and gloves rack. This is a wall unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum. The unit's convenient on wall storage will prolong the useful life of your protection aprons by helping prevent damage to internal components.
V4400 0			Two monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on a two 2048 X 1536 image display monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball
X4122 Console, PACS, Remote View, w/Two 3MP Monitors	1	VV	or voice activated commands.