

maharam

ations Court
ppaugs, NY 11788
631.582.3434
631.342.0264 - Fax

Directions 8

Recommendations for application and maintenance

Control of delivery	Be certain pattern and color are as ordered. All material must be installed in numerical roll sequence within a lot. Never use wallcoverings from different production runs on one wall. Hang in sequence as cut from the roll and avoid infilling.
Attention	Defects in the material can be noticed after hanging three lengths. Should this happen, you should notify your representative immediately. We cannot accept any claims on labor or material after more than three lengths have been cut and applied.
Work neatly	Avoid getting adhesive on the wallcovering surface. Any excessive adhesive should be removed immediately with a sponge and clear water; then dried with a towel. These recommendations for application and maintenance are intended only as a guideline; the installer is accountable for proper installation. Great care has been taken in the production of this vinyl wallcovering; however, variation in texture and color can occur.
Wall preparation	Walls should be structurally sound, dry, smooth, firm, free from dust and grease, uniform in color and normally absorbent. Remove old wallcovering, loose paint layers, ballpoint and crayon marks. Water-soluble paint should be washed down while oil-based paint should be sandpapered and cleaned with ammonia. Walls must be primed using a water-based primer for wallcovering. New plaster walls and drywall should be primed with oil-based or alkyd primer for wallcovering.
Adhesive	Use a heavy-duty, pre-mixed, vinyl adhesive, do not dilute.
Wall application	Store wallcovering for 72 hours at 70°F. Install at similar temperature. Apply an even coat of adhesive to the fabric side of material using a stiff bristle brush or roller. If there is no design repeat (random texture) patterns should normally be reverse hung. The wallcovering should be applied to the wall within 12 minutes. When pasting several strips in advance, booking and rolling is recommended to insure proper wetting of the fibers and no drying of paste on the edges. Smooth surface, working out air bubbles and remove excess paste immediately with clear warm water, sponge, soft bristle brush if necessary, and clean towels.
Maintenance	Directions 8 vinyls are scrubbable and are easily cleaned using mild soap and warm water. For more stubborn stains, use rubbing alcohol.
Warranty	Maharam warrants that for a period of five years its vinyl wallcoverings are guaranteed to be first quality and free of manufacturing defects. This warranty applies only to commercial installations, professionally installed according to our recommended hanging instructions.
Memo samples	Memo samples are available for all our fabrics. We suggest that you obtain a memo sample of our large-scale designs in order to view full pattern effect.

maharam


Research and Development

45 Rasons Court
Hauppauge, NY 11788
631.582.3434
631.342.0264 Fax

To	[REDACTED]	Date	July 9, 2002
From	Research and Development	Pages	1 of 2
Subject	Vesta		

Fax Transmittal


Maharam guarantees that the above referenced wallcovering pattern will perform in accordance with generally accepted industry standards when used under normal conditions and for the purpose intended for a period of five years from the date of purchase.



maharam

45 Re ff
Haupt: 4Y 11788
031.582.3434
631.342.0264 - Fax


July 18, 2002



Dear Gentlemen,

This is confirmation that the wallcovering installers of the Blakely Co. are certified in all aspect of the applications of the installation of the wallcovering furnished for the above job.

Sincerely,



THE BLAKELY CO.

INCORPORATED

PAINTING CONTRACTORS

LICENSE NO. 195215

5533 ALHAMBRA AVENUE • LOS ANGELES, CALIFORNIA 90032 • PHONE (323) 221-4732

July 19, 2002

Dear [REDACTED]

The Following is contractor information required per Section 01781 – Article 1.3.1
Data Package 1:

[REDACTED]

Sub Contractor – Work Performed:
Sections
09721 Vinyl Fabric Wallcovering
09900 Paints and Coatings

The Blakely Co.
5533 Alhambra Ave
Los Angeles, Ca 90032

If there are any questions, please feel free to contact us.

Sincerely,

[REDACTED]