



## DEPARTMENT OF DEFENSE EXPLOSIVES SAFETY BOARD

4800 MARK CENTER DRIVE, SUITE 16E12  
ALEXANDRIA, VIRGINIA 22350-3606

31 MAY 2023

DDESB-PE

MEMORANDUM FOR DIRECTOR, U.S. ARMY DEFENSE AMMUNITION CENTER  
(ATTENTION: ATCL-ACE)

SUBJECT: Approval of 7-Bar Structural Strength Designation for Earth-Covered Magazine  
(ECM) Series 421-80-08 Revision 1

References: (a) U.S. Army Defense Ammunition Center ATCL-ACE Memorandum, 15 March 2023, Subject: Request DDESB Final Approval for the Earth-Covered Magazine (ECM) Series 421-80-08 Revision 1 as a 7-bar magazine.

(b) U.S. Army Corps of Engineers, Engineering and Support Center, Huntsville, Modular Storage Magazine, Box-Type STD 421-80-08 with 14'-8" Door (Revision 1), dated May 2023

(c) Defense Explosives Safety Regulation 6055.09, Edition 1, 13 January 2019

(d) U.S. Army Corps of Engineers, Engineering and Support Center, Huntsville, Modular Storage Magazine, Box-Type STD 421-80-08 with 14'-8" Door, dated June 2013

(e) DDESB Technical Paper 15, "Approved Protective Construction," Revision 4, 26 July 2020

As requested by reference (a), we have reviewed the reference (b) drawings for compliance with Department of Defense explosives safety criteria found in reference (c). Attachments to reference (a) describe the modifications that have been incorporated into those drawings. Based on our evaluation, the design contained in reference (b) is approved as a 7-Bar earth-covered magazine (ECM). This new design supersedes the original 421-80-08 magazine design of reference (d).

The maximum allowable Hazard Division (HD) 1.1 explosive limit for the reference (b) design is 500,000 pounds net explosive weight (NEW).

The revised drawing set of reference (b) incorporates lessons learned from previous construction projects, corrects omissions within the drawings, and improves constructability of the structure. It also incorporates a cast-in-place topping slab over the roof panels for improved seismic performance. The design includes modifications to the blast door detailing for an updated locking system and revised welded connections between door components. Structural steel with a minimum yield strength of 50 ksi is specified for the blast door based on current industry standards and material availability.

The design of reference (b) will be added to Table AP1-1 of reference (e) as approved for new construction, and reference (d) will be relocated from Table AP1-1 to Table AP1-2 and considered not approved for new construction.

Point of contact is Mr. Ryan Bowers at Commercial: (571) 372-6706; DSN: 372-6706; or E-mail: [ryan.w.bowers.civ@army.mil](mailto:ryan.w.bowers.civ@army.mil).



THIERRY L. CHIAPELLO  
Executive Director

Cc:  
USACE CEHNC-EDC-S  
NAVFAC EXWC/SH21  
NOSSA  
USATCES  
AFSEC/SEW  
MARCORSYSCOM/AM-EES