

\*\*\*\*\*  
USACE / NAVFAC / AFCEA UFGS-12301N (September 1999)  
-----  
Preparing Activity: NAVFAC Replacing without revision  
NFGS of same number and date

UNIFIED FACILITIES GUIDE SPECIFICATIONS

References are in agreement with UMRL dated 25 June 2004

\*\*\*\*\*

SECTION TABLE OF CONTENTS

DIVISION 12 - FURNISHINGS

SECTION 12301N

MANUFACTURED VANITIES

09/99

PART 1 GENERAL

- 1.1 REFERENCES
- 1.2 SUBMITTALS
- 1.3 DELIVERY, STORAGE, AND HANDLING

PART 2 PRODUCTS

- 2.1 VANITIES
  - 2.1.1 Quantity
- 2.2 FINISHES
  - 2.2.1 Exposed Surfaces
  - 2.2.2 Concealed Surfaces
- 2.3 END CURBS
- 2.4 DRAWERS
- 2.5 SOURCE QUALITY CONTROL

PART 3 EXECUTION

- 3.1 INSTALLATION
  - 3.1.1 Final Assembly
  - 3.1.2 Fastening

-- End of Section Table of Contents --

\*\*\*\*\*  
USACE / NAVFAC / AFCEA UFGS-12301N (September 1999)  
-----  
Preparing Activity: NAVFAC Replacing without revision  
NFGS of same number and date

## UNIFIED FACILITIES GUIDE SPECIFICATIONS

References are in agreement with UMRL dated 25 June 2004

\*\*\*\*\*

### SECTION 12301N

#### MANUFACTURED VANITIES 09/99

\*\*\*\*\*

NOTE: This guide specification covers the requirements for vanities for Bachelor Enlisted Quarters (BEQ).

Comments and suggestions on this guide specification are welcome and should be directed to the technical proponent of the specification. A listing of technical proponents, including their organization designation and telephone number, is on the Internet.

Recommended changes to a UFGS should be submitted as a Criteria Change Request (CCR).

Use of electronic communication is encouraged.

Brackets are used in the text to indicate designer choices or locations where text must be supplied by the designer.

\*\*\*\*\*

\*\*\*\*\*

NOTE: Lavatories and wall base, if desired, must be specified in other sections. If the project requires custom wood millwork such as required in locations like the Marine Corps Air Station, Cherry Point and Marine Corps Base, Camp Lejeune, North Carolina, do not use this section. Custom wood vanities require the designer to show elevations, sections, and details which clarify materials, thicknesses, size, finishes, and support framing on the contract drawings and use Section 06200N FINISH CARPENTRY to specify the product.

\*\*\*\*\*

## PART 1 GENERAL

### 1.1 REFERENCES

\*\*\*\*\*

NOTE: Issue (date) of references included in project specifications need not be more current than

provided by the latest guide specification. Use of  
SpecsIntact automated reference checking is  
recommended for projects based on older guide  
specifications.

\*\*\*\*\*

The publications listed below form a part of this specification to the  
extent referenced. The publications are referred to within the text by the  
basic designation only.

U.S. DEPARTMENT OF COMMERCE (DOC)

PS1 (1995) Construction and Industrial Plywood  
(APA V995)

U.S. GENERAL SERVICES ADMINISTRATION (GSA)

FED-STD-595 (Rev B; Am 1) Colors, Volume 1

FS A-A-50565 (Basic) Cabinet, Storage; Wardrobe, Three  
Drawer

FS A-A-50567 (Basic; Notice 1) Vanity; Cabinet (Wood or  
Wood and Steel)

1.2 SUBMITTALS

\*\*\*\*\*

NOTE: Submittals must be limited to those necessary  
for adequate quality control. The importance of an  
item in the project should be one of the primary  
factors in determining if a submittal for the item  
should be required.

A "G" following a submittal item indicates that the  
submittal requires Government approval. Some  
submittals are already marked with a "G". Only  
delete an existing "G" if the submittal item is not  
complex and can be reviewed through the Contractor's  
Quality Control system. Only add a "G" if the  
submittal is sufficiently important or complex in  
context of the project.

For submittals requiring Government approval on Army  
projects, a code of up to three characters within  
the submittal tags may be used following the "G"  
designation to indicate the approving authority.  
Codes for Army projects using the Resident  
Management System (RMS) are: "AE" for  
Architect-Engineer; "DO" for District Office  
(Engineering Division or other organization in the  
District Office); "AO" for Area Office; "RO" for  
Resident Office; and "PO" for Project Office. Codes  
following the "G" typically are not used for Navy  
projects.

Submittal items not designated with a "G" are  
considered as being for information only for Army  
projects and for Contractor Quality Control approval

for Navy projects.

\*\*\*\*\*

Government approval is required for submittals with a "G" designation; submittals not having a "G" designation are [for Contractor Quality Control approval.] [for information only. When used, a designation following the "G" designation identifies the office that will review the submittal for the Government.] The following shall be submitted in accordance with Section 01330 SUBMITTAL PROCEDURES:

SD-02 Shop Drawings

Vanities; [G]

Show configuration, materials, thicknesses, hardware, finishes, and colors of vanities for the project.

### 1.3 DELIVERY, STORAGE, AND HANDLING

Deliver vanities undamaged and store in a safe, dry, and clean location. Handle so as to prevent damage.

## PART 2 PRODUCTS

### 2.1 VANITIES

\*\*\*\*\*

**NOTE:** Insert type and size required. Sizes listed are included in FS A-A-50567 and should be used unless otherwise approved by the Engineering Field Division Code 04 in writing. If other sizes are required, determine whether modification of door/intermediate panel configuration is required to maintain proper door size and structural support.

\*\*\*\*\*

FS A-A-50567, [Type I (single lavatory, double doors), Size [A (750 mm30 inches wide)] [B (900 mm36 inches wide)] [C (1050 mm42 inches wide)] [D (1200 mm48 inches wide)]] [Type II (double lavatory, two sets of double doors), Size A (1500 mm60 inches wide)] [Type [\_\_\_\_], except size shall be [as indicated] [[\_\_\_\_] mm inches wide]], and except as specified herein. Wood construction shall be used. Particleboard shall not be used. Countertop, doors, and all wood panels shall be 20 mm 3/4 inch plywood, PS1, Exterior Type, Grade A-A. Chromium-plated brass pulls or aluminum pulls and chromium-plated, spring-loaded, self-closing, adjustable, European type hinges may be used in lieu of pulls, hinges, and magnetic catches specified in FS A-A-50567.

#### 2.1.1 Quantity

[\_\_\_\_] [As indicated].

### 2.2 FINISHES

\*\*\*\*\*

**NOTE:** Since a wood or steel constructed vanity is the Contractor's option, specify finish, pattern, and color for laminated plastic for both and a paint color for steel.

\*\*\*\*\*

Five-digit designations refer to FED-STD-595.

#### 2.2.1 Exposed Surfaces

Exterior of doors and exposed surfaces of cabinet body shall be decorative laminated plastic of color and pattern [indicated] [specified].

#### 2.2.2 Concealed Surfaces

Interior of doors and cabinet body, and concealed exterior surfaces of cabinet body, shall be nondecorative laminated plastic.

#### 2.3 END CURBS

\*\*\*\*\*

**NOTE: Delete this paragraph if end curbs are not required.**

\*\*\*\*\*

Provide end curbs to match back splash where end of countertop abuts a wall.

#### 2.4 DRAWERS

\*\*\*\*\*

**NOTE: Delete this paragraph if drawers are not required.**

\*\*\*\*\*

Where drawers are indicated in vanities, comply with FS A-A-50565 for drawers, drawer slides, and slide supports.

#### 2.5 SOURCE QUALITY CONTROL

Sampling and Examination: FS A-A-50567.

### PART 3 EXECUTION

#### 3.1 INSTALLATION

##### 3.1.1 Final Assembly

Distribute vanities to rooms [as indicated] [as directed]. Uncrate, assemble, adjust as necessary, and place as specified or indicated, complete with accessories and hardware. Position vanities [as indicated] [as directed].

##### 3.1.2 Fastening

\*\*\*\*\*

**NOTE: Ensure that work referred to is actually specified in the referenced sections.**

\*\*\*\*\*

Fasten wood vanities as specified in FS A-A-50567. Fasten steel vanities through the holes in vanity back flanges. Fasteners shall be appropriate for use with the wall construction. Seal joint between back splash and wall and between end curb and wall as specified in Section 07920 JOINT

SEALANTS.

-- End of Section --