

**265 OUTPATIENT-PACT CLINIC****A. FA1: LOBBY / RECEPTION AREA****1. Vestibule (LOB02)**

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A6046	Artwork, Decorative w Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A

**2. Alcove, Wheelchair (SRLW1)**

M4705	Wheelchair, Patient Transport, Folding	1	VV	Folding patient transport wheelchair. Constructed of chrome plated steel with detachable armrest and footrests. Unit has heavy duty front casters with sealed radial high-precision ball bearing assembly. Unit is used for patient transport.	N/A
M4710	Wheelchair, Patient, Bariatric, Transport, Folding	1	VV	Folding bariatric patient transport wheelchair with a capacity of at least 500 lbs. Constructed with a heavy duty steel frame and double cross brace, with detachable armrest and swing away footrests. Unit has heavy duty front casters and rear wheels with precision wheel bearings in front and rear assembly. Unit is used for patient movement.	N/A

**3. Waiting, PACT 1 (WRC04)**

A5210	Bracket, Television, Wall Mounted, w/Adjust Arm TV 26" – 46"	1	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units.	05 50 00
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
F0206	Chair, Side, Bariatric, With Arms	7	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0305	Chair, Waiting Room, Single	26	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.	N/A
F0740	Table, Occasional Lamp	1	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40" diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	N/A

**4. Waiting, PACT 2 (WRC05)**

A5210	Bracket, Television, Wall Mounted, w/Adjust Arm TV 26" – 46"	5	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units.	05 50 00
-------	--	---	----	--	----------

A5220	Bracket, Television, Wall Backing	5	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
F0206	Chair, Side, Bariatric, With Arms	23	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0305	Chair, Waiting Room, Single	87	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.	N/A
F0740	Table, Occasional Lamp	5	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).	N/A
F2000	Basket, Wastepaper, Round, Metal	5	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2300	Rack, Magazine, Wall Mounted	5	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.	N/A
F2310	Rack, Pamphlet, Wall Mounted	5	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3200	Clock, Battery, 12" Diameter	5	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0506	Television, Flat Screen	5	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	N/A

**5. Waiting, PACT 3 (WRC06)**

A5210	Bracket, Television, Wall Mounted, w/Adjust Arm TV 26" – 46"	8	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units.	05 50 00
A5220	Bracket, Television, Wall Backing	8	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
F0206	Chair, Side, Bariatric, With Arms	38	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0305	Chair, Waiting Room, Single	161	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.	N/A
F0740	Table, Occasional Lamp	8	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).	N/A
F2000	Basket, Wastepaper, Round, Metal	8	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2300	Rack, Magazine, Wall Mounted	8	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.	N/A
F2310	Rack, Pamphlet, Wall Mounted	8	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3200	Clock, Battery, 12" Diameter	8	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0506	Television, Flat Screen	8	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	N/A

**6. Waiting, PACT Family (WRF01)**

A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.	05 50 00
-------	---	---	----	---	----------

A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
A6046	Artwork, Decorative w Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0305	Chair, Waiting Room, Single	3	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2045	Furniture, Playroom	1	VV	Assorted playroom furniture. Part of the interior design package. Exact configuration to be determined by using activity. Vendors listed for reference.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0515	Television, Plasma	1	VV	Flat screen television with approximately 32" to 40" diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	N/A

**7. Reception (RECP3)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	12 32 00
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A

**8. Reception, Accessible (RECP5)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00

A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	12 32 00
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A

**9. Kiosk, Patient Check-in (RECP4)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, wall mounted, 1 line.	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A6046	Artwork, Decorative w Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
M1890	Kiosk, Educational, Stand-Up	2	VV	Armless stacking chair scaled for use by children. Lightweight and available with a choice of different seat heights.	N/A

**10. Alcove, Volunteer (NCWD4)**

A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.	12 32 00
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	1	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.	12 32 00
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A

F3025	Board, Bulletin, Wood Framed	1	CC	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.	10 11 23
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.	N/A

**11. Workstation, Patient Education (CLSC2)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A

**12. Toilet, Public (TLTU1)**

A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	10 28 00

A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on" wastepaper basket with inner liner and foot pedal activated flip top.	N/A
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.	10 28 00
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.	10 28 00

**13. Toilet, Family (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**14. Toilet, Male (TLTM2)**

A1067	Mirror, Float Glass, ADA Accessible	2	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A4995	Table, Diaper Changing, Wall Mounted	1	CC	Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15" high, 32" wide and 19" deep.	10 28 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5082	Dispenser, Paper Towel, Sensor, Hands Free	2	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00

A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	2	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
C0041	Rail, Apron, 4x60x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.	12 32 00
CT020	Countertop, Solid Surface	5	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.	N/A
P3070	Lavatory, Vitreous China, Under or Counter Top Mtd	2	CC	An undercounter or countertop mounted vitreous china lavatory (approximate bowl size 6"x17"x14") with gooseneck spout, wrist blade handles, and grid drain. Counter top mounted lavatory to be self rimming with mounting kit provided. Undercounter lavatory to have unglazed rim with a mounting kit also provided. For general purpose use in vanity tops in public, patient and staff toilet rooms.	10 28 00
P8150	Urinal, Wall Hung	2	CC	A low consumption (1.0 gallon per flush) vitreous china, wall hung, washout flush action urinal with extended sides, flushing rim, 3/4" inlet spud, 2" I.P.S. female outlet connection and stainless steel strainer. For general purpose use in male toilet rooms.	10 28 00
P9050	Toilet, Wall Hung, Siphon Jet	2	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.	10 28 00

**15. Toilet, Female (TLTF2)**

A1067	Mirror, Float Glass, ADA Accessible	2	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A4995	Table, Diaper Changing, Wall Mounted	1	CC	Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15" high, 32" wide and 19" deep.	10 28 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5082	Dispenser, Paper Towel, Sensor, Hands Free	2	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	3	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	10 28 00

A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5110	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	1	CC	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	10 28 00
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	3	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
C0041	Rail, Apron, 4x60x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.	12 32 00
CT020	Countertop, Solid Surface	5	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.	N/A
P3070	Lavatory, Vitreous China, Under or Counter Top Mtd	2	CC	An undercounter or countertop mounted vitreous china lavatory (approximate bowl size 6"x17"x14") with gooseneck spout, wrist blade handles, and grid drain. Counter top mounted lavatory to be self rimming with mounting kit provided. Undercounter lavatory to have unglazed rim with a mounting kit also provided. For general purpose use in vanity tops in public, patient and staff toilet rooms.	10 28 00
P9050	Toilet, Wall Hung, Siphon Jet	3	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.	10 28 00

## B. FA2: Patient Aligned Care Team (PACT) Clinic 1

### 1. Alcove, Height / Weight Station (PEHW1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder	N/A
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.	N/A



F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M4040	Scale, Weighing, 300 Pound Capacity	1	VV	Person weighing scale with 300 pound capacity. Unit consists of a rugged base frame of 3/32" thick steel with a non-slip surface and a speedometer dial with ultra sensitive registering mechanisms. Scale is designed for medical use.	N/A

## 2. Alcove, Height / Weight Accessible Station (PEHW2)

M4045	Scale, Wheelchair, Portable, 1000 lb Capacity	1	VV	A battery operated, portable, digital wheelchair scale. This item is designed to accommodate extra-wide wheelchairs for weighing bariatric patients and also can be used for walk-ons. The scale can store the weight of the chair. The digital display unit can be scale mounted or mounted on a wall. An optional AC adapter is available. Designed for a gross 1000 lbs. capacity.	N/A
-------	---	---	----	---	-----

## 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00

CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 32 00
F0205	Chair, Side With Arms	3	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F0740	Table, Occasional, Lamp	1	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A

#### 4. Exam Room, Patient Aligned Care Team (PACT) (EXPA1)

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.	N/A

A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 32 00
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3025	Board, Bulletin, Wood Framed	1	CC	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	

M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A
M4040	Scale, Weighing, 300 Pound Capacity	1	VV	Person weighing scale with 300 pound capacity. Unit consists of a rugged base frame of 3/32" thick steel with a non-slip surface and a speedometer dial with ultra sensitive registering mechanisms. Scale is designed for medical use.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armband. Unit is designed for general use in examination/treatment rooms.	N/A

### 5. Toilet, PACT Patient (TLTU1)

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

### 6. Exam Room, Women's Health (EXW01)

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line	27 31 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.	N/A

A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3025	Board, Bulletin, Wood Framed	1	CC	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A

M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.	N/A

### 7. Toilet, Women's Health Exam Room Patient (TLTF1)

A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	10 28 00
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00

A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.	10 28 00
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.	10 28 00

**8. Procedure Room, General (TRPR1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A1132	Rail, Accessory Mounting, Length As Required	1	VV	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall.	10 28 00
A1200	Lift System, Overhead, Patient Room	1	CC	An overhead rail system specifically designed for patient lifting and movement for a single bed patient room. The system will consist of recessed or ceiling mounted primary and secondary rails, lift motor with rolling carriage, patient harness or seat, and a hand controller or control box with charger. System will facilitate lifting and movement of patient to and from bed to gurney, chair or other requirement. Minimum lift capability is 550 pounds. Custom design of track layout by manufacturer is essential to meet individual facility requirements.	11 73 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	14	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00

CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00
E0915	Locker, Supply, Medication, Wall Mtd, 23"W x 20"D	1	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Locked Drawer w/Locked Lid, 6"H 5 Drawers, 3"H 3 Drawers, 6"H 2 Tray/Shelves Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3025	Board, Bulletin, Wood Framed	1	CC	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.	22 63 00
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.	22 63 00



M0765	Regulator, Vacuum	2	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.	22 63 00
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.	N/A
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A

M7405	Light, Exam, Ceiling Mounted	1	CC	Ceiling exam light. Consists of a lightheaded reflector supported by a ceiling mounted radial arm assembly that provides a wide range of positioning capabilities. Halogen bulbs and an intensity control provide cool, color corrected light. The minimum ceiling height in most cases is 8'-0"; refer to each manufacturer's specific installation requirements. Physical dimensions refer to the retracted light; one length of the dual swing arm around the center mount in width and depth and the combined height of the lamp head and folded arms. Unit may also have a center mount detachable and sterilizable control handle. For use in minor procedure or examination room applications.	26 55 71
M7710	Electrocardiograph, 12 Lead, Portable	1	VV	Used to detect the electrical signals associated with cardiac activity, diagnose cardiac abnormalities, determine a patients response to drug therapy and reveal trends or changes in heart function. Capable of recording two or more leads simultaneously, recording an entire 12 lead ECG in about 10 seconds. Includes of a 3.5 inch, high density, floppy disk drive for test storage. Portable.	N/A
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.	N/A
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.	N/A

**9. Toilet, General Procedure Room Patient (TLTB1)**

A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	10 28 00
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
F2010	Basket, Wastepaper, Step-on	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A

P3005	Lavatory, Vitreous China, Bariatric	1	CC	A floor mounted bariatric lavatory with a capability to withstand a static downward pressure of 1,000 lbs. at the front of the sink. Lavatory will have a gooseneck faucet with wrist blade handles. Lavatory will be ADA compliant.	10 28 00
P9056	Toilet, Floor Mounted, Bariatric	1	CC	A floor mounted, flush valve toilet with an elongated front and a load capacity of 1,000 pounds. The toilet will be vitreous china with a 1.28 or 1.6 Gpf low water consumption rate with a rear outlet. See manufacturer's literature for recommended flush valves and toilet seats.	10 28 00

**10. Tele-Health Room (WRTM2)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00

E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3025	Board, Bulletin, Wood Framed	1	CC	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.	N/A

### 11. Tele-Retinal Room (WRTM3)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A

F3025	Board, Bulletin, Wood Framed	1	CC	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M6050	Retinal Imaging System, Fluorescein/Indocyanine	1	VV	Digital camera system for conducting fluorescing and indocyanine green studies of the choroid of the retina. The infrared sensitive camera has interchangeable barrier and exciter filters for the different dyes. The camera transmits images to a high resolution computer system and monitors for viewing, analysis, enhancement, manipulation, recording and color printing. Database reflects pricing and physical characteristics for the entire system with its required computer.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armband. Unit is designed for general use in examination/treatment rooms.	N/A

## 12. Shared Medical Appointment Room (CLSC4)

E0945	Cart, Computer, Mobile	2	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A
F0295	Chair, Stacking	16	VV	Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending upon the model selected. These chairs are intended primarily as overflow capacity for conference rooms.	N/A
F0435	Cabinet, Storage, Multi Media	1	VV	Multi media storage cabinet, approximately 60" high X 36" wide X 14" deep. For the storage of various types of audio or video cassettes, DVDs, CDs, and other media material.	N/A
F0860	Table, Mobile	4	VV	Mobile table. The unit provides mobile or isolated freestanding work surface. Characteristics and components include 3-1/2 inch casters and attached drawer bearers. Unit is used for general work applications, primarily in dry areas.	N/A
F2010	Basket, Wastepaper, Step-on	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F2250	Camcorder, Hand Held, HD, Zoom, w/Microphone	1	VV	Hand held camcorder with full HD recording, LCD display and microphone. Camcorder will also have capability for still picture capture. Audio and video output will be fully transferable to a computer.	N/A
F3060	Whiteboard, Projection Screen Combination	1	CC	Whiteboard and projection screen combination approximately 48" H x 72" W. Magnetic surface with matte finish for projection. Hard board stabilizer with aluminum foil back. For use with water color pens.	N/A
M0506	Television, Flat Screen	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

**13. Storage, Shared Medical Appointments (SRE01)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

**14. Alcove, Medication (RCA06)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
M3150	Distribution System, Medication, Automatic	1	VV	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.	N/A

**15. Alcove, Resuscitation Cart (RCA01)**

E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.	N/A
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.	N/A
M1110	Resuscitator, Bag-Mask, Hand Op, Infant	1	VV	Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations.	N/A
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.	N/A
M8770	Aspirator/Pressure Unit, General Purpose	1	VV	General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes.	N/A

**16. Team Work Area (WRTM1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
E0042	Workcenter, Computer, Free Standing, 48" W	2	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	10 28 00
F0275	Chair, Swivel, High Back	6	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F0750	Table, Office, (size as required)	1	VV	Office table, sized as required. May be used as either a four (4) to six (6) person conference table or as an extra work surface area.	N/A
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A



F3050	Whiteboard, Dry Erase	1	CC	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.	N/A
M0512	Television, HDTV, Large Screen, 60"	1	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

**17. Workstation, Extended Team (OFA03)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	N/A
E0075	Workstation, L-Shaped, Freestanding, 72x48	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-To-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 2 Tackboards 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Hanging Pedestal, Box/File 1 Pencil Drawer 2 Support Panels	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A

M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
-------	---	---	----	---	-----

**18. Workroom, Patient Aligned Care Team (PACT) (WKT3)**

A1010	Telecommunication Outlet	4	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
F0220	Chair, Conference	4	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F0750	Table, Office, (size as required)	1	VV	Office table, sized as required. May be used as either a four (4) to six (6) person conference table or as an extra work surface area.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3050	Whiteboard, Dry Erase	1	CC	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	4	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

**19. Classroom (WKT1)**

A1010	Telecommunication Outlet	4	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A
F0130	Bookstack, Single	2	CC	Freestanding closed base single open faced book stack, approximately 84" H X 36" W X 13" D with six (6) or seven (7) adjustable shelves and one base shelf. Single-faced units should be transverse-brace secured, or wall, or floor anchored for stability.	N/A

F0220	Chair, Conference	4	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F0750	Table, Office, (size as required)	1	VV	Office table, sized as required. May be used as either a four (4) to six (6) person conference table or as an extra work surface area.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3050	Whiteboard, Dry Erase	1	CC	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.	10 11 23
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A

**20. Workstation, Administrative (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**21. Conference Room (CRA01)**

A1010	Telecommunication Outlet	3	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.	N/A
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
F0220	Chair, Conference	8	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.	N/A

F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.	N/A
F0755	Table, Conference, Wood	1	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI ( American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.	N/A
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.	N/A
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.	N/A
M0512	Television, HDTV, Large Screen, 60"	1	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.	N/A
M1801	Computer, Microprocessing, w/Flat panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

**22. Utility Room, Clean (UCCL1)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
E0903	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an E0921 to transport the locker from place to place.	N/A
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	10 28 00

E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
P8710	Utility Center, Plumbing Connection	1	CC	Plumbing connection utility center, sometimes referred to as a 'GUY GRAY BOX'. This recessed utility center provides for hot and cold water connections and a drain connection at sink and other equipment locations. The utility center includes cutoff valves for the water connections, a plug seal for the drain and an outside cover to provide an aesthetic appearance when connections are no longer required. This center may be installed in locations where no plumbing fixtures are included in a design as a future flexibility device, saving many dollars for later facility modifications to incorporate sinks as functions change.	N/A

**23. Storage, Medical Equipment (SRE01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

**24. Lounge, Staff (SL001)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.	05 50 00
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00

C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.	12 32 00
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	12 32 00
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.	N/A
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.	N/A
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.	N/A
F3065	Whiteboard/Bulletin Board, Combination	1	CC	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.	N/A
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.	N/A

M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.	N/A
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.	N/A

**25. Locker, Staff Personal Property (LR004)**

A1040	Locker, 2 Person, Side by Side, 72x15x18	15	VV	Two person side by side locker. Steel unit. It consists of side by side compartments for hanging clothes and over/under compartments for hats, etc. Used for personal belongings storage.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A

**26. Toilet, Staff (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**C. FA3: Patient Aligned Care Team (PACT) Clinic 2****1. Alcove, Height / Weight Station (PEHW1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 1. Alcove, Height / Weight Station (PEHW1)

**2. Alcove, Height / Weight Accessible Station (PEHW2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 2. Alcove, Height / Weight Accessible Station (PEHW2)

**3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

**4. Exam Room, Patient Aligned Care Team (PACT) (EXPA1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 4. Exam Room, Patient Aligned Care Team (PACT) (EXPA1)

**5. Toilet, PACT Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**6. Exam Room, Women's Health (EXW01)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 6. Exam Room, Women's Health (EXW01)

**7. Toilet, Women's Health Exam Room Patient (TLTF1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 7. Toilet, Women's Health Exam Room Patient (TLTF1)

**8. Procedure Room, General (TRPR1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 8. Procedure Room, General (TRPR1)

**9. Toilet, General Procedure Room Patient (TLTB1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 9. Toilet, General Procedure Room Patient (TLTB1)

**10. Tele-Health Room (WRTM2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 10. Tele-Health Room (WRTM2)

**11. Tele-Retinal Room (WRTM3)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 11. Tele-Retinal Room (WRTM3)

**12. Shared Medical Appointment Room (CLSC4)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 12. Shared Medical Appointment Room (CLSC4)

**13. Storage, Shared Medical Appointments (SRE01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

**14. Alcove, Medication (RCA06)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 14. Alcove, Medication (RCA06)

**15. Alcove, Resuscitation Cart (RCA01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 15. Alcove, Resuscitation Cart (RCA01)

**16. Team Work Area (WRTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

**17. Workstation, Extended Team (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**18. Workroom, Patient Aligned Care Team (PACT) (WKTM3)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 18. Workroom, Patient Aligned Care Team (PACT) (WKTM3)

**19. Classroom (WKTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 19. Classroom (WKTM1)

**20. Workstation, Administrative (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**21. Conference Room (CRA01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 21. Conference Room (CRA01)

**22. Utility Room, Clean (UCCL1)**



See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 22. Utility Room, Clean (UCCL1)

### **23. Storage, Medical Equipment (SRE01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

### **24. Lounge, Staff (SL001)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 24. Lounge, Staff (SL001)

### **25. Locker, Staff Personal Property (LR004)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 25. Locker, Staff Personal Property (LR004)

### **26. Toilet, Staff (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

## **E. FA4: Patient Aligned Care Team (PACT) Clinic 3**

### **1. Alcove, Height / Weight Station (PEHW1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 1. Alcove, Height / Weight Station (PEHW1)

### **2. Alcove, Height / Weight Accessible Station (PEHW2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 2. Alcove, Height / Weight Accessible Station (PEHW2)

### **3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

### **4. Exam Room, Patient Aligned Care Team (PACT) (EXPA1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 4. Exam Room, Patient Aligned Care Team (PACT) (EXPA1)

### **5. Toilet, PACT Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

### **6. Exam Room, Women's Health (EXW01)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 6. Exam Room, Women's Health (EXW01)

### **7. Toilet, Women's Health Exam Room Patient (TLTF1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 7. Toilet, Women's Health Exam Room Patient (TLTF1)

### **8. Procedure Room, General (TRPR1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 8. Procedure Room, General (TRPR1)

**9. Toilet, General Procedure Room Patient (TLTB1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 9. Toilet, General Procedure Room Patient (TLTB1)

**10. Tele-Health Room (WRTM2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 10. Tele-Health Room (WRTM2)

**11. Tele-Retinal Room (WRTM3)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 11. Tele-Retinal Room (WRTM3)

**12. Shared Medical Appointment Room (CLSC4)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 12. Shared Medical Appointment Room (CLSC4)

**13. Storage, Shared Medical Appointments (SRE01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

**14. Alcove, Medication (RCA06)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 14. Alcove, Medication (RCA06)

**15. Alcove, Resuscitation Cart (RCA01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 15. Alcove, Resuscitation Cart (RCA01)

**16. Team Work Area (WRTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

**17. Workstation, Extended Team (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**18. Workroom, Patient Aligned Care Team (PACT) (WKTM3)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 18. Workroom, Patient Aligned Care Team (PACT) (WKTM3)

**19. Classroom (WKTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 19. Classroom (WKTM1)

**20. Workstation, Administrative (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**21. Conference Room (CRA01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 21. Conference Room (CRA01)

**22. Utility Room, Clean (UCCL1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 22. Utility Room, Clean (UCCL1)

### 23. Storage, Medical Equipment (SRE01)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

### 24. Lounge, Staff (SL001)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 24. Lounge, Staff (SL001)

### 25. Locker, Staff Personal Property (LR004)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 25. Locker, Staff Personal Property (LR004)

### 26. Toilet, Staff (TLTU1)

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

## E. FA5: Audiology and Speech Pathology Clinic

### 1. Hearing Aid Fitting Room (HAFR1)

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	10 28 00
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00

E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.	N/A
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-on	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0020	Hearing Aid Analyzer	1	VV	Hearing aid analyzer. It includes a complete acoustic test system, comprised of a control unit, color monitor, and hearing aid test box. For use in automatically testing, calculating and printing all electrical and acoustical performance data of any hearing aid in accordance with ANSI S3.22.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A

M4915	Chair, Exam/Treatment, ENT, w/Adjustable Light	1	VV	ENT exam/treatment chair with adjustable light. Chair can be rotated 330 degrees locking at desired position. Unit is electrically powered for precise positioning and has an adjustable headrest and armrest. It may include an adjustable gooseneck light. Unit is designed for use during examinations, treatments, and minor procedures.	N/A
-------	--	---	----	--	-----

## 2. Exam / Consult, Audiology (EXAU1)

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A1132	Rail, Accessory Mounting, Length As Req	1	VV	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismantling of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismantling equipment without leaving or creating new holes in the finished surface of the wall.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	8	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0035	Analyzer, Auditory, Evoked Potential	1	VV	Evoked potential auditory analyzer. The unit features a large color monitor, a minimum of 4 channel analysis, a computer, built-in electrode impedance testing, a physiological signal amplifier, a digital auditory stimulator and a register recorder. The analyzer is used for analyzing the response of the central nervous system to a variety of external stimuli.	N/A

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M4915	Chair, Exam/Treatment, ENT, w/Adjustable Light	1	VV	ENT exam/treatment chair with adjustable light. Chair can be rotated 330 degrees locking at desired position. Unit is electrically powered for precise positioning and has an adjustable headrest and armrest. It may include an adjustable gooseneck light. Unit is designed for use during examinations, treatments, and minor procedures.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement	N/A
M8540	Microscope, Operating, Wall Mounted	1	VV	Wall mounted operating microscope. Unit consists of a binocular microscope body mounted to a wall support. A magnification changer to determine the magnification ratio is enclosed in the body tube of the microscope. The lens system consists of a range of objectives from 3 to 15 in 5 steps. Includes a fiberoptic halogen light source with beam-splitter, manual or pedal focusing controls and zoom capabilities. Used in clinics, hospitals and doctor's offices during surgery to clarify the surgeon's view of microscopic structures.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

### 3. Exam / Consult, Speech Pathology (EXOS1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1016	Telephone, Desk, With Speaker	1	CC	Telephone, desk, with speaker.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00

A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A
F0205	Chair, Side With Arms	2	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0020	Hearing Aid Analyzer	1	VV	Hearing aid analyzer. It includes a complete acoustic test system, comprised of a control unit, color monitor, and hearing aid test box. For use in automatically testing, calculating and printing all electrical and acoustical performance data of any hearing aid in accordance with ANSI S3.22.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

#### 4. Exam, Audiometric Booth (PEHS4)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	2	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	N/A
F0280	Chair, Swivel, Low Back	2	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0860	Table, Mobile	1	VV	Mobile table. The unit provides mobile or isolated freestanding work surface. Characteristics and components include 3-1/2 inch casters and attached drawer bearers. Unit is used for general work applications, primarily in dry areas.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0025	Audiometer, Diagnostic, Middle Ear, Impedance	1	VV	Diagnostic impedance audiometer. Unit includes a clinical ear analyzer and can link to a complete data base computer system that stores patient results. Used for diagnostic audiological testing for middle ear impedance / compliance.	N/A
M0041	Booth, Audio, Double Wall, Suite	1	CC	Double wall audiometric testing suite with double walled examination and control rooms. Unit includes recessed incandescent lights, carpet, keyed locks on both outer doors, a twelve outlet surface mounted plug mold strip in both rooms. A 24"x30" viewing window and self contained ventilation system permit extended examinations. Unit also includes jack panel between the exam and control rooms. Height may require raising room ceiling.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A



5. Electrophysiology Room (OPAE2)					
A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	8	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0025	Audiometer, Diagnostic, Middle Ear, Impedance	1	VV	Diagnostic impedance audiometer. Unit includes a clinical ear analyzer and can link to a complete data base computer system that stores patient results. Used for diagnostic audiological testing for middle ear impedance / compliance.	N/A

M0035	Analyzer, Auditory, Evoked Potential	1	VV	Evoked potential auditory analyzer. The unit features a large color monitor, a minimum of 4 channel analysis, a computer, built-in electrode impedance testing, a physiological signal amplifier, a digital auditory stimulator and a register recorder. The analyzer is used for analyzing the response of the central nervous system to a variety of external stimuli.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement	N/A
M8830	Table, Instrument/Dressing, Mobile	1	VV	Mobile instrument/dressing table, approximately 34" H x 20" W x 16" D Corrosion resistant stainless steel mobile table with sound-deadening shelf and drawer. Unit is mounted on 2" casters. Designed for all purpose use in the hospital or clinic.	N/A
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

### 6. Vestibulography Room (EXVE1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A1132	Rail, Accessory Mounting, Length As Required	1	VV	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismantling of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismantling equipment without leaving or creating new holes in the finished surface of the wall.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M3073	Container, Biohazard Waste, Step-on, Fire Safe	1		A biohazard waste container with a step-on lid. The container will have a capacity of approximately 12 gallons and be made of a fire safe material.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A

M4840	ENT Unit, w/Air, Electric Power, Suction, Pressure	1	VV	A biohazard waste container with a step-on lid. The container will have a capacity of approximately 12 gallons and be made of a fire safe material.	N/A
M4910	Chair, Exam, Vestibular	1	VV	Vestibular examination chair. Base provides adjustable seat heights. Unit features a fully adjustable headrest with armrests and can be adjusted to the horizontal position. Unit has removable upholstery sections.	N/A
M4915	Chair, Exam/Treatment, ENT, w/Adjustable Light	1	VV	ENT exam/treatment chair with adjustable light. Chair can be rotated 330 degrees locking at desired position. Unit is electrically powered for precise positioning and has an adjustable headrest and armrest. It may include an adjustable gooseneck light. Unit is designed for use during examinations, treatments, and minor procedures.	N/A
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A
M7730	Electronystagmograph w/Accessories	1	VV	Unit detects the electrical currents from muscular contractions which cause eye movement. For the analysis of eye motion as an indicator of brain stem dysfunction, multiple sclerosis, adverse drug reaction or other disorders causing irregular eye movements. The system consists of a electrical leads, large color display, recorder, 2 direct channels, auxiliary channel outputs and an electrode terminal box. The system requires one or more stimulation apparatuses such as an ear irrigator (which generates the plumbing requirements), light bar or rotating drum. System options include several microprocessor and printer configurations. Electrical requirements and weight are for the complete system. Height, width and depth are for the controlling microcomputer only.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

### 7. Group Therapy Room, Audiology (OPMH1)

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
F0220	Chair, Conference	8	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.	N/A
F0755	Table, Conference, Wood	1	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.	N/A
F2250	Camcorder, Hand Held, HD, Zoom, w/Microphone	1	VV	Hand held camcorder with full HD recording, LCD display and microphone. Camcorder will also have capability for still picture capture. Audio and video output will be fully transferable to a computer.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A

### 8. Group Therapy Room, Speech Pathology (OPMH1)

See Above: E. AUDIOLOGY AND SPEECH PATHOLOGY CLINIC, 7. Group Therapy Room, Audiology (OPMH1)

**9. Toilet, Audiology Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**10. Storage, Equipment (SRSE1)**

See Above: G. STAFF AND ADMINISTRATIVE AREA, 2. Office, Dentist Director (OFA01/OFA02)

**H. FA6: Dental Clinic****1. Consult Room, Dental (OFDC2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

**2. X-Ray Room, Panoramic / Cephalometric (DNXS1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
C0041	Rail, Apron, 4x60x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.	N/A
C0047	Frame, Apron, 3 Drawer, 4x60x22	1	CC	Apron frame with three standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.	N/A
CT020	Countertop, Solid Surface	6	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00

D9280	Legs, Rail, Apron	4	CC	Apron rail legs. Used to support countertops when there is no base cabinet to support D9940, height as required. Used in dental operations. Database pricing and dimensional information assumes a 24" deep counter, 36" above the floor.	12 32 00
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on" wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
X3150	Rack, Apron/Gloves, Wall Mounted	1	CC	Apron and gloves rack. This is a wall unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum. The unit's convenient on wall storage will prolong the useful life of your protection aprons by helping prevent damage to internal components.	N/A
X6505	Radiographic Unit, Dental, Panographic & Cephalo	1	VV	Dental panographic and Cephalometric radiographic unit. This is a radiographic system for routine intra-oral examination. This unit shall provide radiographs of the maxillary sinus and the entire jawbone including temporomandibular joints. The unit shall be complete with control panel and mounting hardware.	13 49 00
X6605	Imager, Dental, Digital Image	1	VV	Dental imaging system. Used in intra oral x-ray imaging. Computer-aided to enhance image. Storage and printing capabilities for the image. System includes, CPU, CRT, active surface sensor, 120MB HD storage, thermal printer, mobile workstation, and is compatible with any intra oral x-ray system.	N/A

### 3. Dental Treatment Room (DTR), Multi-Functional (DNTG1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A

A5077	Dispenser, Hand Sanitizer, Hands-Free	2	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
D0670	Console, Treatment Unit, Dental Operatory	1	CC	A dental treatment console or work station (also called a "12 o'clock unit) approximately 45" W x 72" H x 30" D. Consists of a base unit with storage and equipment drawers, a bifold door cabinet with slide out shelves and CPU storage. A midsection with chase and power bar for ancillary equipment and shelf for a monitor and keyboard. Upper storage unit may be pass-through or non-pass-through with glass shelves and see-through cabinet doors. Unit may also be configured with a pivoting work surface to hold all doctor and assistant instrumentation or with a wash station w/SS sink and knee or foot activated faucet and solid surface or laminate countertop. Unit is also available in other widths and heights. Final makeup of this unit is dependant on individual facility requirements determined at time of purchase.	N/A
D0680	Console, Accessory/Side, Dental Operatory	2	CC	An accessory or side console/cabinet approximately 60" W x24"D x 32"H for use in a single chair dental operatory. The console may be a left or a right unit used for the dentist or the assistant depending configuration of the operatory. The unit may contain a sink component with waste drop, a round SS sink with faucet and soap dispenser, a solid surface counter top, a drawer storage module with writing surface and equipment drawers, a double door component with swing out shelves and a glove dispenser. Various combinations are available as well as different widths. Configuration of the unit, including whether the unit is right or left, to be determined at time of purchase.	N/A
D0685	Cabinet, Storage, Dental Operatory, Wall MNTD	2	CC	An upper wall mounted storage cabinet with two adjustable shelves providing additional space for dental supplies and equipment in a dental operative. Cabinet is approximately 34"W x 12"D x 24"H with other widths available. Cabinet is frequently mounted above JSN D0680, Console, Accessory/Side, Dental Operatory.	N/A
D3320	Chair, Operating, Dental	1	VV	Dental operating chair designed for the treatment and comfort of dental patients. The chair shall be capable of multiple positions, shall swivel, contain an adjustable headrest and arm rests that pivot up and down. The chair shall operate by means of electrohydraulics. The upholstery shall be seamless with no crevices to catch debris and be easy to clean.	N/A
D3380	Stool, Operating, Dental, Doctor	1	VV	Dental operating stool. Used by the dentist in the care and treatment of patients. This chair has a gas cylinder to adjust the height of the chair. It also has backrest as an integral part of the unit. The unit is to be equipped with casters. Various color combinations of vinyl or fabric are available.	N/A
D3390	Stool, Operating, Dental, Assistant	1	VV	Dental assistant's operating stool used in dental operatories during procedures. This chair has a body support arm or abdominal support that can be left or right hand adaptable. It is also gas cylinder operated for height adjustments. The chair is available in multiple vinyl or fabric color combinations.	N/A
D3565	Resin Curing Unit, Visible Light	1	VV	Visible light resin curing unit which provides a high intensity, cold light source of visible blue light for the polymerization of all visible light cured materials. The unit provides for time selections between 10 and 60 seconds or continuous operation and beeps at ten or twenty second intervals during use.	N/A

D6050	Light, Dental, Operating, Ceiling, Track	2	CC	Dental operating light used to illuminate the field of work. This is a single light unit on a cantilever arm mounted from a column which is suspended from a moving trolley in a ceiling track. The light can be used in installations where the ceiling height is between 8 and 10.5 feet; some units can mount to ceilings as high as 13 feet. Database physical dimensions refer to the light's maximum travel dimensions centered on the ceiling mounting track. The database weight includes the light, arm and trolley. Mounting this light may require reinforcing the ceiling or hanging the mount from the underside of the slab above a suspended ceiling.	26 55 71
D7090	Utility Center, Dental, Wall or Floor Mounted	1	CC	Utility center. The unit contains electrical and quick connect air, waste and water utility connections. The center accommodates one umbilical and includes shut-off valves and regulators for both the air and water supplies.	N/A
D8250	Delivery System, Dental Operating	1	VV	Dental operating unit. The dentist and/or dental hygienist uses the unit for treatment of dental patients. The unit contains the operating connections for handpieces, the water spray and the vacuum system. The unit can be wall, chair or cart mounted.	N/A
D8850	Amalgamator, Dental	1	VV	Dental amalgamator. The amalgamator is used in dental operatories to triturate alloys for restoration of teeth after removal of caries.	N/A
D9060	Prophylaxis Unit, Ultrasonic	1	VV	Dental ultrasonic prophylaxis unit. Used in dental clinics for the removal of calculus. Unit requires water and air supplies.	N/A
F2010	Basket, Wastepaper, Step-On	2	VV	Step-on" wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	VV	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.	N/A
X6600	Radiographic Unit, Dental, Wall Mounted, 7 mA	1	VV	Dental radiographic unit. Wall mounted, 7 mA, 70 kVp, 120 VAC, electronic remote exposure control unit. The unit shall have electronic timing with automatic reset timing capability and main power correction unit to adjust for line voltage fluctuations. Tube head shall be of the oil immersed, shield type with total inherent filtration of 1.5 mm AL, with a focal spot of 0.6.	13 49 00
X6610	Sensor, Dental Imaging System	1	VV	A filmless digital imaging system using a sensor to acquire and digitize dental x-ray images for viewing, storing or printing. The sensor is used in conjunction with a film based x-ray system. Images are digitized and transmitted to a computer via a standard USB port and is compatible with laptop or desktop systems.	N/A
_0022	Mount, Monitor Track	1	CC	Mount for track mounted monitor used in dental treatment rooms. Mounts have the option of wall mounted, console mounted and chair mounted.	N/A

**4. Toilet, Dental Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**5. Team Work Area, Dental Clinic (WRTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

**6. Laboratory, Dental Prosthetics (DNPL1)**



*_0025	Mixing Valve, Emergency Fixture	1	CC	Thermostatic mixing valve is used to maintain a tempered water supply at the minimum pressure required by ANSI. Used to supply water to eye or face wash and combination units. Flow capacity is at least 8 GPM at 30 psi.	22 40 00
*_0026	Transport Cart, Laboratory	1	VV	Small cart made of polished steel and vinyl matting. 5" swivel caster wheels, with fold down push bar. Cart has a rubber bumper to prevent damage to walls. Weight capacity is approx. 600 lbs. Cart platform measures 23x35.	N/A
*_0027	Oven, Sintering	1	VV	Fully programmable sintering oven with adjustable temperature capable of creating custom cycles.	N/A
A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
C03P0	Cabinet, Sink, U/C/B, 2 Door, 30" W	2	CC	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	12 32 00
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x	5	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
CS200	Sink, SS, Single Compartment, 12x28x16 ID	2	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	12 32 00
CT020	Countertop, Solid Surface	1	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00
D0755	Tank Assembly, Boilout/Curing, Double	1	CC	Two basin washout and boil-out tank assembly with stainless steel tanks and gas heating elements. The unit includes a recirculating pump, wax trap and drain valve. The assembly requires an appropriate cabinet for support.	N/A

D0904	Workstation, Dental Lab, Tech, Single Station	4	CC	Modular technician's workstation for the dental laboratory. The workstation features integrated gas, air, and electrical lines which all connect to building supplies from a single utility panel. The unit contains an overhead task lighting ( approx. 3000 Lux) array. The workstation also includes a dust extraction system with filtration, a minimum of 4 drawers for storage, an air gun, a gas valve for a Bunsen burner and electrical outlets for accessory equipment. The desktop is made from a fiber/cement mixture or similar material to resist heat, abrasion, and chemical attack. This unit has a standard length work surface that varies among manufacturers but is nominally 43". Depending on the manufacturer, workstation package configurations may include seating and other minor accessories. The workstation may require more than one electrical connection to the facility power grid to run the equipment used on the bench.	N/A
D0942	Workstation, Dental Lab, Microblasting	1	CC	Complete micro-blaster and dust extraction device integrated into a 34" high x 24" wide x 24" deep (nominal) cabinet. The micro-blaster can use 25 to 250 micron aluminum oxide, sand, glass bead or walnut shell abrasives. The unit includes micro-blasting pencils, canisters for clean blasting, one recirculating nozzle for gross blasting, an air chisel, an air nozzle and a protective safety shield. The micro-blaster connects to a dust extraction system suitably sized for the micro-blaster.	N/A
D2580	Casting Machine, Induction, Bench Mounted	1	VV	Bench mounted, microprocessor controlled induction casting machine. The unit is designed for safe clean casting of precious and non-precious dental alloys. The machine features automatic temperature control through a range of 900 to 1800 degrees C (1652 to 3272 degrees F), built-in optical pyrometer, a self-contained water cooling system and variable casting arm acceleration rate. The unit is designed for mounting on a low bench to bring it up to counter height for easy use.	N/A
D3295	Chair, Rotary, Laboratory, Dental	4	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.	N/A
D4100	Cleaner, Steam, Dental	1	VV	Dental steam cleaner. The cleaner has a variable temperature control and is capable of generating up to 80 PSI of pressure. The unit is used for flushing out dirt, debris, wax and polishing compounds from models, dentures, impression trays and instruments.	11 17 01
D4260	Handpiece, Laboratory, Dental, Electric	4	VV	Portable dental laboratory handpiece. The unit has a straight handle and is electrically powered. The handpiece includes a controller and power cables. Unit is used to grind, polish or finish precious and non-precious metal alloys.	N/A
D4360	Pump, Vacuum, Dental Oven	1	VV	Vacuum pump. The pump is used in dental laboratories to provide a vacuum source for the vacuum oven listed at JSN D4350.	N/A
D4500	Furnace, Laboratory, Dental, Burnout	1	VV	Dental burnout furnace. The unit is used in dental laboratories for burnout of dental alloy rings and flasks. The furnace is capable of automatic or manual operation and has a automatic self-calibration system as well as a digital readout. The unit can hold a minimum of fifteen 1-3/4" inlay rings. Some model lines are available with several sizes of heating elements and/or for other power configurations.	N/A
D6250	Lathe, Dental, Bench Mounted	4	VV	Dental lathe which can perform grinding or polishing work depending on the attachments to the spindles. The unit is bench mounted and has two speeds, generally 1725 and 3450 rpm, or is variable across its entire operating range up to 3600 rpm.	11 05 12
D6600	Mixer / Investor, With Vacuum	1	VV	Dental vacuum mixer-investor. Unit is used in dental laboratories to mix alginates and other materials as well as investing materials for inlays and crowns. Some units are equipped with a vibrating arm to assist in moving investments from the mixing chamber into the casting rings. Some models are microprocessor controlled. Units are mounted to a wall or bench for stability. Specify mounting when ordering.	N/A
D6650	Former, Vacuum, With Motor, Vacuum Pump, Heater	1	VV	Vacuum former. Used in dental laboratories for adaptation of thermoplastic resins. Unit has a self contained motor, vacuum pump and heater.	N/A
D8510	Oven, Drying, Dental	1	VV	Dental model drying oven. The oven is used to dehydrate refractory models prior to bee's wax dipping. The unit provides efficient circulation of air to eliminate moisture as it evaporates. The unit has an adjustable damper, two shelves, a built-in thermostat, a secondary temperature controller and a glass thermometer.	N/A

D9035	Driver, Model Indexing Pins	1	VV	Model indexing pin driver used to accurately place indexing pins in multiple piece dental models and multiple piece die sets. The bench top instrument provides a means to accurately align, drill and insert indexing pins.	N/A
D9050	Trimmer, Model, Dental, 1/4 HP	1	CC	Dental model trimmer with a 1/4 or 1/3 HP motor and a 10" abrasive wheel. The trimmer is used in dental laboratories for trimming plaster and stone dental impression models. This is a light duty unit and its commonly used accessories include floor switches, water valves, water spray heads and splash shields. The database pricing is for the basic unit only.	11 05 12
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
L2337	Canopy, Hood, Fume, 6 foot	1	CC	Canopy fumehood. The unit includes a switched fan unit with pilot light; corrosion resistant steel, aluminum, or chemical resistant and fire retardant seamless fiberglass construction; dimensions as indicated on design drawings; fire suppression systems and any other special requirements to be defined during the facility design. It also includes a 3/4 horsepower motor blower. The static pressure loss shall not exceed 0.91 at 1290 cfm and 1.65 at 1935 cfm. It is equipped with baffles to maximize slot velocities and control fumes. Used in laboratories for low to moderate risk biological agents. Other sizes may be available. Blower motor mounted separate from the canopy and may not be included in the size specification.	11 71 02
M2015	Cabinet, Storage, Flammable, Freestanding	1	VV	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.	N/A
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.	22 40 00
P7650	Trap, Plaster, Small	1	CC	Plastic or metal bodied plaster trap. The unit has a one piece body which is approximately 12 inches deep. The top has 1.5 inch inlet and drain connections. The trap is used in laboratories to capture solids and preclude the clogging of drain lines. The installation must allow sufficient clearance above or below the unit (depending on the manufacturer) to remove the basket for cleaning.	N/A

**7. Linen Room, Clean (LCCL1)**

F0515	Cart, Supply, Linen	1	VV	Closed linen supply cart. Equipped with four (4) non-marking rubber tire roller bearing casters and heavy duty cover. May be used for the delivery and user storage of clean linen as well as the return of soiled linen.	N/A
M7300	Dispenser, Garment, Scrubs	1	VV	A garment dispenser and receiver cabinet for dispensing scrub sets to customers. Dispenser holds approximately 64 sets of scrubs and accommodates 85 users per day with 2 refills per day. Garments are dispensed in sets by size to authorized personnel by use of hospital ID, bar code, magnetic strip or with keypad backup. Maintains control of scrub sets through usage reports and digital recording of returns.	N/A

**8. Linen Room, Soiled (LCSL2)**

F0510	Cart, Linen, Soiled	2	VV	Soiled linen collection cart, approximately 70" H x 68" W x 28" D with four (4) casters. Used to transport clean or soiled laundry.	N/A
-------	---------------------	---	----	---	-----

F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A

**9. Storage, Equipment (SRE01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

**10. Dental Equipment Mechanical Room (MECH1)**

*_0032	Amalgam Separator	1	CC	The amalgam separator traps wastewater and separates metal particles and other solids from the water before being released into the sewer system.	N/A
*_0033	Pump, Dental Vacuum	2	CC	Dental vacuum pump system is a dry system with the ability to eliminate water and configure with amalgam collector system. A single system will support 12-15 dental treatment rooms.	22 61 19
*_0034	Tank, Vacuum Separation	1	CC	Vacuum separation tank, with high-low liquid sensor and multiple set options. Separation tanks come in different sizes and configurations. Tank option should be coordinated with vacuum pump vendor.	22 61 19
A1000	Extinguisher, Fire	1	VV	10 pound dry chemical fire extinguisher with charging gauge. Other types and sizes are available.	N/A
D4001	Compressor, Dental Air, System	2	CC	Dental air compressor system. Two or more equally sized compressors, with provisions for automatic, alternating and simultaneous operation shall be provided for dental air (DA). Each compressor is to be sized to operate at 65% duty cycle for maintenance of standard demand. Dental compressed air (DCA), 90 PSIG, is used for utility control in dental units, power for lifts, locks, rotary and other pneumatic dental instruments and equipment. DCA shall be oil-free air with the following air standards as maximums: Water - dry to a pressure dew point of 33 degrees F at not less than 90 PSIG; Condensed hydrocarbons - 0.1ppm by weight or 0.1 mg/L; Permanent particulates - 1.0 ppm by weight or 1.0 mg/L. Dental lab air (DLA), 30 PSIG, which is normally used for laboratory restorative and fabrication techniques may be combined with DCA. The system consists of, but not limited to, the following: compressor intake filters, compressors, after-coolers (air cooled), air receiver, pre-filter, dryer (refrigerated), after-filter. Pricing, electrical data and dimensions based upon 16-17 DTRs, each pump sized at approximately 17.5 cfm @ 100 PSIG. Other sizes and configurations are available to meet specified demands.	22 61 19

**G. FA7: Eye Clinic****1. Sub-Waiting, Dilation Patient (WRC03)**

A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.	05 50 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0305	Chair, Waiting Room, Single	1	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.	N/A
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.	N/A

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	N/A

## 2. Fitting and Dispensing Room (EYFD1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A

E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A
E1500	Rail, MOD, W/MNTD, HX144XD	2	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M5520	Lensometer	1	VV	Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.	N/A
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.	N/A
M5735	Warmer, Spectacle, Plastic	1	VV	Plastic spectacle warmer. Bath type. Thermostatically controlled. For use with glass beads or salt.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

3. Exam / Treatment Room (EYOT2)					
A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

M5016	Desk, Refraction w/console, w/o Sink	1	CC	The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.	N/A
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.	N/A
M5530	Lamp, Slit, w/Applanation Tonometer	1	VV	Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.	N/A
M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.	N/A
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.	N/A
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.	N/A
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.	N/A
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.	N/A
M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.	N/A
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.	N/A
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

**4. Exam / Training Room, Low Vision (EYOT4)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
-------	--------------------------	---	----	------------------------------------	----------



A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0903	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an E0921 to transport the locker from place to place.	N/A
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0210	Chair, Side, Without Arms	4	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F0820	Table, Office, Round	1	VV	Round office table, approximately 29" high X 42" diameter.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2435	Lamp, Desk, Fluorescent	1	VV	Fluorescent desk lamp, approximately 13"H X 9"W X 6" D with a 14" wide X 2" deep shade and two (2) 15 Watt fluorescent tubes. Size and lamp shape may vary. Used for general reading luminosity. Convenience outlet required at point of use.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0435	Monitor, CCTV, Small, 9" (Color)	1	VV	Nine (9) inch color CCTV monitor, 9" high X 9" wide X 14" deep with a 9" diagonal picture tube. Convenience outlet required at point of use.	N/A

M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M5016	Desk, Refraction w/console, w/o Sink	1	CC	The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.	N/A
M5520	Lensometer	1	VV	Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.	N/A
M5530	Lamp, Slit, w/Applanation Tonometer	1	VV	Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.	N/A
M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.	N/A
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.	N/A
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.	N/A
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.	N/A
M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.	N/A
M5700	Frame Set, Lens, Trial	1	VV	Trial lens frame set. Set consists of light weight and color-coded marked lenses, holding tray, and a complete assortment of other accessories. It is used to determine visual acuity. Set features horizontal and vertical bridge adjustments with individual adjustments for temple length and angle.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

5. Pre-Testing Room (EYVS1)					
A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 13 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	2	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.	N/A

M5027	Table, Multiple Instrument, Ophthalmic	1	VV	A multiple instrument ophthalmic table. This table is designed to hold up to three ophthalmologic instruments allowing the patient to turn only slightly between them for testing. The table top is adjustable from approximately 26" to 38" and facilitates complete wheelchair accessibility to all instruments.	N/A
M5500	Autorefractor, Ophthalmic	1	VV	Ophthalmic autorefractor. Unit is a tabletop model consisting of a instant display TV monitor, forehead rest, measuring head, height adjustment ring, and joystick lever. It features an automatic fogging and a high speed printer. Designed for visual acuity screening.	N/A
M5570	Armed Forces Vision Tester	1	VV	Armed Forces Vision Tester. Unit is spring balanced for easy height adjustment and has a tension lock. It contains rotating drums for slide alignment and 5 point tests. It is designed to provide accurate vision screening for near point and far point vision. This unit is a special order item normally procured through DSCP. This item is designed for the government and is not available on the open market.	N/A
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.	N/A
M6045	Corneal Topography Unit	1	VV	Computerized corneal mapping system for pre- and post- surgical diagnosis of astigmatism, refractive error, irregularly shaped corneas and other eye conditions. The unit performs analysis of 5,000 - 6,000 different points on a ring pattern reflected from the patient's cornea to quantify the curvature and contours of the corneal surface.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

#### 6. Visual Fields Room (EYVF1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 13 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00

E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1620	Holder, Chart, Patient, Wall or Door Mounted	1	CC	Wall or door mounted patient chart holder. Constructed of durable plastic or metal. Used for holding patient records. Size as required.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.	N/A
M5030	Stool, Surgeon, Revolving	2	VV	Revolving stool. Consists of a padded upholstered seat with height adjustment. Unit rotates and is mounted on ball bearing swivel casters. Designed for use in examinations, treatment, and surgical procedures.	N/A
M5555	Perimeter, Automated	1	VV	Automated ophthalmic perimeter. Unit has on screen display for rapid and accurate alignment of patients automatic pupil size measurement, seven different fixation aids, ergonomic chin rest, several threshold strategies, and high target intensity.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

**7. Photography Room (EYVS1)**

See Above: G. EYE CLINIC, 5. Pre-Testing Room (EYVS1)

**8. Team Work Area, Eye Clinic (WRTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

<b>9. Office, Blind Rehabilitation (VIST) Counselor (OFA04)</b>					
A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A
F0110	Bookcase 3 Shelf	1	VV	Freestanding open metal shelf book case, approximately 60" high X 36" wide X 18" deep with three (3) adjustable shelves and four (4) non-marking floor glides	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

**10. Office, Supervisor (OFA04)**

See Above: G. EYE CLINIC, Office, Blind Rehabilitation (VIST) Counselor (OFA04)

**H. FA8: Mental Health Clinic****1. Biofeedback (OPMH3)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 13 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	1	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File	N/A
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	1	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A

E0912	Locker, Supply, Med Surg, Wall Mtd	1	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	N/A
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.	N/A
F0265	Chair, Recliner	1	VV	Reclining chair, 46" high X 33" wide X 40" deep with arms, straight leg base and floor glides or lockable two (2) inch casters. Seat, back and foot rest are foam padded and upholstered with woven textile fabric or vinyl.	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0340	Stool, Self Adjusting		VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1620	Holder, Chart, Patient, Wall or Door Mounted	1	CC	Wall or door mounted patient chart holder. Constructed of durable plastic or metal. Used for holding patient records. Size as required.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M7710	Electrocardiograph, 12 Lead, Portable	1	VV	Used to detect the electrical signals associated with cardiac activity, diagnose cardiac abnormalities, determine a patients response to drug therapy and reveal trends or changes in heart function. Capable of recording two or more leads simultaneously, recording an entire 12 lead ECG in about 10 seconds. Includes of a 3.5 inch, high density, floppy disk drive for test storage. Portable.	N/A
M8180	Biofeedback Analysis System	1	VV	Computer based biofeedback testing and analysis system. Unit accepts electroencephalograph (EEG), electromyograph (EMG), DC potential, goniometry, body temperature and other physiologic measurements for correlation and analysis. The system is primarily used in psychiatry and psychology clinics for rehabilitation treatments and pain management training.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

## 2. Group Therapy Room, Mental Health (OPMH1)



See Above: E. AUDIOLOGY AND SPEECH PATHOLOGY CLINIC, 7. Group Therapy Room, Audiology (OPMH1)

**3. Consult Room, Mental Health (OFDC1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
E0063	Workstation, L-Shaped w/Peninsula, Wall Mtd, 72x72	1	VV	THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Tackboard 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 1 Cantilevered Work Surface 1 Peninsula Work Surface 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 1 Cpu Holder	N/A
F0110	Bookcase 3 Shelf	1	VV	Freestanding open metal shelf book case, approximately 60" high X 36" wide X 18" deep with three (3) adjustable shelves and four (4) non-marking floor glides	N/A
F0255	Chair, Easy	2	VV	Easy chair approximately 35" high X 28" wide X 32" deep with arms and floor glides. Arms, back and seat are foam padded and upholstered in woven textile fabric or vinyl	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A

**4. Office, Supervisor (OFDC1)**

See Above: H. MENTAL HEALTH CLINIC, 3. Consult Room, Mental Health (OFDC1)

**5. Storage, General (SRS01)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

**6. Team Work Area, Mental Health (WRTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

**I. FA9: Multi-Specialty Clinic****1. Alcove, Height / Weight Station (PEHW1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 1. Alcove, Height / Weight Station (PEHW1)

**2. Alcove, Height / Weight Accessible Station (PEHW2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 2. Alcove, Height / Weight Accessible Station (PEHW2)

**3. Cast Room (OPCR1)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5150	Hook, Garment, Triple, Surface Mounted	1	CC	A surface mounted, anodized aluminum or chrome bar or woodgrain finished panel with triple garment hooks. For general purpose use throughout the facility to hang various items of apparel.	N/A

A5180	Track, Cubicle, Surface Mounted, With Curtain	12	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	12 32 00
CE090	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x36x16	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.	12 32 00
CS180	Sink, SS, Single Compartment, 12x22x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	N/A
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00
E0942	Cart, Cast, Mobile, 36"H x 46"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Accessory Rail, Side 1 Wastebasket 1 Flip-up Shelf 2 Drawers, 3"H 1 Drawer, 6"H Drawer Organizer Bins	N/A
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A

E0963	Cart, General Storage, Mobile	1	VV	Mobile General Storage Cart, approximately 72"H x 23"W x 22"D. THIS TYPICAL INCLUDES: 1 Locker Storage Container on Wheels, w/Solid Door 3 Tray/Shelves 2 Drawers, 3"H 4 Drawers, 6"H 1 Tray/Shelf Divider Drawer Organizer Bins	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.	22 63 00
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.	22 63 00
M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.	22 63 00
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	VV	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.	N/A
M4835	Cutter, Cast, w/Vacuum	1	VV	Cast cutter with vacuum. Item has 2 HP motor and is enclosed in wheeled canister. It is equipped with built-in standpipe and handle, large bag, extractor hose, and 25 foot power cord. Item is designed for orthopedic use.	N/A

M7470	Light, Surgical, Ceiling, Single, Small	1	CC	Ceiling mounted surgical light. Consists of a single lamp head up to 24" in diameter depending on the manufacturer. Unit provides heat filtered, color corrected light. Most lights require a minimum ceiling height of 8 feet 2 inches; check manufacturers' specific recommendations. Light head is in a movable yoke attached to a column hanging from the ceiling. For minor surgery and obstetrical procedures. Physical dimensions refer to the retracted light; one length of the dual swing arm around the center mount for width and depth and the height is the combined lamp head and folded arms height.	26 55 71
M8320	Table, Treatment, Hi/Lo	1	VV	Hi/lo metal treatment table. Unit consists of a hydraulic electromechanical power system operated with a hand or foot control. Includes a foam pad, upholstered top with back section adjustable to a full chair position. Adjustable height from 24" to 39". Provides easy access for patients in wheelchair or stretcher. Designed for general examinations as well as orthopedic and Ob-Gyn.	N/A
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.	N/A
P7650	Trap, Plaster, Small	1	CC	Plastic or metal bodied plaster trap. The unit has a one piece body which is approximately 12 inches deep. The top has 1.5 inch inlet and drain connections. The trap is used in laboratories to capture solids and preclude the clogging of drain lines. The installation must allow sufficient clearance above or below the unit (depending on the manufacturer) to remove the basket for cleaning.	N/A
X4111	Console, PACS, Remote View, 1k X 1k, 1 Monitor	1	VV	One monitor remote viewing for picture archiving and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display on a 1K X 1K single monitor. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.	N/A

**4. Consult Room, Multi-Specialty (OFDC2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

**5. Exam Room, Multi-Specialty (EXPA1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 4. Exam Room, Patient Aligned Care Team (PACT) (EXPA1)

**6. Exam Room, Podiatry (EXP01)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A1132	Rail, Accessory Mounting, Length As Required	2	VV	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M1803	Workstation, Computer, Wall Mounted, Adjustable		VV	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.	N/A
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.	N/A
M4200	Otoscope/Ophthalmoscope, Wall Mounted	1	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.	N/A
M4920	Chair, Exam/Treatment, Podiatry, w/Motor	1	VV	Podiatry exam/treatment chair. Unit is motor driven and has a foot control with gliding foot rest and debris tray. It may include a shoe tray. Unit is fully adjustable to the desired position. It is designed for podiatric examinations and procedures.	N/A

M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

**7. Procedure Room, Multi-Specialty (TRPR1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 8. Procedure Room, General (TRPR1)

**8. Toilet, Multi-Specialty Procedure Room Patient (TLTB1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 9. Toilet, General Procedure Room Patient (TLTB1)

**9. Treadmill Room (OPTM1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	8	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: <input type="checkbox"/> 2 Vertical Hanging Strips <input type="checkbox"/> 1 Lockable Flipper Unit <input type="checkbox"/> 1 Shelf, Storage/Display <input type="checkbox"/> 1 Light <input type="checkbox"/> 1 Cantilevered Work Surface	N/A

E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, Approx 23"W x20"D. THIS TYPICAL INCLUDES: <ul style="list-style-type: none"> <li>1 Wall Mounted Rail</li> <li>1 Locked Storage Container</li> <li>4 Tray/Shelves</li> <li>5 Drawers, 3"H (76mm)</li> <li>2 Drawers, 6"H (152mm)</li> <li>2 Tray/Shelf Dividers</li> <li>Drawer Organizer Bins</li> </ul> Consider the need for an E0921 to transport the locker from place to place.	N/A
E0954	Cart, Emergency, Mobile, 66"H x 52"W x 22"D	1	VV	THIS TYPICAL INCLUDES: <ul style="list-style-type: none"> <li>1 Cart body, style-A narrow, w/raised edge top and breakaway lock bar w/tabs</li> <li>2 Accessory rails, side</li> <li>1 Accessory rail, back</li> <li>1 Defibrillator tray; 1 IV pole</li> <li>1 Flip-up shelf</li> <li>1 Wastebasket and holder</li> <li>1 Oxygen tank holder</li> <li>1 Cardiac board and hanger</li> <li>1 Electrical box-4 outlet</li> <li>1 Cord wrap</li> <li>4 Drawer, 3"H (76mm)</li> <li>3 Drawer, 6"H (152mm)</li> <li>Drawer organizer bins.</li> </ul>	N/A
E1500	Rail, MOD, W/MNTD, HX144XD	1	CC	Wall mounted rail used for hanging (mounting) lockers, shelves drawers on a wall.	N/A
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.	22 63 00
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.	22 63 00
M0765	Regulator, Vacuum	2	VV	An air/oxygen mixer is designed to accurately control a pressurized gas mixing with an oxygen concentration. Unit contains audible alarms to warn of supply failure, an auxiliary outlet and a oxygen concentration control adjustment range from 21% to 100%. The unit can also be used to supply an accurate pre-mixed gas source to respiration or ventilator units. A specific application may require an additional air inlet filter/water trap.	22 63 00



M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; a 3.5" floppy drive; 1.44MB network interface card; video 32 MB NVIDIA; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.	N/A
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.	N/A
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.	N/A
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.	N/A
M7710	Electrocardiograph, 12 Lead, Portable	1	VV	Used to detect the electrical signals associated with cardiac activity, diagnose cardiac abnormalities, determine a patient's response to drug therapy and reveal trends or changes in heart function. Capable of recording two or more leads simultaneously, recording an entire 12 lead ECG in about 10 seconds. Includes of a 3.5 inch, high density, floppy disk drive for test storage. Portable.	N/A
M8133	Ergometer, Upper Body	1	VV	Ergometer for measuring upper body exertion during an exercise regimen. The unit consists of a seat and a hand crank mechanism at shoulder height. The unit is used for physical rehabilitation protocols and stress testing. The unit quantifiably measures the effort exerted by the patient.	N/A
M8185	System, Stress Exercise, w/Treadmill	1	VV	Stress exercise system with treadmill and respiratory/metabolic assessment. The system includes an ECG amplifier, chart recorder, display, console, treadmill and modules for respiratory/metabolic assessment. Used to determine patient's functional capacity, predict and diagnose cardiopulmonary and vascular diseases and for rehabilitation of patients covering from leg injuries or other type of illness. Some vendors require a NEMA 5-20R non-locking receptacle for their treadmills.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

**10. Toilet, Multi-Specialty Patient (TLTB1)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 9. Toilet, General Procedure Room Patient (TLTB1)

**J. FA10: Physical Medicine and Rehabilitation (PM&R) Clinic****1. Dressing Room (DR001)**

A1030	Locker, 2 Person, Over/Under	1	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.	N/A
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00

**2. Treatment Exercise Area (PTEA1)**

A1010	Telecommunication Outlet	4	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A1080	Mirror, Posture, Wall Mounted	4	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
G0144	Ergometer, Recumbent Stepper	1	VV	Seated stepping ergometer for total body, arms and/or legs low impact conditioning. The unit features a closed kinetic chain action which combines reciprocal stepping and arm action. The arm settings and seat are adjustable. A battery operated performance computer allows for adjusting workload level. The unit has a heavy duty steel frame construction with low-density plastic covers	N/A
G1007	Ergometer, Stationary, Stair	1	VV	Stair climbing exercise unit for use in physical training in a gym or in rehabilitation exercise protocols in a physical therapy clinic. The unit includes foot pedals, variable resistance settings, several exercise routines with varying intensity settings and a display for motivation and monitoring. Some models have optional direct or telemetric pulse monitoring. Database electrical specifications are for those models which require power. Refer to the manufacturers' specifications to verify electrical requirements.	N/A

G1026	Exercise Apparatus, Weight Training, Multi-Station	1	VV	Multi-station weight training apparatus for physical development and rehabilitation. Unit features a variety of benches, pull bars, supports and seats grouped around a central frame containing one or more weight stacks. Each station is designed to exercise specific muscle groups. A person can perform an extensive weight training routine by moving around the apparatus from station to station. More than one person can use the apparatus simultaneously by training at different stations. The number and types of exercises available depend on the specific model of equipment chosen. Greater system weight capacities for high level athletic competition training are available on some models. The room ceiling may have to be raised to accommodate this equipment. The database specifications refer to a higher end system with a large number of training stations and a standard weight set.	N/A
G1037	Weight Set, Exercise, Dumbbell	1	VV	Set of weightlifting dumbbells for use in physical training or rehabilitation. Weights can be plain metal, rubber cushioned metal or chrome plated and are in matched pairs at each weight increment. Database information refers to a large set of matched weights increasing in 5-lb. increments from 5-lb. to 100- lb. (20 pairs of weights) stacked on the floor. Differing manufacturers may offer more or less extensive selections. The individual facility's requirement will determine the exact set configuration and cost. See JSN G1040 for the racks to hold these weights.	N/A
G1040	Rack, Dumbbell	1	VV	Rack for holding dumbbells in a gym or rehabilitation facility. The manufacturers provide several different rack styles and capacities depending on the number and type of dumbbells the rack(s) will hold. The database information is for a double rail rack holding twenty (ten pairs) of full size metal plate dumbbells.	N/A
G1043	Ergometer, Recumbent Bicycle, Computer Assisted	1	VV	Computer assisted recumbent bicycle aerobic trainer. The trainer provides aerobic workouts on a computer controlled and monitored recumbent bicycle ergometer. The ergometer has several training routines and intensities which either the exerciser or a therapist can select. The unit display provides a readout of work accomplished as well as graphics to motivate the exerciser. Many models offer optional heart rate monitoring and wheels for easy mobility. Depending on the manufacturer and model, the computer is powered by the exerciser or an external source. The database electrical requirements are for those units requiring electrical power. The trainer is used for cardio-respiratory development in a gym or the exercise area of Physical Therapy.	N/A
M8075	Lift, Patient, Physical Therapy	1	CC	Physical therapy patient lift. The unit is constructed of durable stainless steel and bolted to the floor. The lift consists of a water powered hydraulic lift cylinder, lift swing arm and swivel chair with armrests. The unit is equipped with a control panel and below the floor foundation tube. This lift is custom made to meet specific buyer's needs. Refer to JSN descriptions for hydrotherapy baths and whirlpools before specifying this JSN in drawings. Lifts are integral parts of many baths and pools. The unit is used in physical therapy areas.	N/A
M8125	Ergometer, Bicycle, Stationary	2	VV	Bicycle ergometer. The unit includes an adjustable seat, pedals with toe clips, disc brakes, and tachometer/odometer. The display provides readouts of time, speed and distance. The unit features steel construction for durability and reliability. The ergometer is used in progressive rehabilitation or physical training programs.	N/A
M8133	Ergometer, Upper Body	1	VV	Ergometer for measuring upper body exertion during an exercise regimen. The unit consists of a seat and a hand crank mechanism at shoulder height. The unit is used for physical rehabilitation protocols and stress testing. The unit quantifiably measures the effort exerted by the patient.	N/A
M8140	Exerciser, Ladder	1	CC	Shoulder abduction ladder. Exercise ladder consists of a hardwood unit with 33-36 steps each 2 1/2"W X 1 1/2"H.	N/A
M8145	Exerciser, Staircase, Convertible	1	VV	Convertible exercise staircase. Staircase is sturdily built in two sections permitting a corner type or straight type arrangement. It consists of steps 30-36" wide and a square platform. It includes handrails to accommodate both children and adults. Both steps and platform are covered with non-slip tread.	N/A

M8150	Exerciser, Ramp and Curbs	1	VV	Heavily constructed ramp and curbs exerciser. Unit includes three wide, deep curbs which are 2", 4" and 6" high. The ramp section is also deep and wide and rises gradually from 1/2" to 8" high. The end portion of the ramp section is an 8" high platform which the curb sections meet. The curbs and ramp have a sure-grip, long wearing, non-slip surface. The exerciser is used for training in walking techniques as well as balance.	N/A
M8210	Cart, Weight, Physical Therapy, w/Weights	1	VV	Physical therapy weight cart equipped with weights, two storage shelves, and racks to store dumbbells. Unit is constructed of quality hardwood and mounted on 4 heavy-duty casters. Used for storage of weights.	N/A
M8240	Parallel Bars, Physical Therapy	1	VV	Physical therapy parallel bars. Unit can have manual or electrically powered adjustments. Bar height is adjustable from 25" to 40" and the bar width is adjustable from 16" to 25". Hand rails are chrome plated 1-1/2" steel tubing. Walking aisle is a minimum of 24" wide and finished in natural wood or covered with vinyl matting. Database information reflects 10' or 12' bar length electrically powered units.	N/A
M8245	Platform, Exercise, w/Mat	1	VV	Exercise platform with mat. Platform is ruggedly constructed to resist dents and scratches from wheelchairs and braces. Item has thickly upholstered 2" polyfoam mat with nylon-reinforced tear proof cover. Item is normally used by patients in wheelchairs or with braces.	N/A
M8305	Platform, Exercise, w/Mat, Powered	2	VV	Exercise platform with power height adjustment. The platform rests on one or two pedestal bases which contain the power mechanism for adjusting the table height. The platform top or removable mattress is covered with heavy duty, nylon-reinforced vinyl for durability. The adjustable height feature is designed to accommodate patients who have difficulty sitting or transferring from a wheelchair as well as providing an optimal working height for the physical therapist once the patient is on the table. Larger and smaller units as well as manual crank platform tables are available.	N/A
M8330	Treadmill, Electric	1	VV	Electric treadmill. Unit consists of a strong steel frame with front and side handrails covered with foam rubber, a remote control unit and a moving belt with a speed range from 0 to 10 mph. The unit also has a patient-controlled start/stop switch and a resettable distance counter. The motor controls the belt speed and changes the elevation of one end of the treadmill up to a 20 degree incline. The unit can be used as an exercise/therapy apparatus or in the practice of preventive medicine. Because of their power requirements, treadmills are also available as 208V powered units. At 110V, a treadmill may require a dedicated circuit. Refer to the manufacturer's literature and the specific installation site for deciding which voltage to use. See JSN M8185 for treadmill/electrocardiography systems used in cardiology studies.	N/A
M8331	Treadmill, Weight Bearing System	1	VV	Incremental weight bearing system. Unit is used to limit weight bearing while exercising on a treadmill. Includes frame, harness, sensor, controller and side pads. Does not include the treadmill.	N/A
M8335	Exerciser, Continuous Passive Motion (CPM)	1	VV	Continuous passive motion exerciser (CPM). The unit provides mobilization of a patient's limbs with little or no effort required by the patient. The exerciser is used postoperatively to mobilize knees or shoulders to reduce recovery time and speed ambulation of the patient. The unit is motor driven and may be adjusted to fit a variety of patients. The exerciser also includes adjustments for limiting the range of motion.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

### 3. Treatment Room (PTTC1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00

A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 21 23
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.	N/A
M8174	Ultrasound/Neuromuscular Stimulation Combo Unit	1	VV	Ultrasound unit in combination with a neuromuscular stimulator; unit can deliver both types of treatments simultaneously or individually. The ultrasound unit operates at one or more frequencies. The electrotherapy portion of the instrument can operate at set voltages or continuously variable across a range. Depending on the ultrasound frequency and electrotherapy voltage, the clinician selects one of several treatment unit heads. Some models feature microprocessor controls, data collection, data correlation and data downloading for analysis over time.	N/A
M8315	Table, Traction, Physical Therapy	1	VV	Physical therapy traction table. Upholstered table top with a removable non-friction rolling lumbar section for smooth efficient traction. Mounting board is height adjustable. Some tables include traction units. Used in physical therapy during traction treatments.	N/A

#### 4. Office, Therapist (OFA04)

See Above: G. EYE CLINIC, Office, Blind Rehabilitation (VIST) Counselor (OFA04)

#### 5. Storage, Equipment (SRE01)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

#### 6. Toilet, PM&R Patient (TLTU1)

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

### K. FA11: Prosthetics and Sensory Aids Clinic

#### 1. Sub-Waiting, Prosthetics Patient (WRC03)

See Above: G. EYE CLINIC, 1. Sub-Waiting, Dilation Patient (WRC03)

**2. Workstation, Dispensing Prosthetic Clerk (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**3. Mailing Room, Prosthetic Appliances (MRPA1)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
E0048	Workcenter, Computer, Free Standing, 72" W	1	CC	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

**4. Storage, Prosthetic Appliances (SRCS1)**

A5125	Rack, Crutch, Wall Mounted	2	CC	Wall mounted crutch rack. Constructed of natural finished wood with chrome plated adjustable hangers. Designed for hanging crutches and accessories.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

**L. FA12: Home Based Primary Care****1. Team Work Area, Home-Based Primary Care (WRTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

**2. Storage Room (SRE01)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

**M. FA13: Radiology Service**

<b>1. Sub-Waiting, Diagnostic Patient (WRC01)</b>					
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	CC	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.	05 50 00

A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.	N/A
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.	N/A
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	N/A

## 2. Dressing Room (DR001)

See Above: J. PHYSICAL MEDICINE AND REHABILITATION (PM&R) CLINIC, 1. Dressing Room (DR001)

## 3. Bone Densitometer (XDBD1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
X2120	Scanner, Bone Density, Full Body	1	VV	Full body scanner used to determine bone mineral density measurements and vertebral assessment associated with osteoporotic fracture risk.	13 49 00

**4. Radiology Room, General Purpose (XDR01)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.	N/A
F0465	Cabinet, Storage, 2 Door, 5 Shelf	1	VV	Storage cabinet, 78" high X 48" wide X 24" deep with two (2) doors and five (5) adjustable shelves.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
X1405	Stand, Bucky, Vertical, Tilt, Automatic	1	VV	Vertical and tilting bucky stand. This unit is mounted to the floor and wall to provide a vibration-free mounting platform for the universal bucky. The grid line free radiographs are produced at exposure times as short as two milliseconds. Characteristics and components include aluminum interspaced grid with a 36 inch (914 mm) to 40 inch (1016 mm) focal range. The unit's cassette size sensing tray accommodates all cassette sizes between 5 and 17 inches. The unit tilts at angles of +90/-20 degrees from the vertical position. The unit is used in X-ray facilities for processing radiography images.	13 49 00
X3150	Rack, Apron/Gloves, Wall Mounted	1	CC	Apron and gloves rack. This is a wall unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum. The unit's convenient on wall storage will prolong the useful life of your protection aprons by helping prevent damage to internal components.	N/A



X5700	Radiographic Unit, 65 kW, Non-Tilt Table	1	VV	This system is specifically designed to perform radiographic examinations in the Radiology Department. This units characteristics and components include, 65 kW micro-processor controlled X-ray generator, non-tilting table with a horizontally adjustable bucky and floating table top, ceiling suspended 0.6/1.0 mm tube unit and vertical bucky stand.	13 49 00
-------	--	---	----	---	----------

**5. Radiographic / Fluoroscopic (R/F) Room (XDRF1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.	N/A
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	N/A

X3155	Rack, Apron/Gloves, Mobile	1	VV	Apron and gloves rack. This is a mobile unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum	N/A
X6185	Rad/Fluoro Unit, Remote, 80 kW, 90/90 Table	1	VV	This system is specifically designed to perform radiographic/fluoroscopic examinations in the Radiology Department. On-line digital image processing will provide instant availability of images for review via infrared remote control. This units characteristics and components include, 80 kW micro-processor controlled X-ray generator, remote-controlled 90/90 table with 15" multi-field Image Intensifier and integrated tube support. The Digital Spot Imaging consists of a computer, keyboard with acquisition, viewing monitor and a slave monitor. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended.	13 49 00

**6. Toilet, R/F Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**7. Ultrasound Room (XDUS1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5180	Track, Cubicle, Surface Mounted, With Curtain	12	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 28 00
C0036	Rail, Apron, 4x30x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.	12 32 00
C03F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x30x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.	12 32 00

CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	10 28 00
CT020	Countertop, Solid Surface	5	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 32 00
E0930	Locker, Supply, 6 Drawers, Mobile, 29"W x 20"D	1	VV	THIS TYPICAL INCLUDES: 1 Mobile Supply Locker 2 Tray/Shelf 4 Drawers, 3"H 2 Drawers, 6"H Drawer Organizer Bins	N/A
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.	N/A

M4266	Pump, Volumetric, Infusion, Multiple Line	1	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.	N/A
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.	N/A
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.	N/A
M8940	Stool, Anesthesia, With Back	1	VV	Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.	N/A
X2100	Scanner, Ultrasound, General Purpose	1	VV	High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse and continuous wave imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.	13 49 00

**8. Toilet, Ultrasound Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**9. Sub-Waiting, Mammography Patient (WRC01)**

See Above: M. RADIOLOGY SERVICE, 1. Sub-Waiting, Diagnostic Patient (WRC01)

**10. Mammography Room (XDM01)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00

A5180	Track, Cubicle, Surface Mounted, With Curtain	13	CC	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	10 28 00
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0360	Footstool, Straight w/Handle	1	VV	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
X3150	Rack, Apron/Gloves, Wall Mounted	1	CC	Apron and gloves rack. This is a wall unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum. The unit's convenient on wall storage will prolong the useful life of your protection aprons by helping prevent damage to internal components.	N/A
X5430	Radiographic Unit, Mammography, Digital	1	VV	This is a full-field digital mammography system for screening and diagnostic procedures for standing, seated or recumbent patients. The system is a computer controlled, menu-driven unit for exclusive use in mammography examination procedures. System shall provide superior imaging, maximum patient comfort and enhanced operating efficiency. Shall have stereotactic biopsy capability if this option is selected.	13 49 00

**11. Toilet, Mammography Patient (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**12. Viewing Room, Picture Archiving and Communication System (PACS) (XVC01)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A

E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.	N/A
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
X4124	Console, PACS, Remote View, w/Four 2MP Monito	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.	N/A

**13. Office, Radiology (OFDR1)**

A1010	Telecommunication Outlet	3	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.	N/A

E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A
F0115	Bookcase, Open, 5 Shelf	1	VV	Freestanding open shelf bookcase, approximately 82" high X 37" wide X 18" deep with 5 (five) adjustable shelves. Unit can be separate or part of a system with available add-on shelving.	N/A
F0205	Chair, Side With Arms	2	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
X4122	Console, PACS, Remote View, w/Two 3MP Monitors	1	VV	Two monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on a two 2048 X 1536 image display monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.	N/A

**14. Workstation, Radiology Tech (OFA03)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**N. FA14: Pathology and Laboratory Medicine (PLM) Service**

<b>1. Blood Specimen Collection Room (LBVP1)</b>					
A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	N/A
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; Drawer organizer bins	N/A
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins	N/A



E0963	Cart, General Storage, Mobile	1	VV	Mobile General Storage Cart, approximately 72"H x 23"W x 22"D. THIS TYPICAL INCLUDES: 1 Locker Storage Container on Wheels, w/Solid Door 3 Tray/Shelves 2 Drawers, 3"H 4 Drawers, 6"H 1 Tray/Shelf Divider Drawer Organizer Bins	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
L1350	Centrifuge, Table, Small, 3200 RPM, 6 Place	1	VV	Small table centrifuge. Characteristics/components include a speed range up to 3200 RPM, steel guard bowl, electric motor, speed controlled by a dial rheostat, a six place trunnion head to accommodate 15 ml tubes contained in metal shields with rubber cushions, numbered tube slots and a safety cap. Used in a laboratory for general purpose centrifugation of samples.	N/A
L8520	Shaker, Rotating, 12 Standard Tubes	1	VV	Rotator/shaker. The unit has a speed range approximately 6 to 60 RPM, an adjustable place head, and the capability to hold all tubes 10 to 19 mm in diameter. Used for hematology procedures, micro-diffusion techniques, precipitate washing, blood gas saturation and more.	N/A
M1410	Chair, Laboratory, Blood Drawing, w/Storage	1	VV	Laboratory blood drawing chair with storage. Chair has built-in storage cabinet(s) and locking arm assembly that may be positioned on either side of the fiberglass chair.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.	N/A
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 40 00
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

## 2. Toilet, Specimen Collection (TLTU1)

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

## 3. Laboratory, General (LBGM1)

A1010	Telecommunication Outlet	3	CC	Telecommunication outlet location.	27 31 00
-------	--------------------------	---	----	------------------------------------	----------

A1013	Telephone, Wall Mounted, Multiple Line	1	CC	Telephone, wall mounted, multiple line.	27 31 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	2	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5230	Cabinet, Blanket, Fire, Wall Mounted	1	CC	Fire blanket cabinet with fire blanket, wall mounted cabinet. Finish is rust and acid resistant baked enamel and designed for storage of fire blankets.	N/A
E0589	Workstation, Chemistry Lab, Medium	1	VV	THIS TYPICAL INCLUDES: 6 Module, 80"H x 48"W,w/ 7-1/4 inch utility chase, w/ service shelf; 1 Clinical Panel, Open 80"H x 24"W; 3 Clinical Panel, Open 80"H x 30"W; 1 Clinical Panel, Open 80"H x 48"W; 3 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 30"W; 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 1 Clinical Panel with Floor Entry ELEC/Data Channel, 48"H x 48"W; 2 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 48"H x 48"W; 3 Clinical Panel, 80"H x 30"W; 2 Clinical Panel, 80"H x 48"W; 2 Vertical Chase Cover; 1 Electrical/Data Channel 30"W; 8 Electrical/Data Channel 48"W; 1 Electrical/Data Channel 72"W; 1 Electrical/Data Channel, Corner; 1 Light, 24"W; 9 Light, 48"W; 1 Cantilevered Work Surface, 30"D x 24"W, With Supports; 10 Cantilevered Work Surface, 30"D x 48"W, With Supports; 1 Cantilevered Corner Work Surface, 30"D x 48"W; 1 Height Adjustable Table, 36"D x 72"W; 3 Adjustable Keyboard Tray; 6 Mobile Drawer Caddie with Drawers; 5 DR, 3"H; 11 DR, 6"H; 1 DR, 9"H; 2 Storage Frame; 3 Storage Cabinet With Door; 1 Mobile Cart w/Top Surface; 1 Lockable Flipper Unit, 24"W; 8 Lockable Flipper Unit, 48"W; 1 3-Shelf Unit with Door, 48"W; 1 Shelf, Storage/Display 24"W; 8 Shelf, Storage/Display 48"W; 4 Extra Deep Shelf, 48"W; 1 Sink Base Cabinet, w/Double Door, Backsplash, w/Corian Top, 30"D x 60"W; 1 Swing-Away Evewash	N/A
F0230	Chair, Drafting, Rotary	3	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
F2000	Basket, Wastepaper, Round, Metal	3	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A

L0100	Microscope, Binocular	2	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.	N/A
L0990	Analyzer, Urine, Basic	1	VV	Basic urine analysis system. Automated system provides 8 chemistries. Unit requires only power connection. This unit is a benchtop instrument.	N/A
L1035	Analyzer, Chemistry, Stat	1	VV	Stat chemistry analyzer. The unit performs tests in <10 minutes. The test parameters are serum, urine and CSF. The unit performs over 37 routine tests. The analyzer can process 100 samples at a time with a maximum analytical rate of 420 tests per hour. It is used for electrolytes, blood hematocrit and other routine chemistries.	N/A
L1100	Meter, pH	1	VV	pH meter. The units capabilities/characteristics include ion analyzer capability, provides measurements of pH, temperature, MV and others. The unit includes self-diagnostics, an automatic buffer recognition and a gel-filled electrode. Used for direct measurement of activity concentration.	N/A
L1115	Analyzer, Hematology, Differential, Automatic	1	VV	Automatic hematology counter/analyzer. The analyzers characteristics/components include the measurement of eight hematology parameters as well as platelet counts, auto-rinse cycle between analysis, minimum specimen requirement of 100 microliters, readout results in 40 seconds, automatic calibration and capable of computerized differential counting and manual verification of results. Used for hematology analysis.	N/A
L1182	Refractometer	1	VV	Refractometer. Characteristics/ components include an accommodation of liquids, solids, solids-in-liquids and powders, temperature measured at interface of samples, photosensors measurement, automatic calibration, multi-channel programming, an accuracy of +/- .0001 refractive unit and automatic temperature compensation. Used for glucose and urine refractive indexes.	N/A
L1185	Analyzer, Glucose	1	VV	Discrete glucose analyzer. Characteristics include sample volume of 10 microliters, measurement principle of the oxygen rate method, throughput of 67 samples per hour and a glucose value displayed in mg/dl. This is a self contained system with automatic fill and drain cycles. Used for glucose analysis of serum plasma or saliva samples.	N/A
L1190	Osmometer	1	VV	Osmometer. Characteristics/components include semi-automatic operation, measurement of osmolality of 0.2ml samples, accuracy to (+/-) 0.5%, temperature controlled liquid freezing bath, flow-through cell assembly and high speed testing capability. Used to determine precise concentration of solute particles for urines, urea, free water clearances, electrolyte studies, serum and other applications.	N/A
L1400	Centrifuge, Microhematocrit, 24 Tube	1	VV	Microhematocrit centrifuge. Characteristics/components include speed up to 13000 RPM, a flat head to accommodate 24 capillary tubes, electronic automatic timer that times from 2-15 minutes, built-in precise hematocrit scale and a removable carrying tray. Used for determination of hematocrits.	N/A
L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.	N/A

L1770	Ultracentrifuge	1	VV	Ultracentrifuge. The unit handles tubes from 0.2ml to 3.5ml, has a programmable memory for repeat of select runs and has selectable acceleration and deceleration rates. It operates in the range from 2-40 degrees C. The unit has a digital timer, and electronic door locking mechanism. The maximum speed is 90,000 RPM. Applications range from use as a simple pelleting device to the quantitation of molecular species by sedimentation equilibrium measurements.	N/A
L2000	Purification System, Water	1	CC	Water Purification System (also referred to as a water-polishing unit) that is capable of producing not less than 24 liters of water per hour, free of ionic contamination and with reduced Total Organic Compounds (TOC) not to exceed 6 parts per billion and water resistivity up to 18.3 megohm-cm from a clean (tap) water source. Purified water to be used for HPLC or GC/MS applications and TOC analysis. System must utilize operator replaceable cartridges and UV light source to obtain the specified purity. System must be fully automatic and switch to a standby mode during periods of reduced use. Design must incorporate a resistivity indicator and a final bacterial 0.22 micrometer filter.	N/A
L2336	Cabinet, Bio Safety, Class II/B2, Bench Top, 4ft	1	CC	Class II, Type B2, benchtop biological safety cabinet. The unit includes two HEPA filters, one supply and one exhaust, zero probed, high intake velocity that averages 105 fpm, an audible alarm to notify operator of unsafe window positions an audio-visual alarm to monitor exhaust pressure, interior of type 304 stainless steel with side walls slotted for high velocity air return, an exterior of 16 gauge or heavier steel, two ground key petcocks, a grounded duplex receptacle. Used for low to moderate risk biological agents treated with toxic chemicals and radionucleotides. This unit requires 100% exhaust to the atmosphere. 4 foot model presented, other sizes are available.	N/A
L2570	Incubator, Bacteriological, Single	1	VV	Small bacteriological incubator. It has a corrosion resistant chamber with adjustable shelves and a temperature range of approximately 30-70 degrees centigrade. Used in laboratories to grow cultures.	N/A
L2600	Counter, Cell, Auto	1	VV	Automatic blood cell counter. The counter has a built-in monitoring system. It can perform a test in 13 seconds using a 100 microliter sample and give the results of 3 to 5 parameters of WBC, RBC, Hgb, Hct, and MCV. It has programs that include control data, calibration settings and tests and it has a temperature compensation circuit. Used for hematology analysis.	N/A
L2630	Counter/Timer, Digital	1	VV	Digital counter/timer. The unit can perform frequency measurements in the range of 225 MHz and can perform time interval measurements between two events (start and stop events). The unit has not less than a 6 digit read out. Used for a variety of measurement functions such as frequency, period, time interval (Channel A to Channel B), frequency ratio (Channel A/Channel B), totaling, etc.	N/A
L2650	Counter, Bacteria	1	VV	Bacteria colony counter. This unit is manually adjusted. It is used in bacteriology, virology and mycology laboratories to count or measure bacteria colonies.	N/A
L4200	Bath, Water, Serology, Electric	2	VV	Serological water bath. It operates in the temperature range of 60 to 100 degrees centigrade. It has a corrosion-proof stainless steel water tank with a 3 gallon capacity. Models have drain spouts for easy emptying of media. Used to provide a controlled temperature environment for the preparation of samples for study.	N/A
L7300	Stirrer, Hot Plate, Magnetic	1	VV	Magnetic stirrer-hot plate. It has variable stirring speeds of near 1500 RPM, temperatures of up to about 400 degrees centigrade, back up safety thermostat, plate surface of about 49 square inches and Pyroceram glass ceramic top that is corrosion resistant. Used for reagent mixing and heating, preparing culture media, evaporation and distillation procedures.	N/A
L7305	Mixer, Vortex, Test Tube	1	VV	Vortex test tube mixer. This is a single well type with a stirring action that starts with a touch of the test tube. It is a variable speed unit from 100-3000 rpm. Used in a laboratory for mixing small samples in a test tube, colorimetric tubes or Erlenmeyer flasks.	N/A

L7330	Rotator, Mixer	1	VV	Rotator mixer. It operates between 1-20 RPM oscillation and has reversible cushioning that cradles specimen tubes. It can accommodate up to fifteen 12 X 75ml tubes or ten 17X100ml tubes and has a precision controlled platform with mixing adjusting zones of 1-48 degrees angle. Used for uniform specimen suspension mixing.	N/A
L8520	Shaker, Rotating, 12 Standard Tubes	1	VV	Rotator/shaker. The unit has a speed range approximately 6 to 60 RPM, an adjustable place head, and the capability to hold all tubes 10 to 19 mm in diameter. Used for hematology procedures, micro-diffusion techniques, precipitate washing, blood gas saturation and more	N/A
L8580	Stainer, Slide, Automatic, Hematology	1	VV	Automatic slide stainer. This is a microprocessor controlled stainer designed for minimum of 20 slides at one time. It includes a staining station, rinsing station and drying station. For use in microbiology, histology, and hematology laboratories.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M1840	Printer/Copier/Fax Combination	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.	22 40 00
R6070	Refrigerator/Freezer, Biological, Upright, 18 Cu Ft	1	VV	Biological refrigerator with freezer. This unit includes a freezer compartment for general laboratory use. Its independent direct-set temperature controllers allow temperature selection for +2° to 14°C for the refrigerator, and from -20° to -30°C for the freezer.	11 53 23
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	1	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.	11 53 23

#### 4. Laboratory, Clinical Chemistry (LMCH1)

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	CC	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
C03P0	Cabinet, Sink, U/C/B, 2 Door, 30" W	1	CC	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	N/A
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	N/A
CS090	Sink, SS, Single Compartment, 7.5x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	N/A
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.	12 36 00
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
L1035	Analyzer, Chemistry, Stat	1	VV	Stat chemistry analyzer. The unit performs tests in <10 minutes. The test parameters are serum, urine and CSF. The unit performs over 37 routine tests. The analyzer can process 100 samples at a time with a maximum analytical rate of 420 tests per hour. It is used for electrolytes, blood hematocrit and other routine chemistries.	N/A

L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A

**5. Shipping / Receiving (LBSS1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
E0573	Workstation, Shipping/Receiving Lab, Minimal	1	VV	THIS TYPICAL INCLUDES: 1 Equipment Rail, System-Mt, 48"W 2 Clinical Panel, 80"H x 30"W 1 Module, 80"H x 24W, w/ 7-1/4inch utility chase, w/ service shelf 2 Module, 80"H x 48W , w/ 7-1/4inch utility chase, w/ service shelf 1 Vertical Chase Cover 2 Service Shelf 48W 2 Light 48W 2 Cantilevered Work Surface 30D x 48W 2 Lockable Flipper Unit, 48W 2 Adjustable Keyboard Tray 1 Sink Base Cabinet, Dbl. Door, Backsplash, w/Corian Top, 30D x 48W 1 Swing-Away Eyewash 1 SS Sink 19D x 33D 1 Gooseneck Mixing Faucet ASSY. With Wristbands 1 Strainer and Tailpiece 1 Coat Hook Drawer Organizer Bins * Connecting hardware required to complete installation.	N/A
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.	N/A

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.	22 40 00
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
R5135	Freezer, Undercounter, 5 Cubic Feet	1	VV	Under counter freezer. This unit features space-saving thin-wall construction and has the flexibility of being built with existing cabinets, installed under-counter without top or custom-finished to specifications. This unit is a general purpose laboratory freezer.	N/A
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.	11 53 23

**6. Storage, Bulk (SRS01)**

See Above: H. MENTAL HEALTH CLINIC, 5. Storage, General (SRS01)

**7. Storage, Refrigerated (SRR02)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
R6060	Refrigerator, Biological, SS, 2 Door, 40 Cu Ft	2	VV	Biological refrigerator. This unit shall have a minimum volume of 40 cubic feet, double doors, stainless steel cooler storage with stainless steel drawers, three adjustable shelves and one stationary stainless steel shelf. This refrigerator is used in research laboratories and hospital pharmacies for storage and dispensing of drugs.	N/A

**8. Toilet, Staff (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**O. FA15: Pharmacy Service**



**1. Automated Drug Dispensing System (PHOD4)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
M3150	Distribution System, Medication, Automatic	1	CC	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.	N/A

**2. Dispensing, Window (PHOW1)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	10 28 00
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A

**3. Prescription Receiving, Window (PHOW1)**

See Above: O. PHARMACY SERVICE, 2. Dispensing, Window (PHOW1)

**4. Consult Room, Pharmacy (OFDC2)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

**5. Workstation, Pharmacist (OFA03)**

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

**6. Toilet, Staff (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**7. Pharmacy, PACT 2 (PHOD5)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00

A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	10 28 00
E0612	Shelf Unit, Pharmacy, Wall Mtd, 88"Hx48"Wx16"D	6	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 9 Shelf, Unit	10 28 00
E0648	Station, Picking, Pharm, U-Shape, Free Std, 144x72	1		THIS TYPICAL INCLUDES: 12 solid panels, 85"H x 24"W; 1 solid panel, 85"H x 48"W; 4 panel connectors, 2-way corner, 85"H; 8 panel-to-panel connectors; 2 finished end hardware kits; 6 3-shelf units, 24"W; 1 5-shelf unit, 48"W; 2 corner, 5-shelf units, 48"W; 380 bins, 2-1/4"W x 2-3/16"H; 50 bins, 4-9/16"W x 2-3/16"W; 2 cantilevered, corner work surfaces, 48"W; 1 cantilevered work surface, 48"W; 1 drawer, 3"H and 1 drawer, 6"H .	N/A
E0978	Cart, Wire, Mobile, 72"H x 48"W x 24"D	1	VV	THIS TYPICAL INCLUDES: 1 Wire Cart, w/Casters 5 Wire Shelves w/Fences and Dividers 4 Vertical Back/Side Panels 1 Cart Cover Label Clips	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0530	Cart, Trash	1	VV	Heavy duty trash cart, approximately 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, one (1) or two (2) swivel casters, 2000 pound capacity and tilt mechanism.	N/A
F2000	Basket, Wastepaper, Round, Metal	3	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2026	Container, Recycling, Large	1	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.	N/A
F3200	Clock, Battery, 12" Diameter	2	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
L1200	Cabinet, Specimen, Pass Thru, CRS	3	CC	Pass-through specimen cabinet. The unit has a sight-proof interlocking door that permits only one door to open at a time. It also includes a removable spill tray, corrosion resistant stainless steel welded construction with seamless corners and burr-free edges and is able to adjust to wall thickness between 3-6 inches. Used for passage of specimens from patient area to laboratory.	08 56 19

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1830	Printer, Label, Pharmacy	2	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M1840	Printer/Copier/Fax Combination	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A
M7280	Dispensing System, Prescription, Robotic	2	VV	Robotic prescription dispensing system. System handles 200 tablets and capsules and delivers filled and labeled vials at a rate of up to 100 prescriptions per hour. System uses a computer controlled robotic arm to fill vials directly from medication dispensing cells.	N/A
P1960	Eyewash, Counter Top	1	CC	Counter top mounted emergency eye wash station. Unit is hand operated to provide streams of water to clear or dilute foreign particles or liquids from the eyes in emergency situations. It is equipped with a stainless steel bowl, face spray ring and dual automatic pressure compensation devices. The valve remains open until manually closed. Used in laboratories and areas of the hospital where employees are subject to exposure to foreign bodies or caustic liquid matter to the eyes.	22 40 00
P3100	Lavatory, Vitreous China, Slab Type	2	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
R6060	Refrigerator, Biological, SS, 2 Door, 40 Cu Ft	1	VV	Biological refrigerator. This unit shall have a minimum volume of 40 cubic feet, double doors, stainless steel cooler storage with stainless steel drawers, three adjustable shelves and one stationary stainless steel shelf. This refrigerator is used in research laboratories and hospital pharmacies for storage and dispensing of drugs.	11 53 23
R6100	Freezer, Food, Upright, CRS, 23 CUFT	1	CC	Food freezer approximately 23 CUFT and 84" H x 27" W x 37" D. This unit has a stainless steel case front and doors. The cabinet front and doors are constructed of heavy gauge polished stainless steel to maintain an attractive appearance. The heavy-duty wire shelves are adjustable in one inch increments, used for frozen food storage in food service departments.	N/A
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.	N/A
R7050	Refrigerator, 25 Cubic Feet	1	VV	General purpose refrigerator approximately 84x27x37. This unit is corrosion resistant stainless steel. It has a single self closing door with safety stops. This refrigerator is generally used in commercial kitchens, hospitals and schools.	N/A

**8. Pharmacy, PACT 3 (PHOD6)**

A1010	Telecommunication Outlet	3	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	2	CC	Telephone, desk, multiple line.	27 31 00
A5075	Dispenser, Soap, Disposable	3	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A

A5080	Dispenser, Paper Towel, SS, Surface Mounted	3	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	3	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	10 28 00
E0612	Shelf Unit, Pharmacy, Wall Mtd, 88"Hx48"Wx16"D	6	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 9 Shelf, Unit	N/A
E0648	Station, Picking, Pharm, U-Shape, Free Std, 144x72	1		THIS TYPICAL INCLUDES: 12 solid panels, 85"H x 24"W; 1 solid panel, 85"H x 48"W; 4 panel connectors, 2-way corner, 85"H; 8 panel-to-panel connectors; 2 finished end hardware kits; 6 3-shelf units, 24"W; 1 5-shelf unit, 48"W; 2 corner, 5-shelf units, 48"W; 380 bins, 2-1/4"W x 2-3/16"H; 50 bins, 4-9/16"W x 2-3/16"W; 2 cantilevered, corner work surfaces, 48"W; 1 cantilevered work surface, 48"W; 1 drawer, 3"H and 1 drawer, 6"H .	N/A
E0674	Pharmacy Manuf & Prepack Medium Volume	1	VV	E0674 MFG PRPK, THIS TYPICAL INCLUDES: 4 Shelf Storage Display 24"W; 6 Shelf Storage Display 48"W; 8 Wall Strip, 84"H; 1 Adapter Rail, 48"W; 1 Work Surf, Hvy-Duty 24"D x 48"W; 1 Work Surf, Hvy-Duty 24"D x 72"W; 1 Module, Cant Sink-Adaptable w/Corian Top, 24"D x 48"W; 1 Table, Process w/Casters, Adj Ht 30"D x 48"W; 1 Storage Case, 3 Bottle Dwrs, Legs 1 Storage Frame 2 Drawer, 3("H; 2 Drawer, 9"H; 2 Task Light, 42"W; 1 Eyewash 1 Adjustable Keyboard Tray 1 Sink and Faucet Assembly Drawer Organizer Bins *Connecting hardware required to complete the installation.	N/A
E0978	Cart, Wire, Mobile, 72"H x 48"W x 24"D	4	VV	THIS TYPICAL INCLUDES: 1 Wire Cart, w/Casters 5 Wire Shelves w/Fences and Dividers 4 Vertical Back/Side Panels 1 Cart Cover Label Clips	N/A

F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
F0280	Chair, Swivel, Low Back	2	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0530	Cart, Trash	2	VV	Heavy duty trash cart, approximately 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, one (1) or two (2) swivel casters, 2000 pound capacity and tilt mechanism.	N/A
F2000	Basket, Wastepaper, Round, Metal	5	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2026	Container, Recycling, Large	2	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.	N/A
F3200	Clock, Battery, 12" Diameter	4	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
L1200	Cabinet, Specimen, Pass Thru, CRS	1	CC	Pass-through specimen cabinet. The unit has a sight-proof interlocking door that permits only one door to open at a time. It also includes a removable spill tray, corrosion resistant stainless steel welded construction with seamless corners and burr-free edges and is able to adjust to wall thickness between 3-6 inches. Used for passage of specimens from patient area to laboratory.	08 56 19
M1801	Computer, Microprocessing, w/Flat Panel Monitor	3	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1830	Printer, Label, Pharmacy	3	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M1840	Printer/Copier/Fax Combination	2	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.	N/A
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A
M7265	Counter, Pill/Tablet, Automated, Counter Mounted	1	VV	Table mounted prescription counter device that counts tablets and capsules directly into the final container. The unit shall automatically count and dispense tablets and capsules into a container with speed and accuracy.	N/A

M7280	Dispensing System, Prescription, Robotic	3	VV	Robotic prescription dispensing system. System handles 200 tablets and capsules and delivers filled and labeled vials at a rate of up to 100 prescriptions per hour. System uses a computer controlled robotic arm to fill vials directly from medication dispensing cells.	N/A
P1960	Eyewash, Counter Top	1	CC	Counter top mounted emergency eye wash station. Unit is hand operated to provide streams of water to clear or dilute foreign particles or liquids from the eyes in emergency situations. It is equipped with a stainless steel bowl, face spray ring and dual automatic pressure compensation devices. The valve remains open until manually closed. Used in laboratories and areas of the hospital where employees are subject to exposure to foreign bodies or caustic liquid matter to the eyes.	22 40 00
P3100	Lavatory, Vitreous China, Slab Type	3	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
R6060	Refrigerator, Biological, SS, 2 Door, 40 Cu Ft	2	VV	Biological refrigerator. This unit shall have a minimum volume of 40 cubic feet, double doors, stainless steel cooler storage with stainless steel drawers, three adjustable shelves and one stationary stainless steel shelf. This refrigerator is used in research laboratories and hospital pharmacies for storage and dispensing of drugs.	11 53 23
R6100	Freezer, Food, Upright, CRS, 23 CUFT	1	CC	Food freezer approximately 23 CUFT and 84" H x 27" W x 37" D. This unit has a stainless steel case front and doors. The cabinet front and doors are constructed of heavy gauge polished stainless steel to maintain an attractive appearance. The heavy-duty wire shelves are adjustable in one inch increments, used for frozen food storage in food service departments.	N/A
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.	N/A
R7050	Refrigerator, 25 Cubic Feet	2	VV	General purpose refrigerator approximately 84x27x37. This unit is corrosion resistant stainless steel. It has a single self closing door with safety stops. This refrigerator is generally used in commercial kitchens, hospitals and schools.	N/A

**9. Data Processing (OFA04)**

See Above: G. EYE CLINIC, Office, Blind Rehabilitation (VIST) Counselor (OFA04)

**P. FA16: Clinic Management****1. Office, CMO (OFA04)**

See Above: G. EYE CLINIC, Office, Blind Rehabilitation (VIST) Counselor (OFA04)

**2. Office, Nurse Manager (OFA04)**

See Above: G. EYE CLINIC, Office, Blind Rehabilitation (VIST) Counselor (OFA04)

**Q. FA17: Business Services****1. Workroom, Business Services (WKTM1)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 19. Classroom (WKTM1)

**R. FA18: Engineering Service****1. Repair Shop, Biomedical Engineering (BMER1)**

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	CC	Telephone, desk, 1 line.	27 31 00
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
T0005	Electrical Safety Analyzer	1	VV	Electrical safety analyzer. Characteristics/components include combining all lead connected ECG lead tests measuring individual lead leakage; AC/DC measurement; current consumption; automatic neutral-ground and power-ground resistance and volts. This unit is used for electrical safety testing, preventive maintenance programs and equipment repair. Battery powered models are available.	N/A
T0015	Defibrillator Analyzer, Automatic, Portable	1	VV	Defibrillator analyzer. Characteristics/components include automatic and portable with direct reading; accurately verifies the output characteristics of all defibrillators while simulating the resistance of the human body; output energy measured in joules or watt seconds on two scales of 0-200.0 or 0-1000; output energy remains displayed until the reset button is depressed once the defibrillator is fired; and output jacks provided for oscilloscope connection to observe defibrillator pulse wave shape. Shall include the optional pacemaker testing module if required by the end user. Battery powered models are available.	N/A
T0030	Radiation-Light Field Analyzer	1	VV	Light and radiation field analyzer for quality assurance testing of radiation therapy devices. Unit is self contained and checks the coincidence of light and radiation fields, symmetry of radiation field, flatness of radiation field, and penumbra size of the radiation field. Unit has a built in graphics printer for hard copy output of scanned information.	N/A
T0801	Workbench, Electric, Pedestal Base	1	VV	Electrical workbench approximately 34" H x 72" W x 36" D. Characteristics/components include butcher block maple top; with two drawer or door pedestals and an electronic riser wiring kit. This workbench is used in wood and metal workshops. Workbench is a mix and match construction and can be configured to end users needs.	N/A
T8030	Electrosurgery Analyzer	1	VV	Electrosurgery analyzer. This is a power analyzing system that verifies electrosurgical specifications such as output power, radio frequency leakage and output waveforms. This is necessary because electrosurgical units should provide safe controlled power output at RF with a predetermined physiological load so that burns and electrical shocks are avoided.	N/A

T8055	Wattmeter, Ultrasonic	1	VV	Ultrasonic wattmeter. Characteristics/components include electronic and mechanical design to provide superior performance and greater durability; clear Plexiglas tubing on the front panel that allows the operator to immediately determine the liquid level within the sealed reservoir; and power measurements that can be conveniently read on the LCD display. This unit is a one-of-a-kind instrument used by biomedical repair persons who regularly test therapeutic ultrasound devices. Unit is battery powered.	N/A
-------	-----------------------	---	----	--	-----

## S. FA19: Logistics Service

### 1. Workstation, Logistics (OFA03)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 17. Workstation, Extended Team (OFA03)

### 2. Receiving / Shipping Dock (DOCK1)

A6125	Leveler, Dock	1	CC	Unit attaches to the face of the dock for easy installation. It consists of a counterbalance lip that can be extended to rest on the bed of the trailer for loading and unloading of merchandise. When the trailer departs, the lip will automatically retract behind the bumper face. Size will vary depending on the application.	N/A
K0450	Curtain, Air	1	CC	Air curtain. The unit is generally fabricated to size for operation. This unit is used at entrances and docks to prevent cold and humid or dry and hot air from entering through openings which are exposed to weather conditions. The database pricing reflects an unheated air door 6-1/2' wide with a 3" or 6" deep discharge nozzle to cover a standard two-door width entry. Some units run on 120V power; refer to the manufacturer's specifications for the model chosen. Larger width and industrial duty air doors are available.	N/A
K9300	Washer, Pressure w/Sanitizer	1	CC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.	10 28 00
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.	N/A
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.	N/A
M2120	Truck, Platform, 4 Wheel	1	VV	A 4 wheel platform truck (push cart). Truck has heavy duty platform and is mounted on four 8" diameter casters. The load capacity is 2000-2500 pounds. It is designed for use in the receiving and other material handling areas.	N/A
M4025	Scale, Roll On, Freestanding, 2000 Pound Capacity	1	VV	Freestanding roll on scale with a 2000 pound capacity. Unit consists of a heavy duty anodized aluminum or steel platform with powered digital readout. For use in food service or the laundry.	N/A

### 3. Storage Area, Logistics PACT 1 (SRLG1)

A1010	Telecommunication Outlet	3	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00



E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1840	Printer/Copier/Fax Combination	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.	N/A
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

M2070	Shelving, Storage, 77hx36wx18d	5	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.	N/A
M2085	Shelving, Storage, Pallet	3	VV	Pallet storage shelving starter section. This unit is of heavy duty construction and has channel type bracing in between columns, heavy duty foot plate with 3-point security. The size will be determined by weight load. It is designed for easy forklift access in storage areas and warehouses.	N/A
M2090	Shelving, Storage, Warehouse	3	VV	Warehouse storage shelving approximately 75 inches high by 36 inches wide by 24 inches deep.	N/A
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.	N/A
M2130	Truck, Hydraulic Lift, Electric	1	VV	Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.	N/A
M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.	N/A
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.	22 40 00

#### 4. Storage Area, Logistics PACT 2 (SRLG2)

A1010	Telecommunication Outlet	3	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1840	Printer/Copier/Fax Combination	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.	N/A
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.	N/A
M2025	Rack, Storage, Cylinder, Gas	2	CC	Medical gas cylinder storage rack. Unit is a modular cage frame for holding various sizes of gas cylinders. Nylon or fabric securing straps can be attached to the frame bars to stabilize gas cylinders. Add additional units or specify size as required when ordering. This item is often locally fabricated.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A
M2070	Shelving, Storage, 77hx36wx18d	5	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.	N/A
M2085	Shelving, Storage, Pallet	8	VV	Pallet storage shelving starter section. This unit is of heavy duty construction and has channel type bracing in between columns, heavy duty foot plate with 3-point security. The size will be determined by weight load. It is designed for easy forklift access in storage areas and warehouses.	N/A
M2090	Shelving, Storage, Warehouse	8	VV	Warehouse storage shelving approximately 75 inches high by 36 inches wide by 24 inches deep.	N/A
M2115	Truck, Hand, 2 Wheel	2	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.	N/A

M2130	Truck, Hydraulic Lift, Electric	1	VV	Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.	N/A
M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.	N/A
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.	22 40 00

**5. Storage Area, Logistics PACT 3 (SRLG3)**

A1010	Telecommunication Outlet	4	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	2	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.	N/A
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	2	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2700	Reader, Bar Code, Hand Held, With Interface	2	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.	N/A

M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1840	Printer/Copier/Fax Combination	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.	N/A
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.	N/A
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.	N/A
M2025	Rack, Storage, Cylinder, Gas	3	CC	Medical gas cylinder storage rack. Unit is a modular cage frame for holding various sizes of gas cylinders. Nylon or fabric securing straps can be attached to the frame bars to stabilize gas cylinders. Add additional units or specify size as required when ordering. This item is often locally fabricated.	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A
M2070	Shelving, Storage, 77hx36wx18d	9	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.	N/A
M2085	Shelving, Storage, Pallet	12	VV	Pallet storage shelving starter section. This unit is of heavy duty construction and has channel type bracing in between columns, heavy duty foot plate with 3-point security. The size will be determined by weight load. It is designed for easy forklift access in storage areas and warehouses.	N/A
M2090	Shelving, Storage, Warehouse	12	VV	Warehouse storage shelving approximately 75 inches high by 36 inches wide by 24 inches deep.	N/A
M2115	Truck, Hand, 2 Wheel	2	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.	N/A
M2130	Truck, Hydraulic Lift, Electric	1	VV	Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.	N/A
M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.	N/A

P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.	22 40 00

## T. FA20: Police Service

### 1. Office, Police Service (OFA04)

See Above: G. EYE CLINIC, Office, Blind Rehabilitation (VIST) Counselor (OFA04)

### 2. Operations Room (CROP1)

A1010	Telecommunication Outlet	8	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	4	CC	Telephone, desk, multiple line.	27 31 00
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.	N/A
A5220	Bracket, Television, Wall Backing	2	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.	05 50 00
E0042	Workcenter, Computer, Free Standing, 48" W	2	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray	N/A
E0117	Workstation, Straight, Free Standing, 48" W	2	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.	N/A
F0275	Chair, Swivel, High Back	8	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with woven textile fabric or leather.	N/A
F0425	Cabinet, Filing, Security, Full Height	1	VV	Class 6 full height security filing cabinet, 58" high x 21" wide x 28" deep with five (5) drawers. Used for storage of classified or controlled materials.	N/A
F0780	Table, Work, 60W x 30D	2	VV	Work table approximately 29" high X 60" wide X 30" deep with top and four (4) non-folding legs.	N/A

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2550	Shredder, Paper Heavy Duty	1	VV	Shredder shall be able to process a minimum of 25 sheets of paper per pass at a minimum rate of 20 feet per minute. The unit shall have a 16 inch throat to accept paper. Paper shall be shredded into 1/4 inch strips.	N/A
F3060	Whiteboard, Projection Screen Combination	1	CC	Whiteboard and projection screen combination approximately 48" H x 72" W. Magnetic surface with matte finish for projection. Hard board stabilizer with aluminum foil back. For use with water color pens	N/A
F3200	Clock, Battery, 12" Diameter	4	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
F3230	Rack, Hat / Coat, Wall Mounted	1	VV	Wall mounted hat / coat rack. Decoratively styled and equipped with bars, hooks and hat shelf. For use in waiting rooms.	N/A
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI ( American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.	N/A
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.	N/A
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.	N/A
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	4	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.	N/A
M4125	Radio Communication System	1	VV	Radio equipment to support daily administrative, patient transport, emergency, mass casualty, fire protection and security operations. Includes base station(s), handheld portables, vehicle units, antennas, power supplies, controllers, electrical panels, computers, pagers and other equipment as required. The size, complexity and cost of the system depend on the geographic region covered, dispersement of the facility staff, size and capability of the facility, facility mission and distances to supporting police, fire and disaster relief organizations.	N/A

**3. Locker Room (LR001)**

A1030	Locker, 2 Person, Over/Under	4	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.	N/A
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00

**4. Holding Room (POH01)**

A5020	Bench, Locker Room, Floor Mounted	1	CC	Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.	27 31 00
-------	-----------------------------------	---	----	---	----------

**5. Storage, Secure (SSS01)**

F0425	Cabinet, Filing, Security, Full Height	1	VV	Class 6 full height security filing cabinet, 58" high x 21" wide x 28" deep with five (5) drawers. Used for storage of classified or controlled materials.	N/A
F3105	Safe, F/S , Class 5	1	VV	Class 5 safe, floor standing model with combination lock. Used for storage of narcotics, plans, film, and other classified or control materials.	N/A

**U. FA21: Canteen Service****1. Vending Machine Area (BX002)**

A6030	Machine, Vending	2	L/RE	This JSN is to be used for determining and defining the requirement for vending machines. Item is normally leased or supplied by Canteen Services.	N/A
F0225	Chair, Dining Room	2	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.	N/A
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A

**2. Canteen, PACT 2 (FSCD4)**

_0068	Credit Card Scanner	1	VV	Magnetic Card Reader used to scan credit and debit cards. Approximately 1.34"W x 3.54"D x 1.10"H.	N/A
_0069	Food Case, Grab and Go	1	VV	36-Inch Wide Horizontal Air Curtain Refrigerated Merchandiser, easy customer access to pre-stocked food items and cold beverages.	N/A
_0070	Trash / Recycling Center	1	VV	3- 40 Gallon each, approximately 33-3/4" x 18" x 18" with tops to sort waste, paper, cans and bottles. These units are used to sort trash and items for recycling.	N/A
_0071	Condiments Counter	1	VV	Custom designed unit, provides Canteen customers access to coffee condiments such as sugar, coffee stirrers, napkins, and other items. Custom built with dimensions based on the configuration of the space.	N/A
_0072	Stools, Counter	8	VV	Approximately 41" H x 17" L x 17" W. For use at custom dining counter.	N/A
_0073	Dining Counter (custom)	1	CC	Custom dining counter, approximately 18" D and 42" high. For use by Canteen Customers.	N/A
A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	CC	Telephone, desk, multiple line.	27 31 00
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	12 32 00



CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0225	Chair, Dining Room	2	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F0795	Table, Dining	2	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.	N/A
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.	N/A
F2125	Cash Register, With Locking Drawer	1	VV	Electronic cash register system. This unit includes multiple menu capabilities. Equipped with removable cash drawer for complete security. Calculator function and tax table. Convenience outlet required at point of use.	N/A
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	2	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.	N/A
K4660	Oven, Microwave, Heavy Duty, 1000 Watts	1	CC	Heavy duty, counter mounted, microwave oven which delivers 1000 watts of microwave energy for rapid reheating, defrosting or cooking. The unit's cabinet is made from stainless steel or other rugged material. The touchpad has programmable keys for timing the cooking of specific items and a multiple portion cooking time adjustment key. The unit features an electronic timer with a digital readout. Some models have an additional manual dial timer. The unit can be mounted in a cabinet recess or on a shelf.	N/A
K7250	Table, Food Preparation, CRS, Mobile	1	CC	Food preparation table approximately 36"H x 72"W x 36"D with a 5-6" stainless steel backsplash. This unit has options for heavy-duty casters with 5" hard rubber lockable wheels, under-shelves, stationary legs and storage drawers. Some models feature a removable backsplash, full or partial table replaceable plastic cutting boards, a decking section along the backsplash and tapered deck ends.	N/A

K8250	Toaster, Pop-Up, 4 Slice, Electric	1	VV	Four (4) slice, electric pop-up toaster. The toaster casing is made from stainless steel and can produce up to 290 slices/hr. This is used to toast sliced bread in food service kitchens and hospital cafeteria operations. Several electrical power configurations are available; some may require special wall receptacles. Refer to manufacturers' specifications.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
R7200	Refrigerator, 20 Cubic Feet	1	VV	Commercial refrigerator, 20 cubic feet approximately 80" H x 32" D x 27" W. This unit is generally used to store perishable goods for safekeeping in commercial kitchens, hospitals and schools.	N/A

**3. Canteen, PACT 3 (FSCD5)**

_0068	Credit Card Scanner	2	VV	Magnetic Card Reader used to scan credit and debit cards. Approximately 1.34"W x 3.54"D x 1.10"H.	N/A
_0069	Food Case, Grab and Go	2	VV	36-Inch Wide Horizontal Air Curtain Refrigerated Merchandiser, easy customer access to pre-stocked food items and cold beverages.	N/A
_0070	Trash / Recycling Center	2	VV	3- 40 Gallon each, approximately 33-3/4" x 18" x 18" with tops to sort waste, paper, cans and bottles. These units are used to sort trash and items for recycling.	N/A
_0071	Condiments Counter	2	VV	Custom designed unit, provides Canteen customers access to coffee condiments such as sugar, coffee stirrers, napkins, and other items. Custom built with dimensions based on the configuration of the space.	N/A
_0072	Stools, Counter	6	VV	Approximately 41" H x 17" L x 17" W. For use at custom dining counter.	N/A
_0073	Dining Counter (custom)	2	CC	Custom dining counter, approximately 18" D and 42" high. For use by Canteen Customers.	N/A
_0074	48" Diameter Table	3	VV	Dining Table 30" H with 48" diameter top. For use with dining chairs.	N/A
_0075	Display Casework (custom)	1	CC	Custom wall casework to display items sold in the Canteen Retail Area. Dimensions based on configuration of the space.	N/A
_0076	Display Case (custom)	1	VV	Custom display casework for items sold in the Canteen Retail Area. Dimensions based on configuration of the space.	N/A
A1010	Telecommunication Outlet	4	CC	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	2	CC	Telephone, desk, multiple line.	27 31 00
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	10 28 00

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels	N/A
F0205	Chair, Side With Arms	1	VV	Leather, woven fabric or vinyl upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17".	N/A
F0225	Chair, Dining Room	12	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.	N/A
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.	N/A
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.	N/A
F2125	Cash Register, With Locking Drawer	1	VV	Electronic cash register system. This unit includes multiple menu capabilities. Equipped with removable cash drawer for complete security. Calculator function and tax table. Convenience outlet required at point of use.	N/A
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	2	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.	N/A
K4660	Oven, Microwave, Heavy Duty, 1000 Watts	1	CC	Heavy duty, counter mounted, microwave oven which delivers 1000 watts of microwave energy for rapid reheating, defrosting or cooking. The unit's cabinet is made from stainless steel or other rugged material. The touchpad has programmable keys for timing the cooking of specific items and a multiple portion cooking time adjustment key. The unit features an electronic timer with a digital readout. Some models have an additional manual dial timer. The unit can be mounted in a cabinet recess or on a shelf.	N/A
K7250	Table, Food Preparation, CRS, Mobile	1	CC	Food preparation table approximately 36"H x 72"W x 36"D with a 5-6" stainless steel backsplash. This unit has options for heavy-duty casters with 5" hard rubber lockable wheels, under-shelves, stationary legs and storage drawers. Some models feature a removable backsplash, full or partial table replaceable plastic cutting boards, a decking section along the backsplash and tapered deck ends.	N/A
K8250	Toaster, Pop-Up, 4 Slice, Electric	1	VV	Four (4) slice, electric pop-up toaster. The toaster casing is made from stainless steel and can produce up to 290 slices/hr. This is used to toast sliced bread in food service kitchens and hospital cafeteria operations. Several electrical power configurations are available; some may require special wall receptacles. Refer to manufacturers' specifications.	N/A

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: 3.1 GHz 1 x Pentium processor; 4 GB RAM; 500GB hard drive; CD-ROM/DVD combo; HD Graphics; a 15 inch flat panel color monitor. The computer is used throughout the facility to input, edit and retrieve information.	N/A
R7200	Refrigerator, 20 Cubic Feet	1	VV	Commercial refrigerator, 20 cubic feet approximately 80" H x 32" D x 27" W. This unit is generally used to store perishable goods for safekeeping in commercial kitchens, hospitals and schools.	N/A

## V. FA22: Staff Support Area

### 1. Tele-Health Room (WRTM2)

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 10. Tele-Health Room (WRTM2)

### 2. Alcove, Medication (RCA06)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 14. Alcove, Medication (RCA06)

### 3. Storage, Equipment (SRE01)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 13. Storage, Shared Medical Appointments (SRE01)

### 4. Team Work Area, Clinical Support (WRTM1)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 16. Team Work Area (WRTM1)

### 5. Consult Room, Clinical Support (OFDC2)

See Above: B. PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1, 3. Consult Room, Patient Aligned Care Team (PACT) (OFDC2)

### 6. Conference Room (CRA01)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 21. Conference Room (CRA01)

### 7. Classroom (WKTM1)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 19. Classroom (WKTM1)

### 8. Lactation Room (LAC01)

A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A4995	Table, Diaper Changing, Wall Mounted	1	CC	Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15" high, 32" wide and 19" deep.	10 28 00
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A

A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	N/A
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
C0035	Rail, Apron, 4x24x1	2	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.	N/A
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.	N/A
CS040	Sink, SS, Single Compartment, 7.5x14x14 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	N/A
CT020	Countertop, Solid Surface	6	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 32 00
F0255	Chair, Easy	1	VV	Easy chair approximately 35" high X 28" wide X 32" deep with arms and floor glides. Arms, back and seat are foam padded and upholstered in woven textile fabric or vinyl.	N/A
F0740	Table, Occasional, Lamp	1	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).	N/A
F2010	Basket, Wastepaper, Step-On	1	VV	Step-on wastepaper basket with inner liner and foot pedal activated flip top.	N/A
M2605	Pump, Breast	1	VV	Electrically powered breast pump. The pump provides automatic or semi-automatic control of the pumping cycle and has a pressure limiting valve to prevent damage to breast tissues. Unit includes collection and overflow bottles as well as bacteria filters for the suction line between the pump and the overflow bottle. Options may include a trolley, carrying case and several sizes of collection bottles.	N/A
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.	N/A

**9. Lounge, Staff (SL001)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 24. Lounge, Staff (SL001)

**10. Locker, Staff Personal Property (LR004)**

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 25. Locker, Staff Personal Property (LR004)

**11. Toilet, Staff (TLTU1)**

See Above: A. LOBBY/RECEPTION AREA, 12. Toilet, Public (TLTU1)

**W. FA23: Support Area****1. Communications Room (COMC1)**

A0900	Relay Rack, Aluminum	3	CC	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7" height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).	N/A
A0901	Cable Management, Horizontal Base Unit	26	CC	Horizontal cable management unit for a 19" rack with a channel approximately 2"x2". Provides for professional finish to hide cables in a switch rack. Various models are quoted with fingered type exits or brackets and/or rear access holes.	N/A
A0902	Rear Wire Frame	13	CC	For use with horizontal base unit for double sided management. This item is intended to be used with JSNs A0901 and/or A0903 model HC219 series from Hubbell only.	N/A
A0903	Rear Hinged Cover, for LAN Rack	13	CC	This item is intended to be used with JSNs A0901 and/or A0902 model HC219 series from Hubbell only.	N/A
A0904	Fiber Optic Cabinet, 36 Port, Rack Mounted	1	CC	This cabinet is designed to accommodate up to 6 six-packs of adapters or blank panels. This cabinet is specifically designed to accommodate Hubbell adapter panels as reflected in JSNs A0905 and A0906.	N/A
A0908	Patch Panel, 110 Block/RJ-45, Cat 5E, 48 Port,568A	13	CC	This 48 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI).	N/A
A0911	Power Supply, Uninterruptable, Rack Mounted	1	CC	Uninterruptable Power Supply, Approximately 2200VA/1600W, Rack Mount with extendable Run Time. Unit must incorporate hot user swappable batteries and must have an overload indicator, replace battery indicator, audible alarm, automatic voltage regulation and include Smart Slot card and software. It must use RS232 DB-9 interface for communication. NEMA L5-30P power connector, and (8) NEMA 5-15R outlets.	N/A
A0912	Battery Pack, Extended for use with UPS (A0911)	1	CC	Battery Pack for use with JSN A0911 to extend backup power availability. Battery rated at approximately 1600 VA.	N/A
A0913	Switch, Local Area Network (LAN)	1	VV	Omni switch router, 9 slot chassis, 725W AC power supply and rack mount brackets. Supports high speed frame switching fabric. Software and Manual included. Requires management module JSN A0914 and works with Power Supply A0915.	N/A
A0914	Management Processor Module for LAN Switch	1	VV	Management processor module with 10BaseT with layer-3 switching (HRE-X); 32 MB DRAM & 8 MB flash memory. Operates over the 22G distributed switching fabric. Works with Switch LAN JSN A0913 and Power Supply A0915.	N/A
A0915	Power Supply, 725 W, for LAN Switch	1	VV	725 Watt powersupply. Redundant or spare power supply for the 9 slot Omni Switch Router. Works with Switch LAN JSN A0913 and Management Processor JSN A0914.	N/A

**2. Housekeeping Aides Closet - HAC (JANC1)**

A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A

A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.	N/A
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).	N/A
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 40 00
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	N/A
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.	N/A

### 3. Utility Room, Clean (UCCL1)

See Above: B.PATIENT ALIGNED CARE TEAM (PACT) CLINIC 1 AREA, 22. Utility Room, Clean (UCCL1)

### 4. Utility Room, Soiled (USCL1)

A1010	Telecommunication Outlet	1	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	N/A
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	12 32 00

CS200	Sink, SS, Single Compartment, 12x28x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	12 32 00
CT050	Countertop, Stainless Steel	7	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 32 00
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).	N/A
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 40 00
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	22 40 00
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

**5. Utility Room, Recycled Material (UTC01)**

A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A
F0530	Cart, Trash	1	VV	Heavy duty trash cart, approximately 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, one (1) or two (2) swivel casters, 2000 pound capacity and tilt mechanism.	N/A
F2026	Container, Recycling, Large	1	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.	N/A

**6. Pneumatic Tube Station (NT001)**

A1010	Telecommunication Outlet	2	CC	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	CC	Telephone, wall mounted, 1 line.	27 31 00



A6165	Station, Pneumatic Tube System	1	CC	The basic pneumatic tube system consists of a tube linking two or more different locations, a carrier to carry the payload and a power source to move the carrier from one location to another. The systems becomes more complex when the system is expanded to a network containing hundreds of locations and dozens of zones that need to transport the payload simultaneously.	N/A
-------	--------------------------------	---	----	---	-----

