

**VETERANS CANTEEN SERVICE (206)**

**1 - STAFF AND ADMINISTRATIVE AREA**

**1 - OFA09 - Office, Veterans Canteen Service Chief**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
<b>2 - OFA09 - Office, Food Section Assistant Chief</b>				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> <li>4 Standard Solid Panels</li> <li>2 Panel-to-Panel Connectors</li> <li>1 Panel Connector, 2-Way Corner</li> <li>2 Finished End Hardware</li> <li>2 Lockable Flipper Units</li> <li>2 Shelves, Storage/Display</li> <li>3 Lights</li> <li>3 Tackboards</li> <li>2 Cantilevered Work Surfaces</li> <li>1 Adjustable Keyboard Tray</li> <li>1 Mobile Pedestal, Box/File</li> <li>1 Pencil Drawer</li> <li>2 Support Panels</li> </ul>
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
<b>3 - OFA09 - Office, VCS Retail Assistant Chief</b>				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> <li>4 Standard Solid Panels</li> <li>2 Panel-to-Panel Connectors</li> <li>1 Panel Connector, 2-Way Corner</li> <li>2 Finished End Hardware</li> <li>2 Lockable Flipper Units</li> <li>2 Shelves, Storage/Display</li> <li>3 Lights</li> <li>3 Tackboards</li> <li>2 Cantilevered Work Surfaces</li> <li>1 Adjustable Keyboard Tray</li> <li>1 Mobile Pedestal, Box/File</li> <li>1 Pencil Drawer</li> <li>2 Support Panels</li> </ul>
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
<b>4 - CASH 1 - Secure Money Handling Room</b>				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A6035	Repository, Night, With Safe	1	CC	Constructed of high tensile steel body and jam designed to maximize protection against pry attack. Top or front load depository features a large hopper made of formed heavy duty steel, handle activated and designed for smooth money drop operation and large package capacity. Deposit drawer features a large "fish" resistant pull out drawer depositing directly into standard interior locker.
A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0425	Cabinet, Filing, Security, Full Height	1	VV	Class 6 full height security filing cabinet, 58" high x 21" wide x 28" deep with five (5) drawers. Used for storage of classified or controlled materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3100	Safe, Collection Agent	1	VV	Collection agent safe. Unit consists of thick door equipped with combination lock. All steel welded construction. For special document and record storage.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1805	Copier, Desk Top	1	VV	Desk top copier. Copier consists of two tray paper supply with clip tray, sort indicator, two page copy indicator, automatic paper selection and frame eraser with zoom capabilities. For use where low volume reproduction is required.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
<b>5 - OFA07 - Workstation, Clerk</b>				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

6 - SL001 - Lounge, Staff				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.
M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.

**7 - LR001 - Locker Room, Staff**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	4	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.



<b>8 - TLTU1 - Toilet, Staff</b>				
<b>JSN</b>	<b>NAME</b>	<b>QTY</b>	<b>ACQ/INS</b>	<b>DESCRIPTION</b>
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.



**2 - RETAIL STORE AREA**

**1 - SRE01 - Storage, Retail**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

**2 - MMRP1 - Receiving Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

F0775	Table, Work, 2 Drawer	1	VV	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers/ labels. Convenience outlet required at point of use.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
M2125	Stacker, Straddle, 127" Lift, 2000 lb Capacity	1	VV	Straddle stacker. Battery powered with 2000 pound lifting capacity. Unit lifts to heights up to 127". Equipped with a extra heavy duty hydraulic system. Unit has a built-in automatic battery charger. Electrical requirements are for the charger. Designed for pallet lifting.
M2130	Truck, Hydraulic Lift, Electric	1	VV	Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.

M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.
-------	-------------------	---	----	---

**3 - SR S01 - Storage, Remote Receiving Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

**4 - BX000 - Retail Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.

**5 - BX001 - Retail Area, Adapted for Spinal Cord Injury Patients**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A6030	Machine, Vending	2	L_RE	This JSN is to be used for determining and defining the requirement for vending machines. Item is normally leased or supplied by Army & Air Force Exchange Service, (AAFES).
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.

**6 - JANC1 - Housekeeping Aides Closet (HAC)**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

**3 - RETAIL CONCESSION AREA**

**1 - BX001 - Retail Display and Storage**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A6030	Machine, Vending	2	L_RE	This JSN is to be used for determining and defining the requirement for vending machines. Item is normally leased or supplied by Army & Air Force Exchange Service, (AAFES).
F2015	Basket, Wastepaper, Metal/Plastic,2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.

**4 - COFFEE SHOP AREA**

**1 - BX000 - Retail Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
-------	--------------------------	---	----	------------------------------------

**2 - SRE01 - Storage Room**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

**3 - FSCD1 - Seating Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F0210	Chair, Side, Without Arms	16	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0795	Table, Dining	4	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

**5 - OPTICAL SHOP AREA**

**1 - EYFD1 - Eyeglass Fitting, Display and Dispensing Room**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.
E1500	Rail, MOD, W/MNTD, HX144XD	2	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5520	Lensometer	1	VV	Lensometer. Unit includes lamps, prism measuring lens marking device, cylinder axis wheel calibrated in two 180 degree segments and a green filter for tinted glass. The instrument may be inclined between 25 to 90 degrees. Used for measuring lens.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M5735	Warmer, Spectacle, Plastic	1	VV	Plastic spectacle warmer. Bath type. Thermostatically controlled. For use with glass beads or salt.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

**2 - EYOT2 - Office, Optician / Technician**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.



VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M5016	Desk, Refraction w/console, w/o Sink	1	VC	The ophthalmic refraction desk shall be specifically designed to conduct eye examinations in ophthalmic clinics and hospital. It shall have a control console consisting of three rechargeable instrument wells, two 110v auxiliary switches to control accessories, two low voltage switches to control fixation lights, a separate on/off dimmer control for room lights and an indirect ophthalmoscope control with hanger that provides power to the instrument when lifted. This item may include an optional equipment stand/pole with one to three arms and the ability to accept a phoropter arm. There shall be a swivel Lamp and a trial lens drawer.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M5025	Table, Instrument, Ophthalmic, Adjustable	1	VV	Ophthalmic adjustable instrument table. Four toed pedestal type base with foot pedal brake or hand operated clamp for securing table adjustment. Designed for use with slit lamp, ophthalmometer, perimeter and screening instruments.
M5530	Lamp, Slit, w/Applanation Tonometer	1	VV	Slit lamp with applanation tonometer. Unit consists of a base mounted ophthalmological slit lamp with head and chin rest and manual height and focusing adjustments. The instrument features a microscope head with parallel optics that will accept an applanation tonometer. Designed for use in ophthalmology during diagnostic examinations.
M5535	Ophthalmoscope, Binocular, Indirect	1	VV	Binocular indirect ophthalmoscope. Unit consists of headband and crown, halogen quartz lamp, multi-coated aspherical lenses, scleral depressor and mirror. It also includes a control switch that regulates the illumination from 2 to 6 volts. Used to examine presence of blood vessels in patient's pupils.
M5536	Ophthalmoscope, Direct	1	VV	The Direct Ophthalmoscope shall be an instrument for examining the back portion of the interior of the eyeball and produces an un-reversed image. The unit shall consist of a head, a rechargeable handle, 3.5 v long-life battery and a case.
M5545	Ophthalmometer/Keratometer	1	VV	Keratometer/ophthalmometer. Unit features a focusing system, engraved focusing scale, positive fixation for rapid measurements, center and peripheral corneal measurements scale with a range from 30D to 60D. Unit is used for measuring corneal astigmatism.
M5562	Tester, Visual Acuity, Video/Microprocessor Based	1	VV	Visual acuity tester using video (television monitor) and microprocessor technology. This equipment replaces the projector chart and projector in an eye examination lane. Wall bracing is required for mounting the unit directly to the wall without support from below. An optional floor stand can also be used. The unit requires an electrical outlet on the far end wall of the examination lane. This differs from standard eye examination room configurations which normally do not have electrical outlets in that wall. Other options include binocular vision and contrast sensitivity testing.
M5575	Tonometer, Noncontact	1	VV	Non-contact tonometer. Unit includes a built-in RX selector with four diopter corrections, air pulse button, head rest, and a digital display. Used for patient's eye observation, glaucoma screening, and other routine screening through a puff of air.
M5600	Unit, Exam, Eye, w/Motor Chair, Phoropter	1	VV	Eye exam phoropter unit with motor operated chair. Unit consists of an adjustable chair, and phoropter unit for eye examination, mounted on a stand. Stand includes an additive tray with keratometer arm and tray and a integral instrument tray. Unit is designed for use during ophthalmic examinations.
M5705	Gauge, Distance, Pupillary	1	VV	Pupillary distance gauge. Unit is electronic and features corneal reflection, LCD display, 0.5mm measurement increments, and measure fixation PD distance to 30 cm from infinity. Unit runs on battery power and is designed to measure the distance between pupils as well as corneal and pupil diameter.
M6040	Pachymeter, Ultrasound, Corneal	1	VV	Ultrasonic Pachymeter for measuring corneal thickness.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

**7 - FOOD COURT SUPPORT AREA**

<b>1 - MMRP1 - Receiving, Food Court</b>				
<b>JSN</b>	<b>NAME</b>	<b>QTY</b>	<b>ACQ/INS</b>	<b>DESCRIPTION</b>
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
				This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F0775	Table, Work, 2 Drawer	1	VV	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers/ labels. Convenience outlet required at point of use.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
M2125	Stacker, Straddle, 127" Lift, 2000 lb Capacity	1	VV	Straddle stacker. Battery powered with 2000 pound lifting capacity. Unit lifts to heights up to 127". Equipped with a extra heavy duty hydraulic system. Unit has a built-in automatic battery charger. Electrical requirements are for the charger. Designed for pallet lifting.
M2130	Truck, Hydraulic Lift, Electric	1	VV	Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.
M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.

**2 - SRS01 - Storage, Non-Food**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
-------	--	---	----	---

**3 - SRS01 - Storage, Dry-Food**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

**4 - RER01 - Storage, Refrigerated and Frozen Food**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1000	Extinguisher, Fire	1	VV	10 pound dry chemical fire extinguisher with charging gauge. Other types and sizes are available.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
M2070	Shelving, Storage, 77hx36wx18d	1	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

**5 - FSTD1 - Food Preparation and Production**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1000	Cabinet, Pastry, Mobile, Medium	1	VV	Mobile pastry cabinet. The cabinet is made from aluminum or stainless steel, is mounted on four swivel casters and holds thirty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). Smaller capacity units are available. For larger capacity units see JSN K1010. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.
K1010	Cabinet, Pastry, Mobile, Large	1	VV	Mobile pastry cabinet. This is a heavy duty, aluminum or stainless steel unit on four swivel casters which holds approximately forty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). See JSN K1000 for smaller capacity units. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K1020	Cabinet, Heated, Food, Mobile, Large	1	VV	Insulated food warming cabinet. The cabinet is made of aluminum or stainless steel and is mounted on four heavy duty casters. The interior of the cabinet has slide ledges on both sides spaced at 1-1/2 inch intervals. The unit holds thirty or more 18 inch by 26 inch full size pans or trays. Double door and non-insulated cabinets are available, the second door reduces the tray capacity by one. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). The cabinet is used in commercial and hospital kitchens for food storage prior to serving.
K1030	Cabinet, Hot/Cold, Food, Mobile, Counter Height	1	VV	Half-height food holding cabinet (adjunct to cafeteria counter) which can heat stored food or keep it cold. The cabinet is made of corrosion resistant steel or a composite material and is fully insulated. It has a full length hinged door with lock, four lifting handles and channel type interior slides to hold seven or eight 12 inch wide, 20 inch long and 2-1/2 inch deep pans. The cabinet will also hold 4 inch and 6 inch deep pans. The cabinet has a heating unit, a cold holding plate or cooling unit and four 4 inch casters. For dual compartment cabinets, see JSN K6250. This unit is used to hold hot and cold food in commercial kitchens and hospitals.
K6250	Cabinet, Food, Heated, Mbl, 2 Compartment, Counter Ht	1	VV	Mobile electric hot food warmer and server with dual side by side compartments, temperature and moisture controls, full insulation and casters. The unit holds sixteen 2-1/2" x 12" x 20" pans. Models are also available with heating wells on the top of the cabinet. The unit is used in food service operations for keeping hot food warm in the kitchen prior to serving.

**6 - FSDW1 - Dish Washing**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1695	Conveyor, Meal Tray Return	1	CC	Fixed conveyor for returning soiled meal trays from the main dining room to the tray processing area for cleaning. The database pricing is based on 24 feet of straight conveyor and 4 corner sections. This conveyor could lead to a second conveyor for tray processing or directly to a dishwasher with tray processing en route. Multiple power outlets will be required depending on the conveyors length.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K1800	Sink/Drainboard, Dishwashing, Triple Bowl	1	CC	Triple bowl dishwashing sink with two drainboard counters. The sink is made of 16 gauge stainless steel, has three 20" x 20" sink bowls, has supporting legs and/or wall attachment points and is pre-drilled for faucet and drain connections. Custom sized units are available. The database price includes the cost of welding the disposal cone to the bottom of one sink. See JSN K2620 for disposal units and JSN K9320 for accessory spray arms. The database height dimension is to the top of the backsplash; see the specification sheets for the sink rim height. Larger and smaller units are available as well as units with fewer sink bowls. This unit is used to wash dishes in institutions and commercial kitchens.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K2290	Dishwasher, Conveyor, Steam, 2 Tank	1	CC	Automatic dishwasher which uses steam to heat the water in its two tanks. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Three 1 HP or larger motors power the pre-wash, wash and rinse water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwasher's controls are mounted for ease of operator use. Optional blower/dryer units remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. Because they vary widely from model to model, the dishwasher's final physical and utility configurations should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturer's top line unit for the specified number of tanks.
K2490	Dishwasher, Conveyor, Steam, 1 Tank	1	CC	Automatic dishwasher which uses steam to heat the water in the single tank. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Two 1/2 HP or larger motors power the pre-wash and wash water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwasher's controls are mounted for ease of operator use. Optional blower/dryers remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. Because they can vary widely from model to model, the dishwasher's final physical and utility configurations should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturers top line unit for the specified number of tanks.



VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K2500	Dishwasher, Conveyor, Steam, 3 Tank	1	CC	Automatic dishwasher which uses steam to heat the water in its 3 tanks. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Three 1 HP or larger motors power the pre-wash, wash and rinse water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwashers controls are mounted for ease of operator use. Optional blower/dryer units remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. The dishwasher's final physical and utility configuration should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturer's top line unit for the specified number of tanks.
K2620	Disposal, Waste, Heavy Duty	1	CC	Food waste disposal. The unit has a 10 HP heavy duty motor, a heavy cast alloy body, a 3 inch outlet and a cast-in deflector in upper chamber that force feeds waste down onto a 15" rotor. This unit is used for disposing large quantities of the heavy waste material generated in the central areas of commercial and institutional food service operations.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.
K6670	Sink, Soak, Mobile, 1 Compartment	1	VV	Mobile soak sink. This is a single compartment stainless steel unit. The sink legs are fitted with 4 or 5 inch swivel casters. Two casters have foot locking brakes. The unit is used in kitchens for soaking flatware and other kitchen items.
K8200	Rack, Wash, Pan/Utensil	1	VV	Pan and utensil wash rack. This unit can be a set of racks to accommodate a specific dishwashing unit. The racks are all stainless steel and can be used in large food service operations for cleaning pots and pans.
K9300	Washer, Pressure w/Sanitizer	1	VC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K9320	Hose, Spray, Pre-Rinse	1	CC	Pre-rinse spray hose. The unit is a chrome plated wall or back deck mount design used to rinse dishes before racking in the dishwasher. It has a dual lever control which permits quick water temperature selection, large non-slip grip spray valve and spring loaded goose neck with storage hook.

K9450	Washer, Tray, Automatic Stacking, Electric	1	CC	Tray washer. This unit has eye thermometers, vacuum breaker, motor starter and standard overload protection mounted in a stainless steel enclosure. The unit features a remote stop button on the unloading side of the unit. The continuously moving belt has fingers or racks for easily mounting trays for cleaning. The database height dimension includes the clearance to open and remove a door panel. These washers vary widely in length and capacity; consult the manufacturer's specifications for the specific model. This washer can be found in food service operations of hotels, restaurants and hospitals.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

**7 - FSPW1 - Pot Washing Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1800	Sink/Drainboard, Dishwashing, Triple Bowl	1	CC	Triple bowl dishwashing sink with two drainboard counters. The sink is made of 16 gauge stainless steel, has three 20" x 20" sink bowls, has supporting legs and/or wall attachment points and is pre-drilled for faucet and drain connections. Custom sized units are available. The database price includes the cost of welding the disposal cone to the bottom of one sink. See JSN K2620 for disposal units and JSN K9320 for accessory spray arms. The database height dimension is to the top of the backsplash; see the specification sheets for the sink rim height. Larger and smaller units are available as well as units with fewer sink bowls. This unit is used to wash dishes in institutions and commercial kitchens.
K1860	Sink, Pot, Triple Compartment, w/Drainboards	1	CC	Pot washing and scraping counter. This unit has three sink compartments and is constructed of stainless steel. The dimensions should be specified as required. See JSN K2620 for disposers and K9320 for pre-rinse hoses. Some models are built to accommodate two faucets. See related dishwashing and scullery triple compartment sinks at JSNs K1800 and K6660. This unit is used to wash pots in food service operations of hospitals, hotels and restaurants.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K2620	Disposal, Waste, Heavy Duty	1	CC	Food waste disposal. The unit has a 10 HP heavy duty motor, a heavy cast alloy body, a 3 inch outlet and a cast-in deflector in upper chamber that force feeds waste down onto a 15" rotor. This unit is used for disposing large quantities of the heavy waste material generated in the central areas of commercial and institutional food service operations.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K9300	Washer, Pressure w/Sanitizer	1	VC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K9320	Hose, Spray, Pre-Rinse	1	CC	Pre-rinse spray hose. The unit is a chrome plated wall or back deck mount design used to rinse dishes before racking in the dishwasher. It has a dual lever control which permits quick water temperature selection, large non-slip grip spray valve and spring loaded goose neck with storage hook.
K9760	Washer, Pot/Pan, Electric	1	CC	Pot and pan washer. This unit's wash and rinse cycles pump water and cleaning solution under pressure through its upper and lower spray arms. The washer cleans pots, large preparation bowls and kitchen appliance parts. The unit drains after each cycle. The database information is for a straight pass through unit with an electric tank heater. Corner units and units with chemical or low temperature sterilization are available. The database physical specifications include the clearance needed to remove the unit's vertical doors and the extra footprint of exterior mounted control boxes and pipe connections. This unit is used in hospitals and large food service areas.
K9770	Washer, Pot/Pan, Steam And Electric	1	CC	Pot and pan washer with a steam heated tank. The washer is made of stainless steel and has a 5 HP wash pump motor, hot water spray rinse, sanitizing hot fresh water rinse, steam or electric water temperature booster, exhaust fan and basket screens. See K8200 for the washing racks for this machine.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
P2100	Disposal, Garbage, 2 HP Motor	1	CC	Garbage disposal. A two (2) horsepower versatile waste disposal unit suitable for facilities where 500 to 1000 meals are prepared and served daily. Requires eight (8) gallons per minute water flow rate, and outlet flange tapped for a two (2) inch pipe. Unit will have a manual reversing switch and shall comply with MIL SPEC No. MIL-G-15840. Multiple electrical configurations are available.

**8 - SRHM 1 - Sanitation and Recycling Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.
M2015	Cabinet, Storage, Flammable, Freestanding	1	VV	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

M2070	Shelving, Storage, 77hx36wx18d	1	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.

**9 - UTC01 - Trash Holding Refrigerated Room**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
F0530	Cart, Trash	1	VV	Heavy duty trash cart, approximately 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, one (1) or two (2) swivel casters, 2000 pound capacity and tilt mechanism.
F2026	Container, Recycling, Large	1	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.

**11 - JANC1 - Housekeeping Aides Closet (HAC)**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.

P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

**8 - CAFETERIA SERVING AREA**

**1 - FSSL1 - Serving Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
K0500	Baker, Waffle, Dual Plate	1	VV	Waffle baker. The baker has two 7 inch diameter pans, side by side in a single machine or is two single pan units side by side. The grids are removable for cleaning and the cabinet is constructed of stainless steel. The database height dimensions are for an open pan. Two separate electrical outlets may be needed for two single units operating side by side. It is used in large restaurants and food service operations for hot waffles.
K1000	Cabinet, Pastry, Mobile, Medium	1	VV	Mobile pastry cabinet. The cabinet is made from aluminum or stainless steel, is mounted on four swivel casters and holds thirty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). Smaller capacity units are available. For larger capacity units see JSN K1010. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K1160	Cabinet, Warming, Pass-Thru, CRS	1	VC	Mobile or stationary warming cabinet. This is a pass-through model with doors that can be opened from either side for easy use. The cabinet can have single or double Dutch doors on either or both sides. The unit has an exterior temperature gauge for easy monitoring. The cabinet has a slide in humidity pan or controlled humidity vents in the top of the cabinet. Some models run on 120V power, others on 208V. Refer to the manufacturers specification sheets. The database electrical specifications cover both possibilities. The unit is used in commercial and hospital kitchens for warming prepared food items.
K1600	Counter, Cafeteria, Cold Food, Mobile, 5-Pan	1	VV	Mobile cold food cafeteria counter. The counter features a refrigeration unit with coils around the counter compartment, an open compartment top which can hold five 12" x 20" pans, a double display shelf above the counter unit, sneeze guards, a drop-type solid or three rail tray slide, a server's workshelf, open shelving on the server's side and four 5" swivel casters. Some manufacturers offer a second refrigerated section below the cold pan. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. The unit is used for self-service of cold food in cafeterias and commercial food service areas.
K1650	Counter, Cafeteria, Hot Food, Mobile, 5-Pan	1	VC	Mobile, hot food cafeteria counter. This unit has a top compartment capable of holding five (5) 12" by 20" pans, a full length food display shelf with sneeze guard, a drop-type solid or three rail tray slide, four (4) 5 inch swivel casters, shelving underneath the warming wells and a work shelf on the server's side. The complete unit is insulated as is each well. Each well is also individually thermostatically controlled with an individual heating element. The exact unit dimensions depend on the specific manufacturer; refer to the technical data sheets. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. The unit is used in hospitals, schools and commercial food service establishments.
K1710	Counter, Cafeteria, Utility, W/Power 61x80x42	2	VC	Mobile cafeteria counter. The counter can serve as a mobile utility table and has a double-shelf food display case with sneeze guard, a drop-type solid or three rail tray slide, 120V AC outlets, a work shelf, below the counter shelves and four 5-inch swivel casters. The end user must specify the outlet requirements and configuration. Multiple facility-level outlets may be required depending on the number of convenience outlets the end user requires. The database depth dimension does not include the fold down tray rail but does include the 8-10" working shelf on the server's side. This unit is used in commercial and hospital service areas.
K1750	Counter, Cafeteria, Mobile, Utility	1	VV	Mobile cafeteria counter, approximately 36"H x 80"L x 32"D. The counter is made of stainless steel construction, has intermediate and bottom shelves on the working side, a drop-type solid or three rail tray slide and 5-inch swivel casters. The database depth does not include the depth of the tray slide. It is used for service of food items in hospitals and restaurants.
K2040	Dispenser, Iced Tea	1	VV	Instant tea beverage dispenser. The unit uses either liquid concentrate tea or a brewing system to provide consistent tea in a continuous flow dispensing system. The unit is used to dispense instant tea in hotels, restaurants, hospitals, clubs and other food service operations.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K2050	Dispenser, Bread, CRS, 2 Compartment	1	VV	Bread dispenser. This unit is either an in-counter two compartment system consisting of two sleeves and a facing plate or an above the counter unit holding two or three loaves. The in-counter units have self-leveling dispensers and covers. Either system will store two or three loaves. The unit is designed for use on work boards, sandwich counters, salad bars and other service points.
K2080	Dispenser, Milk, Mobile, Individual Container	1	VV	Milk dispenser cabinet. The cabinet is made of stainless steel which is welded, ground and polished to a uniform finish. The convenient reach-in cooler stores milk or beverages by case or individually stacked container. The dispenser can be used as an individual server or as part of a continuous serving line. The unit is used in food service areas for self-service issue of milk in schools, restaurants and hospitals.
K2085	Dispenser, Milk, Bulk, Double	1	VV	Milk dispenser cabinet. The stainless steel cabinet has two lift valves for dispensing milk, a capacity of twelve total gallons, magnetic door seals and a self-contained mechanical refrigeration system. This unit is used for self-service of milk in cafeteria of schools, hospitals and commercial restaurants.
K2100	Dispenser, Cream, Eutectic, 2 Quart	2	VV	Portable 2 quart cream dispenser. The unit uses a sealed re-freezable (eutectic) cooling element to keep cream cold for up to four hours. The unit features portion control, has stainless steel product contact areas, can be permanently mounted and is easily cleaned.
K2110	Dispenser, Drink, Non-Carbonated	1	VV	Non-carbonated drink dispenser. The unit has a 3-5 gallon capacity beverage bowl with a cover. This unit serves non-carbonated drinks to patients in hospitals.
K2111	Dispenser, Drink, Non-Carbonated w/Refrigeration	1	VV	Non-carbonated drink dispenser with a refrigeration unit. The unit cools or maintains the coldness of liquid or frozen drinks during serving.
K2115	Dispenser, Drink, Carbonated	1	L_RE	Carbonated drink dispenser. The unit dispenses eight carbonated beverages and ice from a self service counter machine. The ice hopper holds 100 lb. of ice and may be connected to a remote ice maker from which it automatically loads ice. If not connected to an ice maker, the unit's ice bin will require manual refilling. The unit does not include the syrup racks, mixing valves, carbon dioxide supply or the chilled water pump. This unit is used to dispense cold carbonated drinks in food service activities.
K2120	Dispenser, Cup/Saucer, Unheated, Mobile, 4 Stack	1	VV	Mobile, unheated cup and saucer dispenser. The cabinet is made of stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes four self-leveling dispensing stacks which are sized to match or are self-adjusting to match the size of the dishware being stored. Heated units, units which hold less than four self-leveling dispensers and units which store larger dishes are also available. The facility's selection of dishware ultimately determines which exact model will be required. The unit is used for self-service of tableware in food service operations.
K2130	Dispenser, Plate, Mobile, Unheated, 4 Stack	2	VV	Mobile, unheated dinner plate dispenser. The cabinet is made of stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes four self-leveling dispensing stacks which are sized to match the size of the plates being stored. See JSN K2140 for a heated 4 stack unit and JSN K2160 for a heated 2 stack unit. Other units are available. The database specifications refer to units which hold 10" plates. The facility's selection of dishware ultimately determines which exact model will be required. The unit is used to dispense dishes in food service facilities, restaurants and hospitals.



K2140	Dispenser, Plate, Mobile, Heated, 4 Stack	1	VV	Mobile, heated dinner plate dispenser. The cabinet is made of stainless steel, is mounted on four heavy duty casters and has a full perimeter strip bumper. The unit includes four self-leveling dispensing stacks which are sized to match the size of the plates being stored. See JSN K2130 for an unheated 4 stack unit and JSN K2160 for a heated 2 stack unit. Heated and unheated units with other capacities are available. The database specifications refer to units which hold 10" plates. The facility's selection of dishware ultimately determines which exact model will be required. The unit is used to dispense plates in food service facilities, restaurants and hospitals.
K2150	Dispenser, Drinking Glass, Mobile	2	VV	Mobile drinking glass dispenser. The unit is made of heavy gauge stainless steel, is enclosed on all four sides and mounted on four heavy duty casters. The unit stores racks filled with drinking glasses and holds the top rack at a constant dispensing height for customer convenience. Stationary units, units with open sides and cantilever style units are also available. This unit is used to dispense glasses in food service operations of hospitals and restaurants.
K2160	Dispenser, Plate, Mobile, Heated, 2 Stack	2	VV	Mobile, heated dinner plate dispenser. The dispenser is made of stainless steel, is mounted on four casters, has closed sides and has a full perimeter strip bumper. The unit includes two self-leveling dispensing stacks which are sized to match the size of the plates being stored. See JSN K2140 for a heated 4 stack unit and JSN K2130 for an unheated 4 stack unit. Other unit configurations are also available. The facility's selection of dishware ultimately determines which exact dispenser model will be required. The database specifications are for units holding 12" plates. The unit is used to dispense dishes in food service facilities, hospitals and restaurants.
K2180	Dispenser, Meal Tray, w/Flatware Cylinders	1	VV	Twin stack stainless steel meal tray dispenser with an eight to ten cylinder silverware dispenser above. The dispenser can be mobile or stationary. Self-leveling dispensers are available. Some models have decorative laminating over portions of the stainless steel.
K2200	Dispenser, Bowl/Plate, Mobile, Unheated, 4 Stack	1	VV	Mobile, unheated bowl and small plate dispenser. The unit is made from stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes four self-leveling, adjusting dispensing stacks which adjust to the size of the dishware being stored and keep the next available dish at a convenient height for removal. The unit is easily cleaned. Heated, non-self adjusting and units with less than four stacks are also available. See JSNs K2210 and K2220 for 2 stack heated and unheated models. The database specifications are for a unit holding bowls and plates between 4-1/4" and 7" in diameter. The facility's selection of dishware ultimately determines which exact model is required. The unit is used to dispense bowls and small plates in food service operations, hotels, restaurants and hospitals.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K2220	Dispenser, Bowl/Plate, Mobile, Unheated, 2 Stack	2	VV	Mobile, unheated bowl and small plate dispenser. The unit is made from stainless steel, is mounted on four casters and has a full perimeter strip bumper. The unit includes two self-leveling, adjusting dispensing stacks which adjust to the size of the dishware being stored and keep the next available dish at a convenient height for removal. The unit is easily cleaned. Units with non-self adjusting dispensers and units with more than two stacks are also available. See JSNs K2200 and K2210 for larger and 2 stack heated models. The database specifications are for a unit holding bowls and plates between 4-1/4" and 7" in diameter. The facility's selection of dishware ultimately determines which exact model is required. The unit is used to dispense bowls and small plates in food service operations, hotels, restaurants and hospitals.
K2230	Dispenser, Meal Tray, Mobile	1	VV	Meal tray dispenser. The dispenser is made of stainless steel, is mounted on heavy duty casters with brakes on at least two casters and has protective bumpers. Self-leveling springs keep trays at a convenient height for use. The dispenser can hold either 14" x 18" or 15" x 20" meal trays. Cantilever, fully enclosed and open side models are available. Many models offer cutlery/silverware dispensers as optional attachments. Tray dispensers are used in serving lines and tray makeup lines in food service operations in hotels, restaurants and hospitals.
K2240	Dispenser, Hot Chocolate, Counter Mounted	1	VV	Hot chocolate dispenser. This is an electric, counter mounted unit. The dispenser provides portion-controlled, single cup size servings in commercial and institutional food service operations.
K2270	Dispenser, Ice Cream, Soft, Freestanding	1	VV	Ice-cream dispenser. The dispenser is made of stainless steel and uses a gravity freezer. The unit can serve either of two flavors or a twist combination. Unit is used to serve frozen desserts in commercial and institutional food service operations.
K2800	Fryer, Electric, 30 Lb. Capacity, Free Standing	1	CC	Two basket electric deep fat fryer. The unit is freestanding, holds 30-35 lb. of hot oil, has leveling legs, swing up or removable corrosion resistant heating elements, solid state or programmable controls, self-diagnostics, a backsplash and an electronic or thermostatic over-temperature shutoff. The basic unit has painted sides, an aluminized back and a stainless steel front and top; a full stainless steel enclosure is optional. Some models have automatic basket lifts. The database height dimension refers to a unit with its coils lifted for cleaning.
K3100	Griddle, Electric, Counter Mounted, 36" Wide	1	CC	Electric griddle. The griddle has a 1/2 inch thick (or greater) steel heating surface, stands on legs on top of a counter, has a thermostat control for each linear foot of griddle and has a drippings channel which empties into a grease drawer for easy cleaning. The griddle has side and rear splash guards. Some manufacturers offer models of differing depths. The model chosen should match the supporting counter or table. The database specifications and pricing reflect a standard depth unit. The griddle is used for food preparation in commercial and institutional food service operations.

VETERANS CANTEEN SERVICE (206) - Contents - VA PG-18-5 (18 Jul 2016 05:03PM ET)

K3400	Hood, Exhaust, Kitchen	1	CC	Stainless steel kitchen exhaust hood. The unit has removable grease filters for use over any area, is fabricated to dimensions as required, provides for forced upward air flow through a hood and the grease filter and can pull the exhaust down through a vent and dissipate it below the kitchen to an outside area with complete automatic grease extraction. The database reflects the requirements for a 12 foot wide unit. The database price does not include the filter elements. The database electrical requirements are for any light fixture that is part of the hood. The fan that draws the air from this unit is not part of this unit. This hood facilitates exhaust dissipation in commercial and institutional food service operations.
K3560	Cabinet, Ice Cream, Mobile, Self-Service	1	VV	Ice cream cabinet for self-service. The cabinet has stainless steel/galvanized steel double walled sides with formed-in-place polyurethane insulation on all sides and the bottom, adjustable temperature control, removable cover, a drain from the inner compartment and externally mounted dial thermometer. The cabinet can be placed adjacent to a food service counter during service of meals.
K6245	Cabinet/Server, Heated, 2 Drawer/Compartment	1	VV	Two drawer hot food warmer and server with temperature control and full insulation. The unit may be mobile or counter mounted and requires a convenience outlet at point of use. It is used in hospital kitchens to keep hot foods warm prior to serving.
K7250	Table, Food Preparation, CRS, Mobile	1	VV	Food preparation table approximately 36"H x 72"W x 36"D with a 5-6" stainless steel backsplash. This unit has options for heavy-duty casters with 5" hard rubber lockable wheels, under-shelves, stationary legs and storage drawers. Some models feature a removable backsplash, full or partial table replaceable plastic cutting boards, a decking section along the backsplash and tapered deck ends.
K8400	Toaster, Conveyor, 600 Slices/Hr, Electric	1	VV	Conveyor toaster. This unit can toast up to 600 slices/hour. Some models use quartz heaters rather than resistive wire elements. The color of the toast is adjusted by varying the conveyor belt speed. This unit is used in large food service operations, for fresh toast or warm buns.
K8500	Rack, Tray/Pan, Mobile, CRS, Light/Medium Duty	1	VV	Mobile tray and pan rack. The rack is made of stainless steel or aluminum and has matched ledges for holding trays and pans. The rack is mounted on medium duty casters. Racks are available in various heights, with channel or angled ledges and in several ledge spacing intervals. The size of the facility's pans and trays will determine the exact model procured. The rack is used to bus dirty trays from the serving line for cleaning and washing.
K8920	Urn, Coffee, 2 Sections, 6 Gallons Each, Electric	1	VC	Electric twin coffee urn (without stand) with a total capacity of twelve (12) gallons, six (6) in each urn, adjustable by-pass and an automatic agitator. The unit is used in hospital food service operations for preparing large volumes of fresh coffee.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms, or patient care areas.
R4650	Ice Maker, Flaked, With Dispenser	1	CC	Ice maker dispenser approximately 71" H x 19" D x 24"W. This unit provides flaked ice and cooled water automatically. The unit has a daily capacity up to 650 pounds and a 100 pound capacity stainless steel storage compartment with water station. It is a freestanding, automatic load ice dispenser for food service and healthcare use. The unit is used in healthcare institutions and various commercial food service operations for dispensing ice.

**9 - CAFETERIA DINING AREA**

**1 - FSCD1 - Dining Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F0210	Chair, Side, Without Arms	16	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0795	Table, Dining	4	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

**10 - VENDING AREA**

**1 - BX001 - Vending Machine Area**

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A6030	Machine, Vending	2	L_RE	This JSN is to be used for determining and defining the requirement for vending machines. Item is normally leased or supplied by Army & Air Force Exchange Service, (AAFES).
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.