

CARDIOVASCULAR LABORATORY SERVICE (210)

1 - RECEPTION AREA

1 - WRC01 - Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.

2 - RECP1 - Reception

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	2	VV	Telephone, desk, multiple line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	2	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.

3 - RECP4 - Kiosk, Patient Check-In

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.
M1890	Kiosk, Educational, Stand-Up	2	VV	A free standing Kiosk providing educational information for patients. The kiosk will, as a minimum, include a computer, an LCD display of approximately 19" with a touch screen, keyboard with track ball, speakers, printer, card reader, bar code scanner and housed in a durable steel enclosure. The unit will contain all necessary software packages to satisfy a wide spectrum of information distribution. Final configuration of kiosk will be determined at time of purchase.

4 - CLSC1 - Workstation, Patient Education

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M1890	Kiosk, Educational, Stand-Up	1	VV	A free standing Kiosk providing educational information for patients. The kiosk will, as a minimum, include a computer, an LCD display of approximately 19" with a touch screen, keyboard with track ball, speakers, printer, card reader, bar code scanner and housed in a durable steel enclosure. The unit will contain all necessary software packages to satisfy a wide spectrum of information distribution. Final configuration of kiosk will be determined at time of purchase.

5 - TLTU1 - Toilet, General

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.

P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

2 - NON-INVASIVE CARDIOLOGY PATIENT AREA

1 - OPEC1 - EKG Testing Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0930	Locker, Supply, 6 Drawers, Mobile, 29"W x 20"D	1	VV	THIS TYPICAL INCLUDES: 1 Mobile Supply Locker 2 Tray/Shelf 4 Drawers, 3"H 2 Drawers, 6"H Drawer Organizer Bins
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2017	Waste Receptacle, 24 GAL	1	VV	Rectangular steel waste receptacle with step-on lid and 24 gallon capacity. The receptacle is used to collect and temporarily store small quantities of paper refuse. Can be used in restrooms, patient areas, laboratories, pharmacies, etc.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M4100	Sphygmomanometer, Aneroid, Wall Mounted	1	VV	Aneroid sphygmomanometer. Unit is wall mounted and has large graphic dial display for easy reading from all angles. It has a 90 degree (angle) swivel and 10 degree (angle) forward tilt to reduce glare. Unit accuracy is within 1% of reading. Sturdy impact-resistant construction.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M7710	Electrocardiograph, 12 Lead, Portable	1	VV	Used to detect the electrical signals associated with cardiac activity, diagnose cardiac abnormalities, determine a patients response to drug therapy and reveal trends or changes in heart function. Capable of recording two or more leads simultaneously, recording an entire 12 lead ECG in about 10 seconds. Includes of a 3.5 inch, high density, floppy disk drive for test storage. Portable.
M9025	Table, Examination/Treatment, With Cabinet	1	VV	Table, examination/treatment with cabinet. Cabinet type exam table with three section upholstered top adjustable to a full chair position. Concealed heel stirrups, dual outlets, drawers, and storage space with optional armboard. Unit is designed for general use in examination/treatment rooms.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7" x15" x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

4 - OPHM 1 - Holter Monitor Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0280	Chair, Swivel, Low Back	2	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M7770	Computer, Holter Monitor Analysis System	1	VV	Central processor for the analysis of Holter monitor recordings. System permits the high speed downloading of Holter recordings into a central database, automated recording analysis and storage, report generation, listing clinical findings and tracking final reports. System may include a monitor, keyboard, scanner, printer, input port and a disk drive storage device.

M9006	Table, Ultrasound, Mobile, Echocardiology	1	VV	Mobile exam table designed for ultrasound and echocardiology examinations. Table has an extra wide top with a 500 lb patient capacity, suitable for bariatric patients. Height range from 23" low to accommodate wheelchair transfers and those with ambulatory difficulties to a high of 39". Table includes motorized height adjustment, Fowler position, Trendelenburg and auto level adjustment.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

5 - OPPE1 - Echocardiograph Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismantling of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismantling equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0912	Locker, Supply, Med Surg, Wall Mtd	1	VV	<p>Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	<p>Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.</p>
F0210	Chair, Side, Without Arms	1	VV	<p>Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.</p>
F0280	Chair, Swivel, Low Back	1	VV	<p>Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.</p>
F0340	Stool, Self Adjusting	1	VV	<p>Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.</p>
F2000	Basket, Wastepaper, Round, Metal	2	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3200	Clock, Battery, 12" Diameter	1	VV	<p>Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).</p>
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	<p>Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.</p>
M0755	Flowmeter, Oxygen, Low Flow	1	VV	<p>Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.</p>

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1620	Holder, Chart, Patient, Wall or Door Mounted	1	VV	Wall or door mounted patient chart holder. Constructed of durable plastic or metal. Used for holding patient records. Size as required.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.
X2105	Scanner, Ultrasound, Cardiac (Echo)	1	VV	High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse, continuous wave imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.

6 - OPPE2 - Stress Echocardiograph Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	1	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
A6210	Uninterruptible Power Supply, Single Phase	1	VV	Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C03J0	Cabinet, U/C/B, 8 Half Drawers, 36x30x22	1	CC	Standing height under counter base cabinet with eight half width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CE030	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x30x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M8185	System, Stress Exercise, w/Treadmill	1	VV	Stress exercise system with treadmill and respiratory/metabolic assessment. The system includes an ECG amplifier, chart recorder, display, console, treadmill and modules for respiratory/metabolic assessment. Used to determine patient's functional capacity, predict and diagnose cardiopulmonary and vascular diseases and for rehabilitation of patients recovering from leg injuries or other type of illness. Some vendors require a NEMA 5-20R non-locking receptacle for their treadmills.
X9810	System, Camera, Gamma, Mobile	1	VC	Mobile gamma camera system. This unit is a compact scintillation camera system. The characteristics and components include a detector, electronics and a console mounted on a mobile base. The console contains all operating controls and the image display. This unit is used for bedside evaluation of critically ill patients.
X9830	Scanner, Nuclear, SPECT, Dual Head	1	VC	The system shall be a single plane or variable angle dual detector emission system, designed for fast data acquisition and high patient throughput for Single Photo Emission Computed Tomography (SPECT), whole body and general purpose nuclear medicine procedures. It shall be designed to image at any energy range for any procedure. The unit detects and counts photons emanating from radiopharmaceuticals. Collimators available to suit full range applications. The system shall be DICOM 3.0 or latest version, compatible, for easy linkage to filmless image management systems and review stations.

7 - OPTM 1 - Stress Testing Treadmill Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	8	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0765	Regulator, Vacuum	2	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4655	Stretcher, Mobile, CRS, 9 Position	1	VV	Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M7710	Electrocardiograph, 12 Lead, Portable	1	VV	Used to detect the electrical signals associated with cardiac activity, diagnose cardiac abnormalities, determine a patients response to drug therapy and reveal trends or changes in heart function. Capable of recording two or more leads simultaneously, recording an entire 12 lead ECG in about 10 seconds. Includes of a 3.5 inch, high density, floppy disk drive for test storage. Portable.

M8133	Ergometer, Upper Body	1	VV	Ergometer for measuring upper body exertion during an exercise regimen. The unit consists of a seat and a hand crank mechanism at shoulder height. The unit is used for physical rehabilitation protocols and stress testing. The unit quantifiably measures the effort exerted by the patient.
M8185	System, Stress Exercise, w/Treadmill	1	VV	Stress exercise system with treadmill and respiratory/metabolic assessment. The system includes an ECG amplifier, chart recorder, display, console, treadmill and modules for respiratory/metabolic assessment. Used to determine patient's functional capacity, predict and diagnose cardiopulmonary and vascular diseases and for rehabilitation of patients recovering from leg injuries or other type of illness. Some vendors require a NEMA 5-20R non-locking receptacle for their treadmills.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

8 - OPTM 2 - Tilt Table Testing Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismantling of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismantling equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

E0222	Worksurface, Computer, O/H Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Tack board 1 Cantilevered Work Surface 1 Adjustable Keyboard Tray 1 CPU Holder
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0300	Chair, Task, Swivel, With Arms	1	VV	Task chair, approximately 34" H X 26" W X 22" D with adjustable arms and a five caster adjustable swivel base. Seat and back are foam padded and upholstered in woven fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M7845	Monitor, Physiological, Bedside, 4 Channel	1	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M9066	Table, Examination, Treatment, Electro/Hydraulic	1	VV	Electro-hydraulic examination treatment table. Unit consists of a stainless steel base with an Electro-hydraulic system with foot controls. It includes vacuum formed vinyl contoured top, padded arm rest, adjustable knee rest, stainless steel drainage pan and built-in paper roll retainer/cutter. Designed for general use in treatment rooms for minor surgical procedures.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

9 - OFDC2 - Consult Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0205	Chair, Side With Arms	3	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F0740	Table, Occasional, Lamp	1	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.

10 - XVC01 - Reading Room, ECHO

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray

E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.
11 - XVC01 - Reading Station, EKG				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.
12 - TLTU1 - Toilet, Patient				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.

P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

3 - NON-INVASIVE CARDIOLOGY SUPPORT AREA

1 - UCCL1 - Utility Room, Clean

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
E0903	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an E0921 to transport the locker from place to place.
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
P8710	Utility Center, Plumbing Connection	1	CC	Plumbing connection utility center, sometimes referred to as a 'GUY GRAY BOX'. This recessed utility center provides for hot and cold water connections and a drain connection at sink and other equipment locations. The utility center includes cutoff valves for the water connections, a plug seal for the drain and an outside cover to provide an aesthetic appearance when connections are no longer required. This center may be installed in locations where no plumbing fixtures are included in a design as a future flexibility device, saving many dollars for later facility modifications to incorporate sinks as functions change.

2 - USCL1 - Utility Room, Soiled

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS200	Sink, SS, Single Compartment, 12x28x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

CT050	Countertop, Stainless Steel	7	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

3 - OPHM 1 - Workroom, Event / Holter Monitor

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0210	Chair, Side, Without Arms	1	VV	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.
F0280	Chair, Swivel, Low Back	2	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	1	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M7770	Computer, Holter Monitor Analysis System	1	VV	Central processor for the analysis of Holter monitor recordings. System permits the high speed downloading of Holter recordings into a central database, automated recording analysis and storage, report generation, listing clinical findings and tracking final reports. System may include a monitor, keyboard, scanner, printer, input port and a disk drive storage device.
M9006	Table, Ultrasound, Mobile, Echocardiology	1	VV	Mobile exam table designed for ultrasound and echocardiology examinations. Table has an extra wide top with a 500 lb patient capacity, suitable for bariatric patients. Height range from 23" low to accommodate wheelchair transfers and those with ambulatory difficulties to a high of 39". Table includes motorized height adjustment, Fowler position, Trendelenburg and auto level adjustment.

P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.
-------	-------------------------------------	---	----	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

4 - SRSE1 - Storage, Non Invasive Cardiology Supplies

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2070	Shelving, Storage, 77hx36wx18d	2	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

5 - SRSE1 - Storage, ICD Equipment

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	2	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2070	Shelving, Storage, 77hx36wx18d	2	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

6 - SRE01 - Storage, Equipment

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

7 - RCA01 - Alcove, Crash Cart

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.
M1110	Resuscitator, Bag-Mask, Hand Op, Infant	1	VV	Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M7905	Oximeter, Pulse	1	VV	Pulse oximeter for continuous surveillance of patient pulse and oxygen saturation rates. Instrument features LED display, audio and visual alarms, automatic calibration and battery operation in case of power failure. Other applications include sleep studies, exercise testing and monitoring certain patients in the home (e.g. infants or patients requiring respiratory therapy).
M8770	Aspirator/Pressure Unit, General Purpose	1	VV	General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes.

8 - SRLW1 - Alcove, Wheelchair / Stretcher				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M4705	Wheelchair, Patient Transport, Folding	1	VV	Folding patient transport wheelchair. Constructed of chrome plated steel with detachable armrest and footrests. Unit has heavy duty front casters with sealed radial high-precision ball bearing assembly. Unit is used for patient transport.

M4710	Wheelchair, Patient, Bariatric, Transport, Folding	1	VV	Folding bariatric patient transport wheelchair with a capacity of at least 500 lbs. Constructed with a heavy duty steel frame and double cross brace, with detachable armrest and swing away footrests. Unit has heavy duty front casters and rear wheels with precision wheel bearings in front and rear assembly. Unit is used for patient movement.
9 - JANC1 - Housekeeping Aides Closet (HAC)				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

4 - INVASIVE CARDIOLOGY PATIENT AREA

1 - XCCE1 - Cardiac Catheterization Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A1122	Column, Equipment Arm, Ceiling Mounted, Surgery	2	CC	A ceiling mounted retractable equipment arm for use in the OR. Designed to provide equipment placement support, power receptacles including low-voltage panels, gas outlets and flat screen mounting for a surgical suite. Unit will provide a range of motion of up to 330 degrees with arm providing additional vertical movement. Units are custom configured with multiple options available. Price is based on a unit with two (double) retractable arms. Also available are units for use in anesthesia, ICU and ER.
A1130	Cabinet, Control, Nitrogen	2	CC	Nitrogen control cabinet. Unit consists of supply cut-off valve, supply pressure gauge, pressure regulator (adjustable 0 to 200 PSI), outlet pressure gauge, nitrogen outlet and connection to surgical gas column. Specify recessed or surface mounting. Designed for powering surgical pneumatic tools.
A5077	Dispenser, Hand Sanitizer, Hands-Free	2	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	2	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2020	Can, Trash, 44 Gallon	2	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0220	Analyzer, Hemoglobin, Portable, Hand Held	1	VV	A portable, hand held analyzer for testing hemoglobin. The analyzer will achieve precision and accuracy comparable to a central laboratory. The unit will be battery operated.
L1085	Analyzer, Coagulation, Automatic	1	VV	Automatic coagulation analyzer. The unit performs on-site blood coagulation tests, prothrombin time (PT), and partial thromboplastin time (PTT) tests on whole blood or plasma samples. The analyzer employs both single and duplicating or stat testing capabilities.
M0750	Flowmeter, Air, Connect w/50 PSI Supply	4	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0755	Flowmeter, Oxygen, Low Flow	4	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	4	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M3150	Distribution System, Medication, Automatic	1	VV	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.
M3175	Electrosurgical Unit, Dual Output	1	VV	Dual output electrosurgical unit. Solid state power source with foot switch jacks, monopolar and bipolar outputs, and four independent modes of operation. Used in the operating room or surgicenter as an alternative to the scalpel for cutting tissue.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M4250	Pump, Syringe, Infusion	1	VV	The infusion syringe pump ensures highly accurate volume delivery and consistent flow for small volumes (<50 ml) of pharmacologic agents or thick feeding solutions. It shall be small, lightweight construction, making it transportable. Shall have menu-driven programming capable of flow rates (e.g. 0.1 or 1.0 mL/hr) that are intended for long-term bedside use and/or critical care patient transport, plunger positioning sensor, LCD display for easy viewing, volume limit programming to serve as a convenient cue of volume or dose delivery completion and multiple delivery modes for all applications requiring precisely controlled infusion rates. The infusion pump shall have automatic syringe size sensing which will give the flexibility to accept a wide range of syringe sizes (up to 60 mL) from different manufacturers. Shall be battery powered/AC adapter.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M4255	Stand, IV, Adjustable	2	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	2	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M4645	Patient Transfer Device	2	VV	A patient transfer board designed to make lateral patient transfers safer for staff and be more comfortable for the patients. The board uses a smooth, low friction and static free surface to eliminate the need for metal rollers. The board has a soft foam core that makes them lightweight for ease of use and storage. The long board device also enables the transfer of a patient in the seated or Fowler position. The boards come in three sizes with the long board being foldable. The dimensions and price are for the long wide board.
M4812	Pacemaker, Single Chamber, External, Temporary	2	VV	A single chamber, external temporary pacemaker designed to provide acute therapeutic, prophylactic, and diagnostic pacing support. It is capable of operating in the demand or asynchronous modes and includes adjustable rate, output, and sensing controls. Battery operated.
M7480	Light, Surgical, Ceiling Mounted, Single, Medium	1	VC	Single ceiling mounted surgical light with a light head diameter generally between 21" and 30" depending on the manufacturer. The light is mounted from a pole extending down from the ceiling and then from a pivotal arm assembly that rotates 360 degrees. It includes a variable intensity control and sterile focus handle. The minimum ceiling height for most models is 8'-9"; check the manufacturers' specific recommendations. The database height dimension below refers to the lamp head housing itself. Width and depth are the length of the swing arm plus the diameter of the light head. This light can be used for both minor and major surgical procedures.
M7650	Defibrillator/Monitor, Acute Care	1	VV	Portable defibrillator/monitor for acute care includes biphasic defibrillator, pacing, SPO2, Interpretive 12-lead, NIBP monitoring, EtCO2 monitoring, Invasive pressure monitoring, Vital Sign monitoring, temperature probe, Fax transmission, PCMCIA Data Cards, Paddle accessories, and a color LCD.
M7818	Monitor, Transport	1	VV	A light weight, rugged patient monitor for use during transport. Unit consists of a compact monitor with touchscreen display with up to 3 waveforms on a on a bright non-fading display. The unit measures ECG/respiration, NBP, SpO2, pressure, and temperature and CO2. Data can be transferred seamlessly throughout the continuum of care. Unit is approved for aeromedical use (US Army Airworthiness Certification and Evaluation (ACE) program. Battery run time of 3 hours before recharge.
M7845	Monitor, Physiological, Bedside, 4 Channel	1	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M7860	Monitoring System, Cardiac Catheterization Lab	1	VV	Computerized monitoring system for use in cardiac catheterization labs and cardio-thoracic operating rooms. The system can display up to 32 different waveforms simultaneously, perform calculations of hemodynamic parameters, valve areas and cardiac output, archive procedure results and accept inputs from a variety of monitoring devices. The installed system can also include remote monitors/terminals and additional workstations and may interface with hospital-wide physiological monitoring or clinical information systems. The system includes several configurations in different locations. Database physical dimensions reflect the largest of these work centers. The estimated total 20 amp electrical requirements will be spread across several circuits in several locations. The system price varies greatly on the size and sophistication of the end user's requirements.
M8800	Cart, Anesthesia	1	VV	Mobile anesthesia cart. The cart shall be built of stainless steel or other appropriate material and mounted on 4" casters for easy mobility. It shall be capable of being equipped with bottle holders, adjustable IV pole, storage drawers, shelves and a top bar/rail.
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.
M8825	Table, Instrument/Dressing, CRS, approx. 36x20x34	1	VV	Instrument and dressing table. Made of corrosion resistant stainless steel with a sound deadened top. Includes guard rail, shelf and two side-by-side drawers. The table is mounted on swivel, ball-bearing casters.
M8940	Stool, Anesthesia, With Back	3	VV	Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.
X2106	Scanner, Ultrasound, Intra-Cardiac Echo	1	VV	A portable cardiovascular ultrasound with full diagnostic and monitoring capabilities. The unit employs phased-array transducer technology for 2D, color and Doppler imaging. It will have multiple focal zones to optimize image quality. The unit will have an integrated EchoPAC with data review, analysis, patient archive and reporting capabilities. It will have full DICOM connectivity with embedded raw data speeds allowing for post-exam quantitative analyses at the users convenience. The rechargeable battery will provide up to 1 hour of full scan operation.
X2125	Scanner, Ultrasound, Portable	1	VV	A portable diagnostic ultrasound scanner system configured for various applications, ease-of-use and high performance for enhanced efficiency and accuracy. The scanner is applicable for use in a wide variety of hospital and office environments including ER, breast surgery, anesthesia, vascular, interventional radiology and critical care. The system features a high quality color doppler ultrasound for imaging.
X3155	Rack, Apron/Gloves, Mobile	1	VV	Apron and gloves rack. This is a mobile unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum.

X6190	Radiographic/Fluoro Unit, Cardiac, 100 kW, Digital	1	VC	This system is specifically designed to perform biplane radiographic/fluoroscopic examinations in the Cardiology Department. On-line digital cardiac image processing will provide instant availability of images for review. This units characteristics and components include 100 kW micro-processor controlled X-ray generators, C-arm and U arm with 9" multi-field Image Intensifier, integrated X-ray tube unit and cine camera. The Digital Imaging for both the AP and Lateral planes shall consist of a computer, keyboard with acquisition, viewing monitor, and slave monitor. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended. System to be procured with Cardiac Cath Lab computerized analysis/monitoring system.
X6195	Injector, Angiographic	1	VC	Angiographic injector. This unit is a specialized radiographic procedure that provides sharp, well-defined visual images of the vascular anatomy. The injector introduces a vision radiopaque fluid (contrast medium) into an artery or vein through a small catheter, making vessels contrast with their more radiolucent surrounding. The unit incorporates an electromechanical or pneumatic driven syringe to deliver the contrast medium. The syringe assemblies consist of an electric motor connected to a jackscrew that moves the syringe piston into or out of the syringe barrel. The unit is used in hospitals with radiographic procedures. Specify if unit is to be pedestal, ceiling, wall or table mounted when ordering.

2 - XCCC1 - Control Room, Cardiac Catheterization

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A5145	Hook, Garment, Double, SS, Surface Mounted	4	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A6110	Counter, Console, Communications	1	CC	Counter, console, communications. Consists of one 18" wide base cabinet with two drawers and file drawer, one 30" wide pencil drawer and one 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb.
C0044	Frame, Apron, 1 Drawer, 4x30x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C0045	Frame, Apron, 1 Drawer, 4x36x22	2	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall. Constructed of steel.
C06M0	Cabinet, U/C/B, 1 PBD, 2 DR, 1 File DR, 30x18x22	3	CC	Sitting height under counter base cabinet with a pullboard above two drawers and file drawer. Also referred to as a drawer cabinet. For general purpose use throughout the facility.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

CT030	Countertop, High Pressure Laminate	13	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M8940	Stool, Anesthesia, With Back	3	VV	Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.
X1425	Imager, Laser (1024 X 1024) (Din/PACS)	1	VV	Laser imager. Solid state laser that provides high resolution images of superior quality and accuracy. An infrared laser beam is scanned across each film by a precision rotating polygon, while correcting optics focus and control the beam's intensity. Can be interfaced to as many as eight (8) modalities with interface kit. For use with digital output imaging modalities.

3 - XCCE1 - Procedure Room, Electrophysiology

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A1066	Mirror, Float Glass, With SS Frame	1	CC	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.
A1122	Column, Equipment Arm, Ceiling Mounted, Surgery	2	CC	A ceiling mounted retractable equipment arm for use in the OR. Designed to provide equipment placement support, power receptacles including low-voltage panels, gas outlets and flat screen mounting for a surgical suite. Unit will provide a range of motion of up to 330 degrees with arm providing additional vertical movement. Units are custom configured with multiple options available. Price is based on a unit with two (double) retractable arms. Also available are units for use in anesthesia, ICU and ER.
A1130	Cabinet, Control, Nitrogen	2	CC	Nitrogen control cabinet. Unit consists of supply cut-off valve, supply pressure gauge, pressure regulator (adjustable 0 to 200 PSI), outlet pressure gauge, nitrogen outlet and connection to surgical gas column. Specify recessed or surface mounting. Designed for powering surgical pneumatic tools.
A5077	Dispenser, Hand Sanitizer, Hands-Free	2	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	2	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2020	Can, Trash, 44 Gallon	2	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0220	Analyzer, Hemoglobin, Portable, Hand Held	1	VV	A portable, hand held analyzer for testing hemoglobin. The analyzer will achieve precision and accuracy comparable to a central laboratory. The unit will be battery operated.
L1085	Analyzer, Coagulation, Automatic	1	VV	Automatic coagulation analyzer. The unit performs on-site blood coagulation tests, prothrombin time (PT), and partial thromboplastin time (PTT) tests on whole blood or plasma samples. The analyzer employs both single and duplicating or stat testing capabilities.
M0750	Flowmeter, Air, Connect w/50 PSI Supply	4	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0755	Flowmeter, Oxygen, Low Flow	4	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	4	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M3150	Distribution System, Medication, Automatic	1	VV	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.
M3175	Electrosurgical Unit, Dual Output	1	VV	Dual output electrosurgical unit. Solid state power source with foot switch jacks, monopolar and bipolar outputs, and four independent modes of operation. Used in the operating room or surgicenter as an alternative to the scalpel for cutting tissue.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M4250	Pump, Syringe, Infusion	1	VV	The infusion syringe pump ensures highly accurate volume delivery and consistent flow for small volumes (<50 ml) of pharmacologic agents or thick feeding solutions. It shall be small, lightweight construction, making it transportable. Shall have menu-driven programming capable of flow rates (e.g. 0.1 or 1.0 mL/hr) that are intended for long-term bedside use and/or critical care patient transport, plunger positioning sensor, LCD display for easy viewing, volume limit programming to serve as a convenient cue of volume or dose delivery completion and multiple delivery modes for all applications requiring precisely controlled infusion rates. The infusion pump shall have automatic syringe size sensing which will give the flexibility to accept a wide range of syringe sizes (up to 60 mL) from different manufacturers. Shall be battery powered/AC adapter.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M4255	Stand, IV, Adjustable	2	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	2	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M4645	Patient Transfer Device	2	VV	A patient transfer board designed to make lateral patient transfers safer for staff and be more comfortable for the patients. The board uses a smooth, low friction and static free surface to eliminate the need for metal rollers. The board has a soft foam core that makes them lightweight for ease of use and storage. The long board device also enables the transfer of a patient in the seated or Fowler position. The boards come in three sizes with the long board being foldable. The dimensions and price are for the long wide board.
M4812	Pacemaker, Single Chamber, External, Temporary	2	VV	A single chamber, external temporary pacemaker designed to provide acute therapeutic, prophylactic, and diagnostic pacing support. It is capable of operating in the demand or asynchronous modes and includes adjustable rate, output, and sensing controls. Battery operated.
M7480	Light, Surgical, Ceiling Mounted, Single, Medium	1	VC	Single ceiling mounted surgical light with a light head diameter generally between 21" and 30" depending on the manufacturer. The light is mounted from a pole extending down from the ceiling and then from a pivotal arm assembly that rotates 360 degrees. It includes a variable intensity control and sterile focus handle. The minimum ceiling height for most models is 8'-9"; check the manufacturers' specific recommendations. The database height dimension below refers to the lamp head housing itself. Width and depth are the length of the swing arm plus the diameter of the light head. This light can be used for both minor and major surgical procedures.
M7650	Defibrillator/Monitor, Acute Care	1	VV	Portable defibrillator/monitor for acute care includes biphasic defibrillator, pacing, SPO2, Interpretive 12-lead, NIBP monitoring, EtCO2 monitoring, Invasive pressure monitoring, Vital Sign monitoring, temperature probe, Fax transmission, PCMCIA Data Cards, Paddle accessories, and a color LCD.
M7818	Monitor, Transport	1	VV	A light weight, rugged patient monitor for use during transport. Unit consists of a compact monitor with touchscreen display with up to 3 waveforms on a on a bright non-fading display. The unit measures ECG/respiration, NBP, SpO2, pressure, and temperature and CO2. Data can be transferred seamlessly throughout the continuum of care. Unit is approved for aeromedical use (US Army Airworthiness Certification and Evaluation (ACE) program. Battery run time of 3 hours before recharge.
M7845	Monitor, Physiological, Bedside, 4 Channel	1	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M7860	Monitoring System, Cardiac Catheterization Lab	1	VV	Computerized monitoring system for use in cardiac catheterization labs and cardio-thoracic operating rooms. The system can display up to 32 different waveforms simultaneously, perform calculations of hemodynamic parameters, valve areas and cardiac output, archive procedure results and accept inputs from a variety of monitoring devices. The installed system can also include remote monitors/terminals and additional workstations and may interface with hospital-wide physiological monitoring or clinical information systems. The system includes several configurations in different locations. Database physical dimensions reflect the largest of these work centers. The estimated total 20 amp electrical requirements will be spread across several circuits in several locations. The system price varies greatly on the size and sophistication of the end user's requirements.
M8800	Cart, Anesthesia	1	VV	Mobile anesthesia cart. The cart shall be built of stainless steel or other appropriate material and mounted on 4" casters for easy mobility. It shall be capable of being equipped with bottle holders, adjustable IV pole, storage drawers, shelves and a top bar/rail.
M8810	Stand, Mayo	1	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.
M8825	Table, Instrument/Dressing, CRS, approx. 36x20x34	1	VV	Instrument and dressing table. Made of corrosion resistant stainless steel with a sound deadened top. Includes guard rail, shelf and two side-by-side drawers. The table is mounted on swivel, ball-bearing casters.
M8940	Stool, Anesthesia, With Back	3	VV	Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.
X2106	Scanner, Ultrasound, Intra-Cardiac Echo	1	VV	A portable cardiovascular ultrasound with full diagnostic and monitoring capabilities. The unit employs phased-array transducer technology for 2D, color and Doppler imaging. It will have multiple focal zones to optimize image quality. The unit will have an integrated EchoPAC with data review, analysis, patient archive and reporting capabilities. It will have full DICOM connectivity with embedded raw data speeds allowing for post-exam quantitative analyses at the users convenience. The rechargeable battery will provide up to 1 hour of full scan operation.
X2125	Scanner, Ultrasound, Portable	1	VV	A portable diagnostic ultrasound scanner system configured for various applications, ease-of-use and high performance for enhanced efficiency and accuracy. The scanner is applicable for use in a wide variety of hospital and office environments including ER, breast surgery, anesthesia, vascular, interventional radiology and critical care. The system features a high quality color doppler ultrasound for imaging.
X3155	Rack, Apron/Gloves, Mobile	1	VV	Apron and gloves rack. This is a mobile unit which holds aprons and gloves. The body is heavy gauge steel finish in gray or green baked enamel, glove and apron holding arms are aluminum.

X6190	Radiographic/Fluoro Unit, Cardiac, 100 kW, Digital	1	VC	This system is specifically designed to perform biplane radiographic/fluoroscopic examinations in the Cardiology Department. On-line digital cardiac image processing will provide instant availability of images for review. This units characteristics and components include 100 kW micro-processor controlled X-ray generators, C-arm and U arm with 9" multi-field Image Intensifier, integrated X-ray tube unit and cine camera. The Digital Imaging for both the AP and Lateral planes shall consist of a computer, keyboard with acquisition, viewing monitor, and slave monitor. The system shall be DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. It is recommended that the TV monitors be ceiling suspended. System to be procured with Cardiac Cath Lab computerized analysis/monitoring system.
X6195	Injector, Angiographic	1	VC	Angiographic injector. This unit is a specialized radiographic procedure that provides sharp, well-defined visual images of the vascular anatomy. The injector introduces a vision radiopaque fluid (contrast medium) into an artery or vein through a small catheter, making vessels contrast with their more radiolucent surrounding. The unit incorporates an electromechanical or pneumatic driven syringe to deliver the contrast medium. The syringe assemblies consist of an electric motor connected to a jackscrew that moves the syringe piston into or out of the syringe barrel. The unit is used in hospitals with radiographic procedures. Specify if unit is to be pedestal, ceiling, wall or table mounted when ordering.

4 - XCCC1 - Control Room, Electrophysiology

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A5145	Hook, Garment, Double, SS, Surface Mounted	4	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A6110	Counter, Console, Communications	1	CC	Counter, console, communications. Consists of one 18" wide base cabinet with two drawers and file drawer, one 30" wide pencil drawer and one 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb.
C0044	Frame, Apron, 1 Drawer, 4x30x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C0045	Frame, Apron, 1 Drawer, 4x36x22	2	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall. Constructed of steel.
C06M0	Cabinet, U/C/B, 1 PBD, 2 DR, 1 File DR, 30x18x22	3	CC	Sitting height under counter base cabinet with a pullboard above two drawers and file drawer. Also referred to as a drawer cabinet. For general purpose use throughout the facility.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

CT030	Countertop, High Pressure Laminate	13	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M8940	Stool, Anesthesia, With Back	3	VV	Anesthesia stool with back. All stainless steel with well-curved back panel and wide conductive seat. Designed for the anesthesiologist during surgical procedures.
X1425	Imager, Laser (1024 X 1024) (Din/PACS)	1	VV	Laser imager. Solid state laser that provides high resolution images of superior quality and accuracy. An infrared laser beam is scanned across each film by a precision rotating polygon, while correcting optics focus and control the beam's intensity. Can be interfaced to as many as eight (8) modalities with interface kit. For use with digital output imaging modalities.

5 - TRTE1 - Transesophageal Echocardiograph (TEE) Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A1132	Rail, Accessory Mounting, Length As Required	1	VC	Horizontal mounting rail will consist of lock mounting devices capable of; supporting up to 75 pounds each, being repositioned, and mounting and dismounting of equipment without the use of tools. The rail must be capable of supporting medical equipment and accessories normally found in exam or patient rooms. The rail system must be capable of mounting and dismounting equipment without leaving or creating new holes in the finished surface of the wall.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0210	Worksurface, w/Overhead Cab, Wall Mtd, 48" W	1	VV	THIS TYPICAL INCLUDES: 2 Vertical Hanging Strips 1 Lockable Flipper Unit 1 Shelf, Storage/Display 1 Light 1 Cantilevered Work Surface
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

				<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F0355	Footstool, Straight	1	VV	Step stool. Used to assist patients getting on and off exam or surgical tables. Fitted with electrically conductive rubber tips.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F2017	Waste Receptacle, 24 GAL	1	VV	Rectangular steel waste receptacle with step-on lid and 24 gallon capacity. The receptacle is used to collect and temporarily store small quantities of paper refuse. Can be used in restrooms, patient areas, laboratories, pharmacies, etc.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	2	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	2	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0765	Regulator, Vacuum	2	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M3150	Distribution System, Medication, Automatic	1	VV	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.
M4116	Monitor, Vital Signs	1	VV	Electronic sphygmomanometer. LCD displays non-invasive blood pressure, pulse rate and temperature. Used in hospitals and clinics. Includes an optional mobile stand.
M4255	Stand, IV, Adjustable	2	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	2	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M7401	Light, Exam, Mobile, Spotlight, Mobile Stand	1	VV	The exam light shall be a mobile floor unit. The light will be a halogen bulb or LED that can produce a continuous and homogeneous spot of light adjustable from 5 to 9 inches in diameter from a set distance. The light intensity shall be a minimum of 750 foot-candles at a distance of 16 inches and have a color temperature of 3,200 degrees Kelvin. The unit will consist of an arm or sleeve of approximately 45 inches in length to allow for easy arm rotation and arm movement up and down. The unit shall be mounted on a caster base for easy movement.
M7650	Defibrillator/Monitor, Acute Care	1	VV	Portable defibrillator/monitor for acute care includes biphasic defibrillator, pacing, SPO2, Interpretive 12-lead, NIBP monitoring, EtCO2 monitoring, Invasive pressure monitoring, Vital Sign monitoring, temperature probe, Fax transmission, PCMCIA Data Cards, Paddle accessories, and a color LCD.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M9006	Table, Ultrasound, Mobile, Echocardiology	1	VV	Mobile exam table designed for ultrasound and echocardiology examinations. Table has an extra wide top with a 500 lb patient capacity, suitable for bariatric patients. Height range from 23" low to accommodate wheelchair transfers and those with ambulatory difficulties to a high of 39". Table includes motorized height adjustment, Fowler position, Trendelenburg and auto level adjustment.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.
X2105	Scanner, Ultrasound, Cardiac (Echo)	1	VV	High definition, diagnostic ultrasound system for Radiology, Cardiology, Vascular, ob-gyn, Perinatology, and Surgical imaging applications. The unit employs curved, phased and linear array imaging technology. The system supports colorflow, pulse, continuous wave imaging modalities. On board software measurement packages available for all imaging applications. The system is DICOM 3.0 compatible, for easy linkage to filmless image management systems and review stations. In addition, a full line of probes and conventional recording devices are available.

6 - USCL4 - Storage, TEE Probe

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M3160	Cabinet, Storage, Hanging Scopes	2	VV	Scope hanging cabinet. Cabinet has the capacity to hold up to nine scopes. Some cabinets may have a roll top closure and optional storage drawer.

9 - TLTU1 - Toilet, Patient

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.

A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

5 - INVASIVE CARDIOLOGY SUPPORT AREA

1 - XCCI1 - Instrument Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
M2035	Rack, Storage, Mobile, Wire, CRS	4	VV	Mobile, wire, storage rack. Unit has open, fully adjustable, corrosion resistant wire surfaces and is mounted on stem casters. Used for linen or other general purpose storage and transport. Racks are provided in various sizes and configurations. The price provided is for a unit approximately 68"H x 18"D x 48"W with four shelves, bumpers, two swivel and two braking casters.

2 - XCCA1 - System Component Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
3 - XVC01 - Viewing Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.

4 - SRS04 - Supply Room, Sterile

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
E0984	Cart, Wire, Mobile, 72"H x 60"W x 24"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wire Cart, w/Casters 5 Wire Shelves w/Dividers 5 Vertical Back/Side Panels 2 Storage Frame 4 Drawers, 6"H 1 Cart Cover Label Clips Drawer Dividers

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers/ labels. Convenience outlet required at point of use.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	VV	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 8" to 10" of wall. Fingertip adjustability for keyboard and monitor enable frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	10	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M8910	Cart, Surgical Case	2	VV	Surgical case cart. Unit consists of two hinged cabinet sections, each section equipped with two pull-out shelves with stops. The entire unit is mounted on four heavy duty conductive swivel casters. Used to transport surgical packs and supplies to surgery and soiled items back to central supply.

5 - OREC1 - Equipment Cleaning Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS200	Sink, SS, Single Compartment, 12x28x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	7	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
E0912	Locker, Supply, Med Surg, Wall Mtd	3	VV	Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	Consider the need for an E0921 to transport the locker from place to place. Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.

P6350	Sink, Flushing Rim, China	1	CC	Flushing rim sink approximately 18" H x 26" D x 22" W. Also called a clinic service sink. Unit is constructed of vitreous china with an integral flushing rim. It includes: faucet with a fork brace; 6 inch wrist control handles; plain end spout with bucket hook; stainless steel spring type front rim guard; and grid drain. If it is to be floor mounted, a base must be provided. Unit is used in utility rooms to clean equipment and materials.
6 - XVC01 - Digital Quality Control Area - PACS				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0048	Workcenter, Computer, Free Standing, 72" W	1	VV	THIS TYPICAL INCLUDES: 2 Paper Tray 1 Diagonal Tray 1 Tool Rail 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0117	Workstation, Straight, Free Standing, 48" W	1	VV	This JSN provides a typical work station to quickly plan work areas in clinical or administrative spaces. THIS TYPICAL INCLUDES: 2 standard solid panels; 1 panel connector, 2-way corner; 2 finished end hardware kits; 1 cantilevered work surface; 1 lockable flipper unit; 1 light; 1 tack board; 1 tool rail; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file; 1 support panel.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4124	Console, PACS, Remote View, w/Four 2MP Monitors	1	VV	Four monitor remote viewing station for picture and retrieval (DIN/PACS) system. This station is for use by providers inside or outside radiology to review images. Station includes local image storage, image manipulation and simultaneous display of multiple images on four 1260 X 1600 monitors. Images are stored on a resident memory and roll off to long term storage as more recent images are sent to the station. Provider may request images from the PACS by LAN for image and result receipt. Console must be DICOM compliant. Input may be by keyboard, mouse, trackball or voice activated commands.

7 - XFDS1 - Digital Archive Storage Room - PACS

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A0900	Relay Rack, Aluminum	1	VV	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).
A0905	Adapter Panel With Couplers, Blue, 6 Port, SM/MM	1	VV	Modular six-pack fiber adapter panel, designed to snap into Hubbell's enclosures such as JSN A0904. Loaded with 3 SM/MM SC duplex style blue adapters, standard density.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A6210	Uninterruptible Power Supply, Single Phase	1	VV	Stand alone uninterruptible power supply (UPS) available in 120, 208 or 240 VAC configuration. Power output can range from 200 VA to 3000 VA depending on the application. Used in areas where power protection is required for computer systems, communication equipment, etc. The UPS is used to keep the equipment on line or safely turn the equipment off in the event of a power loss.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
X4160	Information System, DIN-PACS	1	VC	The Digital Imaging Network – Picture Archiving and Communications System (DIN-PACS) is an open system network of digital devices designed for the acquisition, transmission, display and management of diagnostic imaging studies. Equipment for DIN-PACS will include workstations, storage devices, servers, interconnecting cables, and all software, hardware, firmware and ancillary devices required for full functionality. Systems will meet DICOM and HL7 standards. Turnkey installation and integration with existing networks and legacy systems is required. Size of system is based on volume of exams taken and file size. Equipment configuration and site preparation, if required, is unique and specific to each medical facility.

8 - MEDP1 - Medication Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS250	Sink, SS, Single Compartment, 6x12x9 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	8	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3150	Distribution System, Medication, Automatic	2	VV	An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.

9 - UCCL1 - Utility Room, Clean

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.

E0903	Locker, Supply, w/Shelves, Wall Mtd, 23"W x 20"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E0906	Locker, Supply, General, Wall Mtd, 23"W x 20"D	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E0912	Locker, Supply, Med Surg, Wall Mtd	2	VV	<p>Medical/Surgical Supply locker, Wall Mounted, approximately 23"W x 20"D. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Wall Mounted Rail 1 Locked Storage Container 4 Tray/Shelves 5 Drawers, 3"H 2 Drawers, 6"H 2 Tray/Shelf Dividers Drawer Organizer Bins <p>Consider the need for an E0921 to transport the locker from place to place.</p>
E1500	Rail, MOD, W/MNTD, HX144XD	1	VV	<p>Wall mounted rail used for hanging (mounting) lockers, shelves and drawers on a wall.</p>
F2000	Basket, Wastepaper, Round, Metal	1	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
P8710	Utility Center, Plumbing Connection	1	CC	<p>Plumbing connection utility center, sometimes referred to as a 'GUY GRAY BOX'. This recessed utility center provides for hot and cold water connections and a drain connection at sink and other equipment locations. The utility center includes cutoff valves for the water connections, a plug seal for the drain and an outside cover to provide an aesthetic appearance when connections are no longer required. This center may be installed in locations where no plumbing fixtures are included in a design as a future flexibility device, saving many dollars for later facility modifications to incorporate sinks as functions change.</p>

10 - USCL1 - Utility Room, Soiled

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C05P0	Cabinet, Sink, U/C/B, 2 Door, 36x48x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS200	Sink, SS, Single Compartment, 12x28x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT050	Countertop, Stainless Steel	7	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

11 - SL001 - Lounge, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.

12 - LR002 - Locker Room, Male Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1030	Locker, 2 Person, Over/Under	10	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5020	Bench, Locker Room, Floor Mounted	1	CC	Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

13 - TLTS1 - Toilet / Shower, Male Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1090	Mirror, Float Glass, With SS Frame & Shelf	1	CC	A high quality 1/4" polished float glass mirror, approximately 36" H X 18" W framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners and an integral stainless steel, stain finish, shelf. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in restroom areas, Doctor examination areas, offices, etc. May also be used above double lavatories, either wall or countertop mounted.
A5030	Bench, Stall, Shower, Built In	1	CC	Shower bench; built-in. Eighteen (18) gauge stainless steel frame with anchors built-in into the wall. Size and shape as required.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5110	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5170	Rod, Shower Curtain, 1" Diameter, W/Curtain & Hooks	1	CC	A concealed mounted, 1" outside diameter, satin finish stainless steel, shower curtain rod with white vinyl shower curtain (72" H) and SS shower curtain hooks. Rod and curtain available in various widths. For general purpose use at shower stall or bathtub locations. Pricing based upon standard shower stall dimensions of 36" x 36" and a standard curtain height of 72".
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
A5205	Bar, Towel, 1" Diameter, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, 1" diameter, towel bar. Support posts and flanges are one piece, chrome-plated, cast heavy brass with satin finish. Towel bar shall not rotate within support posts. Available in 18", 24" and 30" widths. For general purpose use in shower or bathtub rooms. Pricing based upon a suggested standard width of 18".
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

P5040	Shower, Single, Hand-Held	1	CC	A complete, barrier-free, single hand-held, personal shower system. The shower system includes: pressure balanced mixing valve with high temperature limit stop; personal hand shower; shower hose; wall supply; and slide bar. For general purpose use throughout the facility in shower stalls.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

14 - LR002 - Locker Room, Female Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1030	Locker, 2 Person, Over/Under	10	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5020	Bench, Locker Room, Floor Mounted	1	CC	Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

15 - TLTS1 - Toilet / Shower, Female Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1090	Mirror, Float Glass, With SS Frame & Shelf	1	CC	A high quality 1/4" polished float glass mirror, approximately 36' H X 18' W framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners and an integral stainless steel, stain finish, shelf. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in restroom areas, Doctor examination areas, offices, etc. May also be used above double lavatories, either wall or countertop mounted.
A5030	Bench, Stall, Shower, Built In	1	CC	Shower bench; built-in. Eighteen (18) gauge stainless steel frame with anchors built-in into the wall. Size and shape as required.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5110	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5170	Rod, Shower Curtain, 1" Diameter, W/Curtain & Hooks	1	CC	A concealed mounted, 1" outside diameter, satin finish stainless steel, shower curtain rod with white vinyl shower curtain (72" H) and SS shower curtain hooks. Rod and curtain available in various widths. For general purpose use at shower stall or bathtub locations. Pricing based upon standard shower stall dimensions of 36" x 36" and a standard curtain height of 72".
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
A5205	Bar, Towel, 1" Diameter, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, 1" diameter, towel bar. Support posts and flanges are one piece, chrome-plated, cast heavy brass with satin finish. Towel bar shall not rotate within support posts. Available in 18", 24" and 30" widths. For general purpose use in shower or bathtub rooms. Pricing based upon a suggested standard width of 18".
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.

P5040	Shower, Single, Hand-Held	1	CC	A complete, barrier-free, single hand-held, personal shower system. The shower system includes: pressure balanced mixing valve with high temperature limit stop; personal hand shower; shower hose; wall supply; and slide bar. For general purpose use throughout the facility in shower stalls.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

16 - RCA01 - Alcove, Crash Cart

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.
M1110	Resuscitator, Bag-Mask, Hand Op, Infant	1	VV	Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M7905	Oximeter, Pulse	1	VV	Pulse oximeter for continuous surveillance of patient pulse and oxygen saturation rates. Instrument features LED display, audio and visual alarms, automatic calibration and battery operation in case of power failure. Other applications include sleep studies, exercise testing and monitoring certain patients in the home (e.g. infants or patients requiring respiratory therapy).

M8770	Aspirator/Pressure Unit, General Purpose	1	VV	General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes.
-------	------------------------------------------	---	----	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

17 - SRLW1 - Alcove, Wheelchair / Stretcher

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M4705	Wheelchair, Patient Transport, Folding	1	VV	Folding patient transport wheelchair. Constructed of chrome plated steel with detachable armrest and footrests. Unit has heavy duty front casters with sealed radial high-precision ball bearing assembly. Unit is used for patient transport.
M4710	Wheelchair, Patient, Bariatric, Transport, Folding	1	VV	Folding bariatric patient transport wheelchair with a capacity of at least 500 lbs. Constructed with a heavy duty steel frame and double cross brace, with detachable armrest and swing away footrests. Unit has heavy duty front casters and rear wheels with precision wheel bearings in front and rear assembly. Unit is used for patient movement.

18 - LCCL1 - Storage, Clean Linen

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
F0515	Cart, Supply, Linen	1	VV	Closed linen supply cart. Equipped with four (4) non-marking rubber tire roller bearing casters and heavy duty cover. May be used for the delivery and user storage of clean linen as well as the return of soiled linen.
M7300	Dispenser, Garment, Scrubs	1	VV	A garment dispenser and receiver cabinet for dispensing scrub sets to customers. Dispenser holds approximately 64 sets of scrubs and accommodates 85 users per day with 2 refills per day. Garments are dispensed in sets by size to authorized personnel by use of hospital ID, bar code, magnetic strip or with keypad backup. Maintains control of scrub sets through usage reports and digital recording of returns.

19 - JANC1 - Housekeeping Aides Closet (HAC)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

6 - INVASIVE CARDIOLOGY PREP AND RECOVERY AREA

1 - RRSS1 - Recovery Room, Patient Prep

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1107	Rail System , Utility, Gas and Electric	3	CC	The headwall rail system shall consist of three horizontal rails mounted to the patient room headwall to provide utilities and patient services to support ancillary equipment to include gas and vacuum. The rail system must be capable of quickly adding or relocating medical gases services and be able to accept new equipment, provide physical support to equipment, brackets, shelves and other patient support items.
A5077	Dispenser, Hand Sanitizer, Hands-Free	3	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	3	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	3	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5180	Track, Cubicle, Surface Mounted, With Curtain	24	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
E0945	Cart, Computer, Mobile	3	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	3	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F0205	Chair, Side With Arms	3	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F2010	Basket, Wastepaper, Step-On	3	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
M0750	Flowmeter, Air, Connect w/50 PSI Supply	3	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	3	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0765	Regulator, Vacuum	6	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	3	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3070	Hamper, Linen, Mobile, w/Lid	1	VV	Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen transport in hospitals and clinics.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
M4200	Otoscope/Ophthalmoscope, Wall Mounted	3	VV	Wall mounted otoscope and ophthalmoscope. Includes 6 foot line cord and plug and accepts and includes two handles. Contains head turn-on/turn-off, built-in speculum tray and 8 foot coiled cords. Unit is designed for use in patient exam rooms.
M4255	Stand, IV, Adjustable	3	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	3	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.
M4275	Pump, Continuous, Analgesia (PCA)	3	VV	Continuous analgesia pump. Also known as a PCA or patient controlled analgesia pump. The unit provides a controlled, continuous or as required (PRN) dose of analgesia medications for postoperative patients. The patient can control administration of the prescribed drug up to a preset rate. The unit can be mounted to an IV pole and/or be small enough to be carried in a pouch. Use of this device speeds patient ambulation and reduces the length of hospital stays. Depending on the manufacturer, electrical requirements refer to either the unit itself or the battery recharging unit.
M4665	Stretcher, Recovery, Surgical	3	VV	Recovery/surgical stretcher. Strong I-beam construction type unit. The height is adjustable with manual backrest and crank operated knee catch. Stainless or painted steel top and chassis. Features 8" or 10" conductive casters, with lock and brake, folding, tuck-away chrome side-rails and IV stand and a flame retardant antibacterial mattress. Designed for operating room transport or recovery applications.

M7040	Table, Overbed	3	VV	Overbed table. Adjustable height table constructed of heavy gauge steel. Mounted on 2" diameter twin swivel casters with bumper caps. Table top is constructed with a high pressure plastic laminated surface that resists chipping, scratching, and staining. It includes a vanity tray and a mirror. Table is designed for use over bed, wheelchair or large chair.
M7405	Light, Exam, Ceiling Mounted	3	CC	Ceiling exam light. Consists of a lightheaded reflector supported by a ceiling mounted radial arm assembly that provides a wide range of positioning capabilities. Halogen bulbs and an intensity control provide cool, color corrected light. The minimum ceiling height in most cases is 8'-0"; refer to each manufacturer's specific installation requirements. Physical dimensions refer to the retracted light; one length of the dual swing arm around the center mount in width and depth and the combined height of the lamp head and folded arms. Unit may also have a center mount detachable and sterilizable control handle. For use in minor procedure or examination room applications.
M7845	Monitor, Physiological, Bedside, 4 Channel	3	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.
M8810	Stand, Mayo	3	VV	Adjustable instrument table. Table is corrosion resistant stainless steel construction and is mounted on two casters with two skid rails. It has telescopic upright adjusts from 39 inches to 60 inches with automatic locking device, and removable 13"x19" instrument tray. Designed for use in operating and procedure rooms.

2 - RROP1 - Recovery Cubicle, Patient Prep

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A1107	Rail System, Utility, Gas and Electric	1	CC	The headwall rail system shall consist of three horizontal rails mounted to the patient room headwall to provide utilities and patient services to support ancillary equipment to include gas and vacuum. The rail system must be capable of quickly adding or relocating medical gases services and be able to accept new equipment, provide physical support to equipment, brackets, shelves and other patient support items.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	VV	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5180	Track, Cubicle, Surface Mounted, With Curtain	10	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
E0945	Cart, Computer, Mobile	1	VV	A mobile computer cart for use throughout the facility. The cart dimensions will be approximately 45" H x 30" W x 22" D with casters. May include drawers and miscellaneous other accessories that will be determined at time of purchase. This Typical may include: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top 1 Flip-Up Shelf 1 Sharps Container Holder 1 Wastebasket 1 Chart Holder 2 Drawers, 3"H 2 Drawers, 6"H 3 Accessory Rail, Side Drawer Organizer Bins
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0265	Chair, Recliner	1	VV	Reclining chair, 46" high X 33" wide X 40" deep with arms, straight leg base and floor glides or lockable two (2) inch casters. Seat, back and foot rest are foam padded and upholstered with woven textile fabric or vinyl.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.
M0750	Flowmeter, Air, Connect w/50 PSI Supply	1	VV	Air flowmeter. Unit has a stainless steel needle valve with clear flowtube for connection to 50 PSI air outlet from central pipeline system. Requires the appropriate adapter for connection to the wall outlet and fitting to connect to tubing. Database prices reflect fittings with an attached DISS power outlet. Other outlet and adapter configurations are available.
M0755	Flowmeter, Oxygen, Low Flow	1	VV	Oxygen flowmeter. Consists of a clear crystal flowtube calibrated to 3.5 or 8 LPM depending on manufacturer. For oxygen regulation in hospital settings. Database pricing includes DISS fitting and DISS power outlet and wall adapter. Other fitting and adapter configurations are available.
M0765	Regulator, Vacuum	2	VV	Vacuum pressure regulator for connection to central piped vacuum system. Standard display scale is graduated at least from 0 to 200 mm Hg of vacuum. Displays on specialized regulators may cover other vacuum ranges. Regulator type (continuous, intermittent, continuous/intermittent, surgical, pediatric, thoracic, etc.) as required. To be used in delivery, neonatal, pediatrics or any area where suction is required. Database pricing reflects continuous regulators graduated to 200 mm Hg with a full line vacuum selection switch and DISS configured inlets and outlets.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M4255	Stand, IV, Adjustable	1	VV	Adjustable IV stand with 4-hook arrangement. Stand has stainless steel construction with heavy weight base. It adjusts from 66 inches to 100 inches and is mounted on conductive rubber, ball bearing, swivel casters. Stand is used for administering intravenous solutions.
M4266	Pump, Volumetric, Infusion, Multiple Line	1	VV	Volumetric infusion pump. Pump is self-regulating with automatic sensor and adjustable rate. Equipped with visual and audible alarms and up to 10 hour capacity battery. For the administration of a wide variety of therapeutic agents where precise control is required. Unit provides individual control to IV lines simultaneously.

M4665	Stretcher, Recovery, Surgical	1	VV	Recovery/surgical stretcher. Strong I-beam construction type unit. The height is adjustable with manual backrest and crank operated knee catch. Stainless or painted steel top and chassis. Features 8" or 10" conductive casters, with lock and brake, folding, tuck-away chrome side-rails and IV stand and a flame retardant antibacterial mattress. Designed for operating room transport or recovery applications.
M7040	Table, Overbed	1	VV	Overbed table. Adjustable height table constructed of heavy gauge steel. Mounted on 2" diameter twin swivel casters with bumper caps. Table top is constructed with a high pressure plastic laminated surface that resists chipping, scratching, and staining. It includes a vanity tray and a mirror. Table is designed for use over bed, wheelchair or large chair.
M7405	Light, Exam, Ceiling Mounted	1	CC	Ceiling exam light. Consists of a lightheaded reflector supported by a ceiling mounted radial arm assembly that provides a wide range of positioning capabilities. Halogen bulbs and an intensity control provide cool, color corrected light. The minimum ceiling height in most cases is 8'-0"; refer to each manufacturer's specific installation requirements. Physical dimensions refer to the retracted light; one length of the dual swing arm around the center mount in width and depth and the combined height of the lamp head and folded arms. Unit may also have a center mount detachable and sterilizable control handle. For use in minor procedure or examination room applications.
M7845	Monitor, Physiological, Bedside, 4 Channel	1	VV	4 channel bedside physiological monitor. The unit consist of a four-channel non-fade monochrome display monitor, an alarm system and printer-recording capabilities. The monitor has color coded controls and automatic calibration. The unit displays up to four waveforms simultaneously. The parameters to be monitored are user selectable. The monitor may be connected to a central monitoring station. The unit monitors patients in most acute care areas, step-down units, procedure rooms and emergency rooms.
P3100	Lavatory, Vitreous China, Slab Type	1	CC	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.

3 - TLTU1 - Toilet, Prep / Recovery Patient

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

4 - NST A1 - Nurse Station

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	2	VV	Telephone, desk, multiple line.

				<p>Nurse station typicals have non-powered steel frames with a pre-installed metal junction box for user defined electrical solutions. Data modules and low voltage cabling can be routed freely within the frame. Electrical and/or data devices are not provided with the nurse station. Panel inserts are available in fabric, painted metal, tackable, acoustical, paper management, rail, glass, open and electrical/data accessible styles. Typicals include panel inserts for both sides of the steel frame. All electrical connections must be made by an electrical contractor. THIS TYPICAL INCLUDES:</p> <p>5 steel frames, 70"H x 24"W; 1 steel frame, 70"H x 48"W; 2 steel frames, 38"W x 48"W; 4 steel frames, 38"H x 24"W; 1 steel frame w/low access, 38"H x 48"W; 2 frame connectors, 3-way corner, 70"H; 1 frame connector, 2-way corner, 38"H; 2 frame connectors, 135 degree, 2-way, 38"H; 9 finished end hardware; 6 frame-to-frame connectors; 3 cantilevered work surface, 48"W; 2 cantilevered, work surface, 72"W; 1 cantilevered low access work surface, 135 degree, 48"W; 2 pedestal box/box/files; 2 panel inserts, painted metal, 8"H x 24"W; 50 panel inserts, painted metal, 16"H x 24"W; 10 panel inserts, painted metal, 16"H x 48"W; 2 panel inserts, painted metal, 20"H x 48"W ; 2 panel inserts, tackable, 16"H x 24"W; 2 panel inserts, paper mgmt., 8"H x 48"W; 1 countertop w/light support assembly, 16"D x 14'-0"L; 18 paper tray, 10"W; 2 chart shelf, pass-thru, 24"W; 2 chart shelf, pass-thru, 48"W.</p>
E0418	Nurse Station, Medium, Free Standing	1	VV	
F0280	Chair, Swivel, Low Back	4	VV	<p>Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.</p>
F2000	Basket, Wastepaper, Round, Metal	2	VV	<p>Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.</p>
F3050	Whiteboard, Dry Erase	1	VV	<p>Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.</p>

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1605	Holder, Chart, 20 Each	1	VV	Clinical chart holder cart. 20 chart capacity. 2 side-by-side tiers. May be ordered in various chart capacities. Constructed of heavy metal frames with vinyl laminated surfaces or painted panels. 3" casters with locks. Used to hold patient spring loaded charts.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	4	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1820	Imprinter, Data Record, Electric	1	VV	Electric data record imprinter. The device accepts embossed plastic patient cards in either the 50 column or the 80 column format and adjusts automatically for card size and form thickness. Device will provide clear readable impressions with a cycle that is less than 1 second in length. Electro-mechanical design provides for a consistent impression that is independent of operator knowledge or technique. Unit may include a date/time stamp as an accessory.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
M1855	Facsimile Machine	1	VV	Plain paper facsimile unit used to transmit printed matter or images over standard telephone lines. The unit operates at a modem speed of 33.6 Kbps and automatically recognizes and communicates with a variety of standard facsimile machines. Commonly referred to as "fax" unit.
M7850	Monitor, Physiological, Central, 8 Bed, Color	1	VV	Eight bed central physiologic monitoring station. System consists of a central monitor that displays patient information from bedside monitors. It also centralizes alarm and recording functions from ECG tracings to vital signs display. Up to eight patients monitoring capabilities. Designed for use in the ICU, CCU, emergency room or recovery room.

5 - NCWD4 - Alcove, Nourishment Station

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.

CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	1	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3025	Board, Bulletin, Wood Framed	1	VV	Bulletin board approximately 36"W x 24"H. Wood framed 1/2" cork posting panel with moisture proof backing. Units are factory assembled and have keyhole hangers for easy installation.
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.

6 - RCA01 - Alcove, Crash Cart

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
E0954	Cart, Emergency, Mobile, 66"H x 32"W x 22"D	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Cart body, style-A narrow, w/raised edge top 1 Accessory rail, side 1 Accessory rail, back 1 Defibrillator tray 1 IV pole 1 Breakaway bar 1 Flip-up shelf 1 Wastebasket 1 Oxygen tank holder 1 Electrical box-4 outlet 1 Cord wrap 4 Drawer, 3"H 3 Drawer, 6"H Drawer organizer bins.
M1100	Resuscitator, Bag-Mask, Hand Operated	1	VV	Hand operated bag-mask resuscitator. Consists of face mask, non-rebreathing valve, compression bag and tidal bag. Used for resuscitation in life saving situations.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M1110	Resuscitator, Bag-Mask, Hand Op, Infant	1	VV	Hand operated bag-mask resuscitator. Consists of an infant face mask, non-rebreathing, pressure limiting safety valve, compression bag, tidal bag, oxygen reservoir bag and manometer connection and wall bracket. Cleaning and decontamination methods include disinfecting, pasteurization, boiling and steam autoclaving. Used for resuscitation of infants in life saving situations.
M7660	Defibrillator/Monitor/Recorder, Portable	1	VV	Portable defibrillator-monitor-recorder. Integral unit system operable from self-contained rechargeable batteries. ECG may be viewed through paddles or patient cable. Options include external pacing and 12-Lead.
M7905	Oximeter, Pulse	1	VV	Pulse oximeter for continuous surveillance of patient pulse and oxygen saturation rates. Instrument features LED display, audio and visual alarms, automatic calibration and battery operation in case of power failure. Other applications include sleep studies, exercise testing and monitoring certain patients in the home (e.g. infants or patients requiring respiratory therapy).
M8770	Aspirator/Pressure Unit, General Purpose	1	VV	General purpose suction/pressure apparatus. Double stainless steel console unit with a 1/8 HP motor, stand-mounted. Stands include 2 1/2" casters with chemical resistant top. Pumps suction capacity: 22 LPM. Unit includes collection bottle, bacteria filter and suction regulating valve. Used for oral/nasal, tracheal suctioning and other emergency purposes.

7 - SRE01 - Storage, Equipment

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

7 - STAFF AND ADMINISTRATIVE AREA

1 - OFA09 - Office, Cardiovascular Laboratory Service Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - SEC01 - Secretary / Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	<p>This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0305	Chair, Waiting Room, Single	2	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

3 - OFA07 - Workstation, Physician

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

4 - OFA09 - Office, Nurse Manager

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
5 - OFA07 - Workstation, Nurse Practitioner				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
6 - OFA07 - Workstation, Nurse				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

7 - OFA07 - Workstation, Technician

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

8 - OFA07 - Workstation, Administration

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

9 - CRA02 - Conference Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

F0220	Chair, Conference	10	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
F0295	Chair, Stacking	8	VV	Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending upon the model selected. These chairs are intended primarily as overflow capacity for conference rooms.
F0600	Credenza, Executive, Wood	1	VV	Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with adjustable shelf and floor glides.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0755	Table, Conference, Wood	2	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.
F2005	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.

10 - WRCH1 - Workroom, Cardiology Team

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	2	VV	Telephone, desk, 1 line.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

E0042	Workcenter, Computer, Free Standing, 48" W	2	VV	<p>THISTYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
F0275	Chair, Swivel, High Back	4	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0750	Table, Office, (size as required)	1	VV	Office table, sized as required. May be used as either a four (4) to six (6) person conference table or as an extra work surface area.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

11 - RPR01 - Copier / Printer Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
F0465	Cabinet, Storage, 2 Door, 5 Shelf	1	VV	Storage cabinet, 78" high X 48" wide X 24" deep with two (2) doors and five (5) adjustable shelves.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2550	Shredder, Paper Heavy Duty	1	VV	Shredder shall be able to process a minimum of 25 sheets of paper per pass at a minimum rate of 20 feet per minute. The unit shall have a 16 inch throat to accept paper. Paper shall be shredded into 1/4 inch strips.
M1810	Copier, Floor Standing, Digital	1	VV	Floor standing copier. Unit features automatic paper size selection, automatic document feeder and sorter. The system also has zoom capabilities and automatic two-sided copying. For use where medium volume reproduction is required in the range of 30 to 40 copies per minute.

M1835	Printer, Color Laser, Large	1	VV	Color laser printer designed for high volume use and network capable. The printer shall be capable of printing a minimum of 25 pages per minute (ppm) of black print and 20 ppm color print. Resolution shall be no less than 600 X 600 dpi. It shall be capable of printing on multiple media types (plain, inkjet, photo paper and transparencies) and be capable of accepting media sizes of 3 X 5 to 8.5 X 14 inches. The printer is used in multi-user network offices.
M1855	Facsimile Machine	1	VV	Plain paper facsimile unit used to transmit printed matter or images over standard telephone lines. The unit operates at a modem speed of 33.6 Kbps and automatically recognizes and communicates with a variety of standard facsimile machines. Commonly referred to as "fax" unit.

12 - SRS01 - Storage, Forms/ Literature

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

13 - TLTU1 - Toilet, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.

A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

8 - EDUCATION AREA

1 - OFA09 - Office, Residency Program Director

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - OFA07 - Workstation, Intern / Resident / Fellow

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

3 - CLR01 - Conference Room / Classroom

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A0925	Cabinet, Computer, Server, Blade	1	VV	Rack enclosure cabinet for blade servers and other data center components. Rack is designed to support power management, efficient cooling and flexible cable management. Front and rear doors will aid cooling and simplify component installations. Numerous sizes and configurations are available.
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

A5220	Bracket, Television, Wall Backing	2	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
F0115	Bookcase, Open, 5 Shelf	1	VV	Freestanding open shelf bookcase, approximately 82" high X 37" wide X 18" deep with 5 (five) adjustable shelves. Unit can be separate or part of a system with available add-on shelving.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0280	Chair, Swivel, Low Back	32	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F0465	Cabinet, Storage, 2 Door, 5 Shelf	1	VV	Storage cabinet, 78" high X 48" wide X 24" deep with two (2) doors and five (5) adjustable shelves.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation, approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0780	Table, Work, 60W x 30D	16	VV	Work table approximately 29" high X 60" wide X 30" deep with top and four (4) non-folding legs.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2100	Lectern, Mobile, With Reading Light	1	VV	Portable floor lectern with reading light and self-contained audio. May use 110V or batteries (not included). Convenience outlet required if not using batteries.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3060	Whiteboard, Projection Screen Combination	1	VV	Whiteboard and projection screen combination approximately 48" H x 72" W. Magnetic surface with matte finish for projection. Hard board stabilizer with aluminum foil back. For use with water color pens.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.

CARDIOVASCULAR LABORATORY SERVICE (210) - Contents - VA PG-18-5 (18 Jul 2016 04:49PM ET)

M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.