BACK-UP WALL (CMU, CONCRETE, OR STEEL STUD) AND STRUCTURE. EXTERIOR GRADE (GLASS-MAT FACED SHOWN) SHEATHING (NOT APPLICABLE FOR CMU AND CONCRETE BACK-UP WALLS). ALL JOINTS SEALED WITH SELF-ADHESIVE COMPATIBLE MEMBRANE PRODUCT WALL DRAINAGE PLANE PRODUCT METAL PANEL CLADDING SELF-ADHERED FLEXIBLE MEMBRANE FLASHING INSTALLED OVER CORROSION-RESISTANT, CONTINUOUS METAL FLASHING. SECURE TOP EDGE WITH CONTINUOUSLY SEALED TERMINATION BAR. TREAT ALL JOINTS AND EDGES PER MANUFACTURER REQUIREMENTS (MASTIC OR OTHER REQUIRED PRODUCT) AND OVERLAP ALL JOINTS A MINIMUM OF 2-INCHES MORE THAN THAT REQUIRED BY THE MANUFACTURER CORROSION-RESISTANT METAL FLASHING RIGID OR OTHER MOISTURE TOLERANT INSULATION SEALANT JOINT CONCEPTUAL - NOT FOR CONSTRUCTION

KEY CONCEPTS:

The dimensions and material relationships shown in this detail are **not to scale** and have been exaggerated for clarity. Actual dimensions will vary, and should be carefully coordinated with sequencing and construction tolerances to ensure the long-term durability and performance of this and similar exterior wall details.

Interface conditions between building envelope materials, components and systems should be fully detailed in a manner that is both technically sound and serviceable. Detailing should, at a minimum, allow for coordination of drainage planes when two or more different wall types are used in the same facade; allow for thermal and moisture-induced changes in material properties and differential thermal movement; and allow for in-service deflection, shrinkage, creep and similar behavior considered to be within the allowable structural limits of the project without compromise to the weather-tight integrity and thermal performance of the building envelope.

The air barrier can either be formed by employing the interior side airtight drywall approach or an exterior side air barrier.

The location of or need for a vapor retarder within wall assemblies will vary based upon climate, and can be significantly influenced by the storage capacity and vapor permeance of the materials selected for each layer of the wall system. A climate-specific, hygrothermal analysis for any wall assembly should be considered to further evaluate this concern.

See the General section of the WBDG for additional information and guidance.

METAL PANEL THROUGH-WALL FLASHING -OVERALL DETAIL

The details, graphics and related information shown above are intended to illustrate basic design concepts and principles only and should be considered collectively with the appropriate narrative sections of the Whole Building Design Guide (WBDG). The information contained herein is not intended for actual construction, and is subject to revision based on changes and/or refinements in local, state and national building codes, emerging building envelope technologies, and advancements in the research and understanding of building envelope failure and failure mechanisms. The actual design and configuration of these and similar details will vary based upon applicable local, state and national building code requirements, climatic considerations, and economic constraints unique to each project. Full compliance with the manufacturer's recommendations and recognized industry standards for each building envelope material, component and system specified for this and similar exterior wall assemblies is recommended, and should be reflected in the appropriate sections of the project specifications.